Oiltight Enclosures

Construction:

- Fabricated in accordance with UL specifications from 14 gauge steel.
- Neoprene gasket attached to cover with oil resistant adhesive.
- Stainless steel external screw clamps on three sides.
- Stainless steel continuous hinge.

- Continuously welded seams ground smooth.
- External mounting feet.
- Enclosures that are 6x4x3 and over are provided with stand-offs for mounting optional panel.

A+1.50 SECTION Y-Y 12x10 12x12

Finish:

Austin JIC Continuous Hinge NEMA 4 boxes are provided standard with an ANSI 61 gray polyester powder coating. Optional panels are painted white.

Options:

- Special materials.
- Special finishes.
- Custom box size or construction.
- Hasp for padlocking.

STANDARDS

UL 50 Type 4, 12 & 13 UL 508 Type 4, 12 & 13 NEMA Type 4, 12 & 13 CUL Type 4, 12 & 13

Austin Electrical Enclosures Post Office Box 2320 Yadkinville, NC 27055

Phone: 336.468.2851 800.288.2851

Catalog Number	Enclosure Size (AxBxC)	Weight	Panel Catalog Number
AB-443JFH	4x4x3	2	NA
AB-643JFH	6x4x3	3	AB-64JP
AB-863.5JFH	8x6x3 1/2	6	AB-86JP
AB-664JFH	6x6x4	4	AB-66JP
AB-1084JFH	10x8x4	9	AB-108JP
AB-12105JFH	12x10x5	13	AB-1210JP
AB-10106JFH	10x10x6	11	AB-1010JP
AB-12126JFH	12x12x6	15	AB-1212JP
AB-14126JFH	14x12x6	17	AB-1412JP
AB-16146JFH	16x14x6	20	AB-1614JP



Phone: 336.468.2851

800.288.2851