

PRODUCT DATA SHEET

Double-sectioned Wallmount Cabinet Star Series

Feature:

- Double -section wallmount cabinet.
- Tempered glass front door with 180° turning radius rotatable key lock.
- Removable side and rear panels for quick installation of equipment.
- Adjustable front and rear mounting posts conform to different equipment depth requirements. Dual mounting post with #12-24 threaded holes and square holes for cage nuts.
- Ventilated door design for added air flow and cooling.
- Cable entry brush panel on the top cover and knock-outs on the bottom plate.
- Provided with 1 fans with UL cord installed. Additional fan may be provided upon request.
- Easy to wall mount back plate.
- Available in heights from 6u to 23u.
- Fully assembled for quick installation and packaged in a honeycomb carton. aOptional space saving flat packaging available upon request.



Standards:

Complies with ANSI/EIA RS-310-D, IEC297-2, DIN41491; PART1, DIN41494; PART7, GB/3047.2-92 standards, UL certified

Material:

SPCC Cold Rolled Steel.

Static Loading Capacity:

NTDWC6U600: 70 kgs
NTDWC9U600: 70 kgs
NTDWC12U600: 75 kgs
NTDWC16U600: 80 kgs
NTDWC20U600: 90 kgs
NTDWC23U600: 95 Kgs

Degree of Protection:

Ip20

Thickness of Steel :

Mounting post: 1.5mm, frame: 1.2mm, back panel: 1.5mm, front door frame: 1.2mm,
Others: 1.0mm



Surface treatment:

Degreasing, pickling, phosphoric treatment, powder spraying

Colors option:

RAL9004/9005 BLACK; Standard Stocking Color
RAL7035 COMPUTER GRAY; Special Order. Lead times may vary.
RAL9010 CREAM WHITE; Special Order. Lead times may vary.

Ordering Information:

| Specifications | | | | | AWG | | | |
|----------------|----|--------|-------|-----------|-----------|------------|--------------|-------------|
| Part Number | RU | Format | Depth | Structure | Top Panel | Front Door | Bottom Panel | Side Panels |
| NTDWC6U600 | 6 | 19" | 23" | 20 | 20 | 20 | 20 | 16 |
| NTDWC9U600 | 9 | 19" | 23" | 20 | 20 | 20 | 20 | 16 |
| NTDWC12U600 | 12 | 19" | 23" | 20 | 20 | 20 | 20 | 16 |
| NTDWC16U600 | 16 | 19" | 23" | 20 | 20 | 20 | 20 | 16 |
| NTDWC20U600 | 20 | 19" | 23" | 20 | 20 | 20 | 20 | 16 |
| NTDWC23U600 | 23 | 19" | 23" | 20 | 20 | 20 | 20 | 16 |

