

Model #: SRW6U

SmartRack 6U Wall-Mount Rack Enclosure Cabinet



Highlights

- Designed for VoIP closets and education environments where equipment needs to be secure and out of the way
- 6U with adjustable front vertical rackmount rails
- Locking, reversible front door and locking, removable side panels
- Fully assembled for quick installation
- Meets all enclosure requirements towards PCI DSS (Payment Card Industry Data Security Standard) Compliance

Description

The SRW6U 6U Wall-Mount Rack Enclosure Cabinet is designed to integrate wall-mounting, easy equipment access, and cable management in IT network applications with limited floor space. Ventilated front door and side panels allow generous airflow to keep equipment operating safely. Adjustable rack rails with square mounting holes accommodate up to 6U of standard 19" rackmount equipment. Supports up to 200 lbs of equipment. A sturdy wall-mount bracket allows the cabinet to quickly be hung on the wall.

Applications

IT network environments with limited floor space, VoIP closets, and classrooms where equipment needs to be secure and out of the way of students.

Package Includes

- SRW6U Wallmount Rack Enclosure
- (12) M6 screws
- (12) M6 cage nuts
- (12) M6 washers
- (2) Keys
- Owner's Manual

Features

- 6U wall-mounted enclosure
- Ideal for VoIP wiring closets and education venues that require security
- Adjustable mounting depths up to 17" by 2 front vertical rackmount rails
- Ventilated front door and side panels for increased airflow
- · Locking, reversible front door
- Locking, removable side panels
- Fully assembled for quick installation
- Meets all enclosure requirements towards PCI DSS (Payment Card Industry Data Security Standard) Compliance

Specifications

PHYSICAL		
Installed whole system maximum rack depth (inches)	16.5	

Installed whole system maximum rack depth (cm)	41.9
Installed whole system minimum rack depth (inches)	3
Installed whole system total rack space height (rack spaces)	6U
Shipping weight (lbs)	32
Shipping weight (kg)	14.5
Shipping Dimensions (HWD/in)	17.5" x 26.5" x 20.5"
Shipping Dimensions (HWD/cm)	44.45 x 67.31 x 52.07
Unit weight (Ibs)	29
Unit weight (kg)	13
Unit Dimensions (cm)	11.43 x 60.02 x 44.45
Unit Dimensions (in)	EXTERNAL DIMENSIONS: 14.5" x 23.63" x 17.5" (HWD)
Color	Black
Weight Capacity - Stationary (Ibs)	200
Weight Capacity - Stationary (kg)	90.7
Cable Access Hole Measurement (inches)	9.812 x 2.35 (l x w)
SPECIAL FEATURES	
Grounding lug	Front and Back door frames
CERTIFICATIONS	
Certifications	EIA-310-E
NOM (Mexico)	Tested to NOM (Mexico)
Approvals	RoHS
WARRANTY	
Product Warranty Period (Worldwide)	5-year limited warranty

Related Items

Optional Products

Related Model	Description	Qty.
SRFANWM	Wall-Mount Roof Fan Kit, 120V (2 high-performance fans; 5-15P plug)	1
SRSHELF2P1U	1U Cantilever Fixed Shelf (40 lb / 18 kg capacity; 12-in. / 305 mm depth.)	1
UPSHDEARKIT	Heavy-Duty Mounting Ear Kit - Supports 2U cabinets up to 65 lb / 29 kg from front vertical rails in 4-post or 2-post racks and enclosures.)	1
SRSWITCH	Magnetic Door Switch Kit for front and rear doors; requires ENVIROSENSE	1

SRCASTER	Heavy-Duty Rolling Caster Kit (Includes 4 casters. Casters are included with 48/42/25U enclosures.)	1
N252-012	12-Port Cat6 Patch Panel 568B, 1U	1
N252-024	24-Port Cat6 Patch Panel 568B, 1U	1
N252-048	48-Port Cat6 Patch Panel 568B	1
SRCAGENUTS	Square Hole Hardware Kit (Includes 50 M6 screws and washers.)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=4606.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.