

- ▶ Solid One-Piece Copper Connector made from Extruded or Stamped Electrolytic Copper for Superior Mechanical Strength and Excellent Electrical Performance
- ▶ Steel Slotted or Allen-Head Screw
- ▶ Suitable for use with Copper wire only
- ▶ Rated 600V




Dimensions = Inches

Cat. No.	Fig	Wire Range	Bolt Size	Dimensions			Pad Thickness	Screw Type	Box Qty
				Length	Width	Height			
<b>Extruded Copper - Straight Tang</b>									
90560	1	6 - 14	1/4-28	1.020	.40	.375	3/32"	1/4" Hex Head	100
90562	1	4 - 14	1/4-28	1.075	.44	.45	3/32"	1/4" Hex Head	100
90564	1	2 - 14	5/16-24	1.125	.48	.458	1/8"	1/4" Hex Head	50
90566	1	1/0 - 14	7/16-20	1.277	.66	.548	1/8"	1/4" Hex Head	50
90568	1	4/0 - 2	5/8-18	1.950	.95	.812	7/32"	1/4" Hex Head	10
90593	2	350 MCM - 6	.56	2.00	1.92	1.12	3/16"	5/16" Hex Head	15
<b>Copper - Straight &amp; Round Tang</b>									
90506	3	6—14	1/4-28	1.02	.40	.375	1/16	Slotted	100
90507	3	4 - 14	5/16-24	1.075	.444	.45	3/32	Slotted	100
90550	4	8 - 14	3/16	13/16	3/8	3/8	5/64	Slotted	100
90552	4	4 - 14	1/4	1-1/8	1/2	3/32	3/32	Slotted	100
90554	4	1/0 - 8	5/16	1 1/2	3/4	3/4	3/32	1/4" Hex Head	50
90556	4	250 MCM - 6	3/8	1-15/16	15/16	1-1/16	1/8	1/4" Hex Head	25

## Copper Mechanical Off-Set Lugs

- ▶ Manufactured from High Strength Pure Electrolytic Copper to insure both Maximum Strength and Conductivity
- ▶ Arched Pressure bar and V-bottom collar positions the wire for Positive Contact and Maximum Reliability
- ▶ Steel Plated Screws/Bolts prevent rusting
- ▶ Easy to Install with screwdriver, wrench or pliers
- ▶ Copper Finish
- ▶ Rated 600 Volts



Dimensions = Inches

Cat. No.	Fig	Amp Rating	Wire Range	Length	Width	Height	Hole Size	Box Qty
<b>Single Conductor Off-Set</b>								
90514	1	35A	6 - 14	1.19	0.38	0.5	0.25	100
90515	1	70A	4 - 14	1.31	0.50	0.56	0.28	100
90516	1	90A	2 - 12	1.55	0.50	.65	0.34	50
90518	1	125A	1/0 - 8	1.97	0.63	.88	0.28	50
90520	1	175A	3/0 - 4	2.19	0.75	1.03	0.50	25
90522	1	225A	4/0 - 6	2.38	1.00	1.17	0.56	25
90524	1	300A	350 MCM - 1/0	3.16	1.00	1.39	0.94	18
90526	1	400A	500 MCM - 4/0	4.25	1.50	1.57	1.00	3
90528	1	650A	1000 MCM - 600 MCM	4.63	2.00	2.34	0.69	1
<b>Two Conductor Off-Set</b>								
90532	2	450A	4/0 - 2	3.38	1.50	.940	.41	6
90534	2	600A	350 MCM - 1/0	3.63	1.75	1.18	.41	6
90536	2	800A	500 MCM - 1/0	4.44	2.00	1.41	.53	3