According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 3.0

Revision Date: 02/16/2017

Print Date: 02/17/2017

# **SECTION 1. IDENTIFICATION**

Product name

: Shell Gadus S5 V460 1.5

Product code

: 001D8441

#### Manufacturer or supplier's details

Manufacturer/Supplier

: Shell Oil Products US

PO Box 4427

Houston TX 77210-4427

USA

SDS Request

(+1) 877-276-7285

**Customer Service** 

Emergency telephone number

Spill Information
Health Information

: 877-504-9351 : 877-242-7400

# Recommended use of the chemical and restrictions on use

Recommended use

: Automotive and industrial grease.

# **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Chronic aquatic toxicity

: Category 3

**GHS** label elements

Hazard pictograms

: No Hazard Symbol required

Signal word

: No signal word

Hazard statements

: PHYSICAL HAZARDS:

Not classified as a physical hazard under GHS criteria.

HEALTH HAZARDS:

Not classified as a health hazard under GHS criteria.

**ENVIRONMENTAL HAZARDS:** 

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

: Prevention:

P273 Avoid release to the environment.

Response:

No precautionary phrases.

Storage:

No precautionary phrases.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

# Other hazards which do not result in classification

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 3.0

Revision Date: 02/16/2017

Print Date: 02/17/2017

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used grease may contain harmful impurities.

High-pressure injection under the skin may cause serious damage including local necrosis. Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

: A lubricating grease containing polyolefins and additives.

#### Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (%)
Zinc dialkyl dithiophos- phate	Phosphorodithioic acid, O,O-di-C1-14- alkyl esters, zinc salts	68649-42-3	1 - 3
Calcium alkaryl sulphonate		Not Assigned	0.10 - 0.90
Alkyl amine		68955-53-3	0.01 - 0.099

# **SECTION 4. FIRST-AID MEASURES**

General advice

: Not expected to be a health hazard when used under normal

conditions.

If inhaled

No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

In case of skin contact

: Remove contaminated clothing. Flush exposed area with wa-

ter and follow by washing with soap if available.

If persistent irritation occurs, obtain medical attention.

When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait

for symptoms to develop.

Obtain medical attention even in the absence of apparent

wounds.

In case of eye contact

: Flush eye with copious quantities of water.

Remove contact lenses, if present and easy to do. Continue

rinsing.

If persistent irritation occurs, obtain medical attention.

If swallowed

: In general no treatment is necessary unless large quantities

are swallowed, however, get medical advice.

Most important symptoms and effects, both acute and delayed

: Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas.

Ingestion may result in nausea, vomiting and/or diarrhoea. Local necrosis is evidenced by delayed onset of pain and

2/15

800001029867

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 3.0

Revision Date: 02/16/2017

Print Date: 02/17/2017

tissue damage a few hours following injection.

Protection of first-aiders

: When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

Immediate medical attention, special treatment

: Treat symptomatically.

High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue dam-

age and loss of function.

Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthet-

ics, and wide exploration is essential.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media

: Foam, water spray or fog. Dry chemical powder, carbon diox-

ide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

: Do not use water in a jet.

Specific hazards during firefighting

: Hazardous combustion products may include:

A complex mixture of airborne solid and liquid particulates and

gases (smoke).

Carbon monoxide may be evolved if incomplete combustion

occurs.

Unidentified organic and inorganic compounds.

Specific extinguishing methods

: Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Special protective equipment for firefighters

: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in

a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

# **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures

Personal precautions, protec- : Avoid contact with skin and eyes.

Environmental precautions

: Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

 Version 3.0
 Revision Date: 02/16/2017
 Print Date: 02/17/2017

rivers by using sand, earth, or other appropriate barriers.

Methods and materials for containment and cleaning up

: Shovel into a suitable clearly marked container for disposal or reclamation in accordance with local regulations.

Additional advice

: For guidance on selection of personal protective equipment

see Chapter 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Chapter 13 of

this Safety Data Sheet.

# **SECTION 7. HANDLING AND STORAGE**

Technical measures : Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

material.

Precautions for safe handling

: Avoid prolonged or repeated contact with skin.

Avoid inhaling vapour and/or mists.

When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate-

rials in order to prevent fires.

Avoidance of contact

: Strong oxidising agents.

Storage

Other data

: Keep container tightly closed and in a cool, well-ventilated

place.

"Use properly labeled and closable containers.

Store at ambient temperature.

Packaging material

Suitable material: For containers or container linings, use mild

steel or high density polyethylene.

Unsuitable material: PVC.

Container Advice

Polyethylene containers should not be exposed to high tem-

peratures because of possible risk of distortion.

# SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

# Components with workplace control parameters

Contains no substances with occupational exposure limit values.

# Biological occupational exposure limits

No biological limit allocated.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 3.0

Revision Date: 02/16/2017

Print Date: 02/17/2017

# **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.isp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

#### **Engineering measures**

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

# General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Due to the product's semi-solid consistency, generation of mists and dusts is unlikely to occur.

### Personal protective equipment

Respiratory protection

: No respiratory protection is ordinarily required under normal conditions of use.

Version 3.0

Revision Date: 02/16/2017

Print Date: 02/17/2017

In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are sultable, select an appropriate combination of mask and filter.

Select a filter suitable for the combination of organic gases and vapours [Type A/Type P boiling point >65°C (149°F)].

Hand protection Remarks

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Eye protection

: If material is handled such that it could be splashed into eyes,

protective eyewear is recommended.

Skin and body protection

: Skin protection is not ordinarily required beyond standard

work clothes.

It is good practice to wear chemical resistant gloves.

Thermal hazards

: Not applicable

Protective measures

 Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

### Environmental exposure controls

General advice

: Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being dis-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 3.0

Revision Date: 02/16/2017

Print Date: 02/17/2017

charged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before

discharge to surface water.

Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing

vapour.

# SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

: Semi-solid at ambient temperature.

Colour

: light brown

Odour

: Slight hydrocarbon

**Odour Threshold** 

: Data not available

pН

: Not applicable

Drop point

: 260 °C / 500 °FMethod: IP 396

Initial boiling point and boiling

range

: Data not available

Flash point

: Not applicable

Evaporation rate

: Data not available

Flammability (solid, gas)

: Data not available

Upper explosion limit

: Typical 10 %(V)

Lower explosion limit

: Typical 1 %(V)

Vapour pressure

: < 0.5 Pa (20 °C / 68 °F) estimated value(s)

Relative vapour density

: > 1estimated value(s)

Relative density

: 0.900 (15 °C / 59 °F)

Density

: 900 kg/m3 (15.0 °C / 59.0 °F)

Method: Unspecified

Solubility(ies)

Water solubility

: negligible

Solubility in other solvents

: Data not available

Partition coefficient: n-

octanol/water

: Pow. > 6(based on information on similar products)

Auto-ignition temperature

: >

320 °C / 608 °F

7/15

800001029867

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 3.0

Revision Date: 02/16/2017

Print Date: 02/17/2017

Viscosity

Viscosity, dynamic

: Data not available

Viscosity, kinematic

: Not applicable

Explosive properties

: Not classified

Oxidizing properties

: Data not available

Conductivity

This material is not expected to be a static accumulator.

Decomposition temperature

: Data not available

# **SECTION 10. STABILITY AND REACTIVITY**

Reactivity

: The product does not pose any further reactivity hazards in

addition to those listed in the following sub-paragraph.

Chemical stability

: Stable.

Possibility of hazardous reac-

tions

: Reacts with strong oxidising agents.

Conditions to avoid

: Extremes of temperature and direct sunlight.

Incompatible materials

: Strong oxidising agents.

Hazardous decomposition

products

: Hazardous decomposition products are not expected to form

during normal storage.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

Basis for assessment

: Information given is based on data on the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

# Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

# **Acute toxicity**

# Product:

Acute oral toxicity

: LD50 (rat): > 5,000 mg/kg

Remarks: Expected to be of low toxicity:

Acute inhalation toxicity

: Remarks: Not considered to be an inhalation hazard under

normal conditions of use.

Acute dermal toxicity

: LD50 (Rabbit): > 5,000 mg/kg

Remarks: Expected to be of low toxicity:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 3.0

Revision Date: 02/16/2017

Print Date: 02/17/2017

# Skin corrosion/irritation

#### **Product:**

Remarks: Expected to be slightly irritating., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

#### Serious eye damage/eye irritation

#### **Product:**

Remarks: Expected to be slightly irritating.

#### Components:

Zinc dialkyl dithlophosphate:

Remarks: Based on available data, the classification criteria are not met.

#### Respiratory or skin sensitisation

#### **Product:**

Remarks: Not expected to be a skin sensitiser.

#### Components:

### Alkyl amine:

Remarks: May cause an allergic skin reaction in sensitive individuals.

# Germ cell mutagenicity

#### **Product:**

: Remarks: Not considered a mutagenic hazard.

# Carcinogenicity

# Product:

Remarks: Not expected to be carcinogenic.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcino-

gen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcino-

gen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 3.0

Revision Date: 02/16/2017

Print Date: 02/17/2017

# Reproductive toxicity

#### Product:

Remarks: Not expected to impair fertility., Not expected to be a developmental toxicant.

# STOT - single exposure

#### Product:

Remarks: Not expected to be a hazard.

# STOT - repeated exposure

#### Product:

Remarks: Not expected to be a hazard.

# Aspiration toxicity

#### **Product:**

Not considered an aspiration hazard.

#### **Further Information**

### **Product:**

Remarks: Used grease may contain harmful impurities that have accumulated during use. The concentration of such harmful impurities will depend on use and they may present risks to health and the environment on disposal., ALL used grease should be handled with caution and skin contact avoided as far as possible.

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Remarks: Slightly irritating to respiratory system.

# **SECTION 12. ECOLOGICAL INFORMATION**

Basis for assessment

: Ecotoxicological data have not been determined specifically

for this product.

Information given is based on a knowledge of the components

and the ecotoxicology of similar products.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).

**Ecotoxicity** 

Product:

Toxicity to fish (Acute toxici-

ty)

Remarks: Expected to be harmful:

LL/EL/IL50 10-100 mg/l

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 3.0

Revision Date: 02/16/2017

Print Date: 02/17/2017

Toxicity to daphnia and other

aquatic invertebrates (Acute toxicity)

Remarks: Expected to be harmful:

LL/EL/IL50 10-100 mg/l

Toxicity to algae (Acute tox-

icity)

Remarks: Expected to be harmful:

LL/EL/IL50 10-100 mg/l

Toxicity to fish (Chronic tox-

icity)

: Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

: Remarks: Data not available

Toxicity to bacteria (Acute

toxicity)

: Remarks: Data not available

# Persistence and degradability

#### Product:

Biodegradability

: Remarks: Expected to be not readily biodegradable.

Major constituents are expected to be inherently biodegradable, but contains components that may persist in the environ-

ment.

# **Bloaccumulative potential**

# Product:

Bioaccumulation

: Remarks: Contains components with the potential to bioac-

cumulate.

# Mobility in soil

### **Product:**

Mobility

: Remarks: Semi-solid under most environmental conditions.

If it enters soil, it will adsorb to soil particles and will not be

mobile.

Remarks: Floats on water.

#### Other adverse effects

no data available

# **Product:**

Additional ecological information

: Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities.

Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.

Poorly soluble mixture.

May cause physical fouling of aquatic organisms.

800001029867

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 3.0

Revision Date: 02/16/2017

Print Date: 02/17/2017

# **SECTION 13. DISPOSAL CONSIDERATIONS**

#### Disposal methods

Waste from residues

: Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods to the state of the sta

ods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.

Contaminated packaging

: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local legislation

Remarks

: Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

#### **SECTION 14. TRANSPORT INFORMATION**

### **National Regulations**

# US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

# International Regulations

#### **IATA-DGR**

Not regulated as a dangerous good

### IMDG-Code

Not regulated as a dangerous good

# Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category

Not applicable

Ship type

Not applicable
Not applicable

Product name

: Not applicable

Special precautions

# Special precautions for user

Remarks

 Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 3.0

Revision Date: 02/16/2017

Print Date: 02/17/2017

**Additional Information** 

: MARPOL Annex 1 rules apply for bulk shipments by sea.

#### **SECTION 15. REGULATORY INFORMATION**

**OSHA Hazards** 

: No OSHA Hazards

**EPCRA - Emergency Planning and Community Right-to-Know Act** 

# **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

# SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards

: No SARA Hazards

**SARA 302** 

: No chemicals in this material are subject to the reporting re-

guirements of SARA Title III, Section 302.

**SARA 313** 

: The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

Zinc dialkyl dithiophos-

68649-42-3

3 %

phate

### Clean Water Act

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

### **New Jersey Right To Know**

Zinc dialkyl dithiophosphate

68649-42-3

California Prop 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other re-

productive harm.

### The components of this product are reported in the following inventories:

**EINECS** 

; All components listed or polymer exempt.

**TSCA** 

: All components listed.

DSL

: All components listed.

#### **SECTION 16. OTHER INFORMATION**

#### Further information

NFPA Rating (Health, Fire, Reac- 0, 1, 0

tivity)

Version 3.0

Revision Date: 02/16/2017

Print Date: 02/17/2017

Due to the conversion of this product to GHS classification and labelling, there has been a significant change to the nature of the information presented in chapter 2.

A vertical bar (I) in the left margin indicates an amendment from the previous version.

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

> ACGIH = American Conference of Governmental Industrial Hygienists

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances

ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council

CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut für Normung

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial Chemical Substances

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

1L50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables

KECI = Korea Existing Chemicals Inventory

LC50 = Lethal Concentration fifty

LD50 = Lethal Dose fifty per cent.

LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading

LL50 = Lethal Loading fifty

MARPOL = International Convention for the Prevention of Pollution From Ships

NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level

OE HPV = Occupational Exposure - High Production Volume PBT = Persistent, Bioaccumulative and Toxic

PICCS = Philippine Inventory of Chemicals and Chemical

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 3.0

Revision Date: 02/16/2017

Print Date: 02/17/2017

Substances

PNEC = Predicted No Effect Concentration

REACH = Registration Evaluation And Authorisation Of

Chemicals

RID = Regulations Relating to International Carriage of Dan-

gerous Goods by Rail

SKIN\_DES = Skin Designation STEL = Short term exposure limit TRA = Targeted Risk Assessment

TSCA = US Toxic Substances Control Act

TWA = Time-Weighted Average

vPvB = very Persistent and very Bioaccumulative

**Revision Date** 

: 02/16/2017

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.