

MATERIAL SAFETY DATA SHEET

Trade Name: Johnsens Gas Treatment
MSDS NO. 4679
Revision Date: 05/25/2007
Date Printed: 12/30/2008

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name: Johnsens Gas Treatment
Chemical Family: PETROLEUM DISTILLATE
Synonyms: None
Emergency Telephone (24 hr.): CHEMTREC 1-800-424-9300

Supplier: Technical Chemical Company, P.O. Box 139, Cleburne, Texas 76033

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight %	OSHA TWA	OSHA STEL	OSHA SKIN
Solvent naphtha (petroleum), light aromatic 64742-95-6	.1-10	Not Listed	Not Listed	Not Listed
400/500 Base Solvent 64742-47-8	90-100	500 ppm	Not Listed	Not Listed

Component	Weight %	OSHA Z PEL	OSHA Z TWA	OSHA Z Ceiling
Solvent naphtha (petroleum), light aromatic 64742-95-6	.1-10	Not Listed	Not Listed	Not Listed
400/500 Base Solvent 64742-47-8	90-100	500 ppm	500 ppm	Not Listed

Component	ACGIH TLV TWA	ACGIH TLV STEL	ACGIH TLV Ceiling
Solvent naphtha (petroleum), light aromatic 64742-95-6	Not Listed	Not Listed	Not Listed
400/500 Base Solvent 64742-47-8	Not Listed	Not Listed	Not Listed

3. HAZARDS IDENTIFICATION

Emergency Overview: Warning! May cause delayed lung injury. Combustible Liquid and Vapor. Exposure to vapors can cause central nervous system depression, drowsiness, weakness, headache, dizziness, and nausea. Harmful if inhaled. Avoid breathing vapors. Avoid contact with skin and eyes. Keep away from heat, sparks, and flame.

HMIS Classification: Health: 2 Flammability: 2 Physical Hazard: 0
NFPA Rating: Health: 2 Flammability: 2 Reactivity: 0

4. FIRST AID MEASURES

Eye Contact: In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person. If victim is conscious and alert, give 1-2 glasses of water to drink. If vomiting occurs, keep head lower than hips to prevent aspiration.

Inhalation: If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin Contact: Remove contaminated clothing and shoes, and launder before reuse. Wash with soap and water. If irritation or rash develops, obtain medical assistance.

MATERIAL SAFETY DATA SHEET

Trade Name: Johnsens Gas Treatment
MSDS NO. 4679
Revision Date: 05/25/2007
Date Printed: 12/30/2008

5. FIRE FIGHTING MEASURES

Flammable Properties

Flash Point °F(°C): >155 F
Flash Point Method: TAG Closed Cup
Flammable Limits in Air - Lower (%): .7 vol %
Flammable Limits in Air - Upper (%): 6 vol %
Autoignition Temperature °F(°C): >550 F
Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam. Use water spray to keep containers cool that are exposed to heat or flames. Water stream may spread fire.

Protection Of Fire-Fighters:

Special Fire-Fighting Procedures: Wear approved positive-pressure self-contained breathing apparatus and protective clothing.
Hazardous Combustion Products: Oxides of Carbon. Fumes and Smoke. Oxides of Nitrogen.
Aerosol Comments: Not Applicable

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear appropriate protective clothing and equipment to prevent skin and eye contact.
Spill Procedures: Sweep or scrape up material and place in a suitable clean, dry container for disposal by approved methods.
Action to be taken if material is released or spilled: Remove sources of ignition. Increase area ventilation. Leaking containers should be removed to an isolated, well-ventilated area and transferred to other suitable containers.
Environmental Precautions: Do not allow to enter sanitary drains, sewer or surface and subsurface waters.

7. HANDLING AND STORAGE

Handling and Storage: Keep containers tightly closed when not in use. Keep away from heat and open flame. Wash thoroughly after handling. Use only with adequate ventilation. Avoid extreme temperatures. Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Exhaust ventilation. Showers. Eyewash stations.
Eyes: Wear safety glasses or goggles to protect against exposure. Chemical goggles; also wear a face shield if splashing hazard exists.
Skin Protection: Nitrile coated apron or clothing. Neoprene coated apron or clothing. Avoid skin contact. Wear protective clothing and gloves.
Respiratory Protection: Use an approved NIOSH organic vapor respirator below the TLV. If TLV is exceeded or overexposure is likely, use positive pressure or self contained breathing apparatus.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Colorless to light yellow liquid
Odor: KEROSENE
pH Value: Not Determined
Vapor Pressure: .00386 psia @ 68F
Vapor Density (Air=1): 6
Boiling Point (°F): >400F
Melting/Freezing Point: 25F
Solubility in Water: NEGLIGIBLE
Bulk Density at 20°C: Not Determined
Molecular Weight: Mixture
Specific Gravity (H2O=1): .803 @ 70F
Viscosity: >1.7 cst @ 40C
Evaporation Rate: Not Determined
VOC Content(%): 2.71 (CARB Method 310)
Decomposition Temperature: Not Known

MATERIAL SAFETY DATA SHEET

Trade Name: Johnsens Gas Treatment
MSDS NO. 4679
Revision Date: 05/25/2007
Date Printed: 12/30/2008

10. STABILITY AND REACTIVITY

Chemical Stability: Stable under normal conditions of handling, use and transportation.
Conditions to Avoid: Keep away from heat, sparks and flame. Do not expose to heat or store at temperatures above 120 F.
Materials to Avoid: Strong oxidizing agents.
Hazardous Decomposition Products: Carbon monoxide and other asphixiates.
Hazardous Polymerization: WILL NOT OCCUR

11. TOXICOLOGICAL INFORMATION

Toxicological Data:

Component	Route	Species	Dose
Solvent naphtha (petroleum), light aromatic 64742-95-6	Oral	Rats	LD50 8400 mg/kg
400/500 Base Solvent 64742-47-8	Inhalation	Rats	Not known.

Carcinogenicity:

Component	IARC	NTP	OSHA
Solvent naphtha (petroleum), light aromatic 64742-95-6	Not Listed	Not Listed	Not Listed
400/500 Base Solvent 64742-47-8	Not Listed	Not Listed	Not Listed

12. ECOLOGICAL INFORMATION

Remarks: Ecological testing has not been conducted on this product.

13. DISPOSAL CONSIDERATION

Waste Classification: Not determined.
Waste Management: Recovery and reuse, rather than disposal, should be the ultimate goal of handling efforts.
Disposal Method: Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION

U.S. DOT:

Proper Shipping Name: Consumer Commodity
Hazard Class: ORM-D
UN/NA Number: Not Applicable
DOT Packing Group: Not Applicable

IMDG:

Proper Shipping Name: Combustible Liquid, nos
Hazard Class: 3
Hazard Subclass: Not Determined
UN No.: 1993
Packing Group: III
Marine Pollutant: No

15. REGULATORY INFORMATION

US Federal Regulations:

MATERIAL SAFETY DATA SHEET

Trade Name: Johnsens Gas Treatment
 MSDS NO. 4679
 Revision Date: 05/25/2007
 Date Printed 12/30/2008

Component	SARA 313	SARA 302	TPQ	RQ
Solvent naphtha (petroleum), light aromatic 64742-95-6	Not Listed	Not Listed	Not Listed	Not Listed
400/500 Base Solvent 64742-47-8	Not Listed	Not Listed	Not Listed	Not Listed

SARA 311/312 Hazard Categories: Immediate/Acute, Delayed/Chronic, Fire

State Regulations:

Component	California Prop. 65 Cancer list	California - Prop 65 Developmental Toxicity	California Prop. 65 Reproductive Female	California Prop. 65 Reproductive Male
Solvent naphtha (petroleum), light aromatic 64742-95-6	Not Listed	Not Listed	Not Listed	Not Listed
400/500 Base Solvent 64742-47-8	Not Listed	Not Listed	Not Listed	Not Listed

U.S. TSCA: The components of this product are listed on the TSCA Inventory.
Canadian Inventory: The components of this product are listed on the Canadian DSL or NDSL Inventory.

Consumer Product Safety Improvement Act of 2008 General Conformity Certification

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product container.

16. OTHER INFORMATION

General Notes:
Disclaimer: Do not allow undiluted material or large quantities to reach groundwater, bodies of water or sewer system. The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.