

## Material Safety Data Sheet

### 1. MATERIAL AND COMPANY IDENTIFICATION

**Material Name** : Quaker State Ultimate Durability SAE 10W-30 Full Synthetic Motor Oil  
**Uses** : Engine oil.

**Manufacturer/Supplier** : SOPUS Products  
PO BOX 4427  
Houston, TX 77210-4427  
USA

**SDS Request** : 877-276-7285

**Emergency Telephone Number**  
**Spill Information** : 877-242-7400  
**Health Information** : 877-504-9351

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Identity	CAS No.	Concentration
Highly-refined mineral oils	64742-65-0	60.00 - 100.00 %

Synthetic base oil and additives.  
The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.  
The highly refined mineral oil is only present as additive diluent.

### 3. HAZARDS IDENTIFICATION

Emergency Overview	
<b>Appearance and Odour</b>	: Amber. Liquid at room temperature. Slight hydrocarbon.
<b>Health Hazards</b>	: Not classified as dangerous for supply or conveyance.
<b>Safety Hazards</b>	: Not classified as flammable but will burn.
<b>Environmental Hazards</b>	: Not classified as dangerous for the environment.

**Health Hazards** : Not expected to be a health hazard when used under normal conditions.

**Health Hazards**  
**Inhalation** : Under normal conditions of use, this is not expected to be a primary route of exposure.

**Skin Contact** : Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

**Eye Contact** : May cause slight irritation to eyes.

**Ingestion** : Low toxicity if swallowed.

**Other Information** : Used oil may contain harmful impurities.

**Signs and Symptoms** : Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas.

## Material Safety Data Sheet

<b>Aggravated Medical Conditions</b>	: Ingestion may result in nausea, vomiting and/or diarrhoea. : Pre-existing medical conditions of the following organ(s) or organ system(s) may be aggravated by exposure to this material: Skin.
<b>Environmental Hazards</b>	: Not classified as dangerous for the environment.
<b>Additional Information</b>	: Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

---

### 4. FIRST AID MEASURES

<b>General Information</b>	: Not expected to be a health hazard when used under normal conditions.
<b>Inhalation</b>	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
<b>Skin Contact</b>	: Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
<b>Eye Contact</b>	: Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
<b>Ingestion</b>	: In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
<b>Advice to Physician</b>	: Treat symptomatically.

---

### 5. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

<b>Flash point</b>	: Typical 226.66 °C / 439.99 °F (PMCC / ASTM D93)
<b>Upper / lower Flammability or Explosion limits</b>	: Typical 1 - 10 %(V)
<b>Auto ignition temperature</b>	: > 320 °C / 608 °F
<b>Specific Hazards</b>	: Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
<b>Suitable Extinguishing Media</b>	: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
<b>Unsuitable Extinguishing Media</b>	: Do not use water in a jet.
<b>Protective Equipment for Firefighters</b>	: Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.

---

### 6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe the relevant local and international regulations.

## Material Safety Data Sheet

- Protective measures** : Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
- Clean Up Methods** : Slippery when spilled. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
- Additional Advice** : Local authorities should be advised if significant spillages cannot be contained.

### 7. HANDLING AND STORAGE

- General Precautions** : Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
- Handling** : Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
- Storage** : Keep container tightly closed and in a cool, well-ventilated place. Use properly labelled and closeable containers. Store at ambient temperature.
- Product Transfer** : This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.
- Recommended Materials** : For containers or container linings, use mild steel or high density polyethylene.
- Unsuitable Materials** : PVC.
- Additional Information** : Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Occupational Exposure Limits

Material	Source	Type	ppm	mg/m3	Notation
Highly-refined mineral oils	OSHA Z1	PEL(Mist.)		5 mg/m3	
Highly-refined mineral oils	ACGIH	TWA(Inhalable fraction.)		5 mg/m3	

**Material Safety Data Sheet**

Highly-refined mineral oils	OSHA Z1	(Mist.)			Listed.
Oil mist, mineral	ACGIH	TWA(Inhalable fraction.)		5 mg/m3	
Oil mist, mineral	OSHA Z1	PEL(Mist.)		5 mg/m3	

**Biological Exposure Index (BEI)**

No biological limit allocated.

**Exposure Controls**

: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

**Personal Protective Equipment**

: Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

**Respiratory Protection**

: No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point >65°C(149 °F)].

**Hand Protection**

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a

## Material Safety Data Sheet

non-perfumed moisturizer is recommended.

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognise that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time may be acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material.

- Eye Protection** : Wear safety glasses or full face shield if splashes are likely to occur.
- Protective Clothing** : Skin protection not ordinarily required beyond standard issue work clothes.
- Monitoring Methods** : Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory. Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods <http://www.cdc.gov/niosh/>  
Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods <http://www.osha.gov/>  
Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances <http://www.hse.gov.uk/>  
Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany. <http://www.dguv.de/inhalt/index.jsp>  
L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

- Environmental Exposure Controls** : Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Amber. Liquid at room temperature.  
Odour : Slight hydrocarbon.  
pH : Not applicable.  
Initial Boiling Point and Boiling Range : > 280 °C / 536 °F estimated value(s)  
Pour point : Typical -36 °C / -33 °F

## Material Safety Data Sheet

Flash point	: Typical 226.66 °C / 439.99 °F (PMCC / ASTM D93)
Upper / lower Flammability or Explosion limits	: Typical 1 - 10 %(V)
Auto-ignition temperature	: > 320 °C / 608 °F
Vapour pressure	: < 0.5 Pa at 20 °C / 68 °F (estimated value(s))
Specific gravity	: Typical 0.856 at 15.6 °C / 60.1 °F
Density	: Typical 856 kg/m <sup>3</sup> at 15.6 °C / 60.1 °F
Water solubility	: Negligible.
n-octanol/water partition coefficient (log Pow)	: > 6 (based on information on similar products)
Kinematic viscosity	: Typical 60.96 cSt at 40 °C / 104 °F (ASTM D 445)
Vapour density (air=1)	: > 1 (estimated value(s))
Electrical conductivity	: This material is not expected to be a static accumulator.
Evaporation rate (nBuAc=1)	: Data not available

### 10. STABILITY AND REACTIVITY

<b>Stability</b>	: Stable.
<b>Conditions to Avoid</b>	: Extremes of temperature and direct sunlight.
<b>Materials to Avoid</b>	: Strong oxidising agents.
<b>Hazardous Decomposition Products</b>	: Hazardous decomposition products are not expected to form during normal storage.

### 11. TOXICOLOGICAL INFORMATION

<b>Basis for Assessment</b>	: Information given is based on data on the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
<b>Acute Oral Toxicity</b>	: Expected to be of low toxicity: LD50 > 5000 mg/kg , Rat
<b>Acute Dermal Toxicity</b>	: Expected to be of low toxicity: LD50 > 5000 mg/kg , Rabbit
<b>Acute Inhalation Toxicity</b>	: Not considered to be an inhalation hazard under normal conditions of use.
<b>Skin Irritation</b>	: Expected to be slightly irritating. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.
<b>Eye Irritation</b>	: Expected to be slightly irritating.
<b>Respiratory Irritation</b>	: Inhalation of vapours or mists may cause irritation.
<b>Sensitisation</b>	: Not expected to be a skin sensitiser.
<b>Repeated Dose Toxicity</b>	: Not expected to be a hazard.
<b>Mutagenicity</b>	: Not considered a mutagenic hazard.
<b>Carcinogenicity</b>	: Not expected to be carcinogenic.

Material	Carcinogenicity Classification
Highly refined mineral oil (IP346 <3%)	: ACGIH Group A4: Not classifiable as a human carcinogen.
Highly refined mineral oil (IP346 <3%)	: IARC 3: Not classifiable as to carcinogenicity to humans.

## Material Safety Data Sheet

Highly refined mineral oil (IP346 <3%)	:	GHS / CLP: No carcinogenicity classification
--	---	--

- Reproductive and Developmental Toxicity** : Not expected to be a hazard.
- Additional Information** : Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible. Continuous contact with used engine oils has caused skin cancer in animal tests.

---

## 12. ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

- Acute Toxicity** : Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l (to aquatic organisms) LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract.
- Mobility** : Liquid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile. Floats on water.
- Persistence/degradability** : Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.
- Bioaccumulation** : Contains components with the potential to bioaccumulate.
- Other Adverse Effects** : Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.

---

## 13. DISPOSAL CONSIDERATIONS

- Material Disposal** : Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses.
- Container Disposal** : Dispose in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

## Material Safety Data Sheet

**Local Legislation** : Disposal should be in accordance with applicable regional, national, and local laws and regulations.

---

### 14. TRANSPORT INFORMATION

#### US Department of Transportation Classification (49CFR)

This material is not subject to DOT regulations under 49 CFR Parts 171-180.

#### IMDG

This material is not classified as dangerous under IMDG regulations.

#### IATA (Country variations may apply)

This material is either not classified as dangerous under IATA regulations or needs to follow country specific requirements.

---

### 15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

#### Federal Regulatory Status

##### Notification Status

EINECS	All components listed or polymer exempt.
TSCA	All components listed.
DSL	All components listed or polymer exempt.

##### Comprehensive Environmental Release, Compensation & Liability Act (CERCLA)

Quaker State Ultimate Durability SAE 10W-30 Full Synthetic Motor Oil ( )	Reportable quantity: 83 lbs
---	-----------------------------

Zinc dialkyl dithiophosphate (84605-29-8)

Ethylene glycol (107-21-1)	Reportable quantity: 5000 lbs
----------------------------	-------------------------------



## Material Safety Data Sheet

Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.  
The components with RQs are given for information.

Under Section 311 of the Clean Water Act (CWA) this material is considered an oil. As such, spills into surface waters must be reported to the National Response Center at (800) 424-8802.

**SARA Hazard Categories (311/312)**  
No SARA 311/312 Hazards.

### SARA Toxic Release Inventory (TRI) (313)

Zinc dialkyl dithiophosphate (84605-29-8)  
Ethylene glycol (107-21-1)  
Diphenylamine (122-39-4)

### State Regulatory Status

#### California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

This material does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

#### New Jersey Right-To-Know Chemical List

Highly-refined mineral oils (64742-65-0)	Listed.
	Listed.
Zinc dialkyl dithiophosphate (84605-29-8)	Listed.
Ethylene glycol (107-21-1)	
	Listed.
Diphenylamine (122-39-4)	
	Listed.

#### Pennsylvania Right-To-Know Chemical List

Highly-refined mineral oils (64742-65-0)	Listed.
	Listed.
Ethylene glycol (107-21-1)	Environmental hazard.
	Listed.
Diphenylamine (122-39-4)	Environmental hazard.
	Listed.

---

## 16. OTHER INFORMATION

**Material Safety Data Sheet**

- NFPA Rating (Health, Fire, Reactivity)** : 0, 1, 0  
**SDS Version Number** : 1.1  
**SDS Effective Date** : 03/12/2013  
**SDS Revisions** : A vertical bar (|) in the left margin indicates an amendment from the previous version.  
**SDS Regulation** : The content and format of this MSDS is in accordance with the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
**SDS Distribution** : The information in this document should be made available to all who may handle the product.  
**Disclaimer** : The information contained herein is based on our current knowledge of the underlying data and is intended to describe the product for the purpose of health, safety and environmental requirements only. No warranty or guarantee is expressed or implied regarding the accuracy of these data or the results to be obtained from the use of the product.