

SAFETY DATA SHEET

Revision Date: 07/06/2017

Print Date: 8/2/2018 SDS Number: R0366793

Version: 1.3

Valvoline[™] SAE 5W-20 Motor Oil

797974

29 CFR 1910.1200 (OSHA HazCom 2012) SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

:

Product identifier

Trade name

Valvoline™ SAE 5W-20 Motor Oil

Relevant identified uses of the substance or mixture and uses advised against Recommended use : Motor Oil

/alvoline LLC	D-VALVOLINE (1-800-825-8654)
00 Valvoline Way	
	Ilatory Information Number
	D-TEAMVAL
Jnited States of America (USA)	
	uct Information
)-TEAMVAL

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS label elements

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	35.2137
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	6.9317



Revision Date: 07/06/2017

Version: 1.3

Valvoline[™] SAE 5W-20 Motor Oil

SAFETY DATA SHEET

797974

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	Asp. Tox. 1; H304	1.6633	
---	------------	-------------------	--------	--

SECTION 4. FIRST AID MEASURES General advice : No hazards which require special first aid measures. If inhaled : If breathed in, move person into fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician. In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water. In case of eye contact : Remove contact lenses. Protect unharmed eye. If swallowed : Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. : Acute aspiration of large amounts of oil-laden material may Most important symptoms produce a serious aspiration pneumonia. Patients who and effects, both acute and aspirate these oils should be followed for the development of delayed long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities. Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: acne stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways) Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES



SAFETY DATA SHEET	Revision Date: 07/06/201
	Print Date: 8/2/201
	SDS Number: R036679
Valvoline™ SAE 5W-20 Motor Oil	Version: 1
797974	

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	carbon dioxide and carbon monoxide Hydrocarbons nitrogen oxides (NOx)
Specific extinguishing methods	:	
		Product is compatible with standard fire-fighting agents.
Further information	:	Standard procedure for chemical fires.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.	d
Environmental precautions	: Prevent further leakage or spillage if safe to do so.	
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.	
Other information	: Comply with all applicable federal, state, and local regulations	3.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8.
Materials to avoid	: No materials to be especially mentioned.



SAFETY DATA SHEET	Revision Date: 07/06/2017
	Print Date: 8/2/2018
	SDS Number: R0366793
Valvoline™ SAE 5W-20 Motor Oil	Version: 1.3
797974	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
F		(Form of	parameters /	
		exposure)	Permissible	
		expected by	concentration	
The identity and concentration o	f one or more co	omponent(s) is t	eing withheld under b	usiness
confidentiality.		,	Ū	
HYDROTRÉATED LIGHT	64742-55-8	TWA	5 mg/m3	OSHA Z-1
PARAFFINIC DISTILLATE			Mist	
		TWA	5 mg/m3	ACGIH
			Inhalable fraction	
		TWA	5 mg/m3	OSHA P0
			Mist	
		TWA	5 mg/m3	NIOSH REL
			Mist	
		ST	10 mg/m3	NIOSH REL
			Mist	
		PEL	5 mg/m3	CAL PEL
			particulate	

Hazardous components without workplace control parameters

Components	CAS-No.
Engineering measures	General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.
Personal protective equipment	
Respiratory protection :	No personal respiratory protective equipment normally required.
Eye protection :	Not required under normal conditions of use. Wear splash- proof safety goggles if material could be misted or splashed into eyes.
Skin and body protection :	Wear as appropriate: Safety shoes Wear resistant gloves (consult your safety equipment supplier).
Hygiene measures :	General industrial hygiene practice.



Page: 5

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Odour	: No data available
Odour Threshold	: No data available
рН	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: > 390 °F / > 199 °C Method: Cleveland open cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 6 %(V) Calculated Explosive Limit
Lower explosion limit	: 1 %(V) Calculated Explosive Limit
Vapour pressure	 Calculated Explosive Limit 0.0012 hPa (20 °C) Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.8620 g/cm3 (15.56 °C)
Solubility/icc)	
Solubility(ies) Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n- octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity Viscosity, dynamic	: No data available
Viscosity, kinematic	: 50 mm2/s (40 °C)



SAFETY DATA SHEET

Print Date: 8/2/2018

Revision Date: 07/06/2017

797974

Oxidizing properties

Valvoline[™] SAE 5W-20 Motor Oil

: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: excessive heat
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	carbon dioxide and carbon monoxide Hydrocarbons Nitrogen oxides (NOx)

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	: Inhalation Skin contact Eye Contact Ingestion	
Acute toxicity		
Not classified based on availabl <u>Components:</u>	e information.	
Distillates (Petroleum), Hydrotre	ated Heavy Paraffinic:	
Acute oral toxicity	: LD50 (Rat): > 15 g/kg	
Acute dermal toxicity	: LD50 (Rabbit): > 5 g/kg	
DISTILLATES (PETROLEUM), Acute oral toxicity	SOLVENT-DEWAXED HEAVY PARAFFINIC: : LD50 (Rat): > 5,000 mg/kg	
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg	
Skin corrosion/irritation Not classified based on availabl <u>Components:</u> Distillates (Petroleum), Hydrotre Result: Slight, transient irritation	ated Heavy Paraffinic:	

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:





Revision Date: 07/06/2017

Print Date: 8/2/2018 SDS Number: R0366793

Version: 1.3

Valvoline[™] SAE 5W-20 Motor Oil

SAFETY DATA SHEET

797974

Result: Slight, transient irritation

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC: Result: Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information. Product: Remarks: Unlikely to cause eye irritation or injury.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic: Result: No eye irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE: Result: Slight, transient irritation

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC: Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information. Germ cell mutagenicity Not classified based on available information. Carcinogenicity Not classified based on available information. **Reproductive toxicity** Not classified based on available information. STOT - single exposure Not classified based on available information. **STOT - repeated exposure** Not classified based on available information. Aspiration toxicity Not classified based on available information. Product: No aspiration toxicity classification

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic: May be fatal if swallowed and enters airways.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE: May be fatal if swallowed and enters airways.

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC: May be fatal if swallowed and enters airways.

Further information <u>Product:</u> Remarks: No data available



SAFETY DATA SHEETRevision Date: 07/06/2017Print Date: 8/2/2018Print Date: 8/2/2018Valvoline™ SAE 5W-20 Motor OilVersion: 1.3797974Version: 1.3

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity <u>Product:</u> Ecotoxicology Assessment Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.
<u>Components:</u> Distillates (Petroleum), Hydroti Toxicity to fish		ted Heavy Paraffinic: LL50 (Fish): > 100 mg/l
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Aquatic invertebrates): > 10,000 mg/l
Toxicity to algae	:	EL50 (Algae, algal mat (Algae)): > 100 mg/l
Toxicity to fish (Chronic toxicity)	:	NOEC (Fish): 10 mg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Aquatic invertebrates): 10 mg/l
Persistence and degradabilit <u>Components:</u> No data available Bioaccumulative potential <u>Components:</u> No data available Mobility in soil <u>Components:</u> No data available Other adverse effects No data available <u>Product:</u> Additional ecological		No data available
	•	INU UALA AVAIIAULE

Components:

information

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice

: Dispose of in accordance with all applicable local, state and federal regulations.



Page: 9

797974

Contaminated packaging

: Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	------------------	-----------------------	------------------	------------------------------------

MX_DG

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

TDG_INWT_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - ROAD

Not dangerous goods



SAFETY DATA SHEET	Revision Date: 07/06/2017
	Print Date: 8/2/2018
	SDS Number: R0366793
Valvoline™ SAE 5W-20 Motor Oil	Version: 1.3
797974	

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
TOLUENE	108-88-3	1000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	:	No SARA Hazards
SARA 313		This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
California Prop 65		Proposition 65 warnings are not required for this product based on the results of a risk assessment.
• •		All components of this product are on the Canadian DSL
AICS	:	On the inventory, or in compliance with the inventory
ENCS	:	Contact your sales representative for additional information.
KECI	:	On the inventory, or in compliance with the inventory
IECSC	:	Contact your sales representative for additional information.
PICCS	:	On the inventory, or in compliance with the inventory
TSCA	:	On TSCA Inventory

Inventories


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

Valvoline.	Page: 11
SAFETY DATA SHEET	Revision Date: 07/06/2017
	Print Date: 8/2/2018
	SDS Number: R0366793
Valvoline™ SAE 5W-20 Motor Oil	Version: 1.3
797974	

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 07/06/2017



NFPA Flammable and Combustible Liquids Classification Combustible Liquid Class IIIB

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction



Revision Date: 07/06/2017

Print Date: 8/2/2018 SDS Number: R0366793 Version: 1.3

Valvoline™ SAE 5W-20 Motor Oil

SAFETY DATA SHEET

797974

FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization" IMDG : International Maritime Code for Dangerous Goods ISO : International Organization for Standardization logPow : octanol-water partition coefficient LCxx : Lethal Concentration, for xx percent of test population LDxx : Lethal Dose, for xx percent of test population. ICxx : Inhibitory Concentration for xx of a substance Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified OECD : Organization for Economic Co-operation and Development **OEL** : Occupational Exposure Limit P-Statement : Precautionary Statement PBT : Persistent, Bioaccumulative and Toxic **PPE : Personal Protective Equipment** STEL : Short-term exposure limit STOT : Specific Target Organ Toxicity TLV : Threshold Limit Value TWA : Time-weighted average vPvB : Very Persistent and Very Bioaccumulative WEL : Workplace Exposure Level CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act DOT : Department of Transportation FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act HMIRC : Hazardous Materials Information Review Commission HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System