

Specsheet

SW 8x5/3 Stainless Steel General Purpose Trolley 3 shelves 800x500



Image example, technical changes reserved, without decoration.

Article-code:	0111962
Number of shelves:	3
Shelf dimensions in mm:	800 x 500 mm
Load per unit area / shelf:	40 kg
Working height between shelves in mm:	278 mm
Height of top shelf in mm:	851 mm
Chassis:	4 swivel castors, 2 of them with brake, Ø 125 mm
Total load capacity:	120 kg
Net weight:	17,8 kg
External dimensions W x D x H in mm:	895 x 595 x 960 mm

The serving trolleys are manufactured from high-quality stainless steel.

Rugged construction made from two tubular steel bar push handles, Ø 25 mm, with welded deep drawn shelves with elevated perimeter flange in-between. Deposit surface with large radii for easy cleaning, lowered by approx. 10 mm in contrary to the perimeter flange.

Shelves are bevelled by 35 mm allover, with flat safety return to the inside and sound absorbing lining. The trolley is protected from damage by four disc bumpers which are fixed directly above the castors. Disc bumpers are made from elastic and shock resistant plastic material. If necessary they can be exchanged easily by releasing the castors.

Corrosion-protected and maintenance-free castors. Housings made from zinc-chrome plated steel, solid castor made from impact-proof, accident grease-proof plastic, tyres from thermoplastic rubber. High-grade bearing by slide-bearings. 4 swivel castors, Ø 125 mm, 2 with brake.

If necessary the castors can be exchanged easily, pin fixing.

Optionally and for additional price the trolleys can also be equipped with 2 fixed and 2 swivel castors.