



Product Code: FS90 27-108

Air cooled standard Ice Cuber



Features & Benefits

FS90

- Innovatively designed with new user-friendly electro-mechanical controls to ensure reliability
- The models also incorporate a condenser thermostat, which ensures a full harvest of cubes
- Produces ultra cold square cubes that last longer in the glass, ice bucket and the machine's storage bin
- Uses as little as 5 litres of water to produce 1 kilo of ice - important where water is metered.
- The new flush system ensures clear ice free from impurities and eliminates the risk of lime-scale
- Bin capacity: 42kgs
- Ice: Cubed 35x37x32mm

Base Fittings

Adjustable leg set Option

Product Extras

Condensate pump Option

Refrigeration

Ice bin type Integral

R134a - Industry Standard Standard

Drain Rqd 20mm

Specification

Air cooled ice maker Standard

Width (mm) 700

Depth (mm) 580

Height (mm) 995

Cubes - 37 x 35 x 32mm Standard

KG per 24 hours 82

Electrical & Service Data

230/50/1 Standard

Finish

Stainless steel Standard

Footnotes

- Output figures quoted are based on 10°C water input and ambient air temp of 21°C
- Dimensions: Legs provided as standard to increase height for drainage where required - 120cm maximum height increase
- Note: A minimum clearance of 15cm (6") must be left at the sides of the machine for routing cooling air drawn into and exhausted out of the compartment to maintain a proper condensing operation
- Maximum ambient air temperature 40°C; maximum input water temperature 35°C
- Everpure filter, cartridge and head kit available as an option
- Everpure water filter and ION clean installation kit available as an option



Energy



Quality



Value



Design



Hygiene



After Care

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU

Phone 08432 168800 | Email sales@foster-uk.com | Visit www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.