

# GBK Bench Check Weighing Scales



## Speed, Performance, Value - The Right Balance

- 3 Weighing units (g, lb, oz)
- Adjustable filters
- Memory accumulation
- Easy to use keypad
- Date and time
- Full range tare
- Tare function
- Check-weighing with low and high limits
- Check weighing LED bar graph
- Large backlit LCD display
- Capacity tracker
- Non-slip adjustable feet
- Overload protection
- Grade 304 stainless steel pan
- Colour coded, sealed keypad
- Full colour coded keypad with numeric entry
- Simple user-friendly operation
- Splashproof to protect from accidental spills
- Precision load cell technology
- Internal counting resolution 1:400,000
- Easy access to the rechargeable battery
- RS-232 bi-directional interface
- Rechargeable battery up to 90 hours operation
- Auto sleep / power down function to save battery life
- Zero adjust facility to enable zero reading
- Low battery indication
- AC Adapter
- Weighing
- Parts counting
- Percentage weighing
- Animal / dynamic weighing
- Check weighing
- Check counting



## Technical Specifications

Model	GBK 8	GBK 16	GBK 32	GBK 60	GBK 120
Maximum capacity	8000g	16kg	32kg	60kg	120kg
Readability	0.1g	0.5g	1g	2g	5g
Repeatability (S.D.)	0.2g	1g	2g	1g	4g
Linearity (±)	0.3g	1g	2g	1g	4g
Units of measurement	Gram (g), Kilogram (kg)				Kilogram (kg)
Pan size	300x400mm				

## General Specifications

Typical stabilisation time	2-3 Sec
Housing	ABS Plastic Indicator and Stainless Steel Pan
Overall dimensions (wxdxh)	300x520x680mm
Net weight	7.6kg

## Key Accessories

- RS-232 to USB Interface Cable (must be ordered with 30740102)
- RS-232 to PC Cable
- AdamDU - Data Collection Program
- Adam Printer
- Thermal Paper Roll for Adam Printer
- In-use Cover
- ATP Thermal Printer
- Thermal Paper for ATP



**Adam Equipment - offices worldwide**

Pneutrol International Ltd, 5 Caulside Drive, Antrim, Northern Ireland, BT41 2DU  
 www.pneutrolspares.com, sales@pneutrol.com, Tel: +44 (0) 28 9448 1800