



Speed, Performance, Value - The Right Balance

- 5 weighing units (kg, g, lb, oz, lb:oz)
- Full range tare
- Zero Tracking
- Simple user-friendly operation
- Large backlit LCD display
- Non-slip adjustable levelling feet
- Overload protection
- Colour coded, sealed keypad
- Large stainless steel pan
- Modern low profile design
- Precision load cell technology
- Splashproof to protect from accidental spills
- External calibration
- Rechargeable battery up to 150 hours operation
- Auto sleep / power down function to save battery life
- Low battery indication
- Mains Power Cord
- Weighing
- Parts counting
- Percentage weighing



Technical Specifications


Model	LBK 3	LBK 6	LBK 12	LBK 30
Maximum capacity	3000g	6000g	12kg	30kg
Readability	0.5g	1g	2g	5g
Repeatability (S.D.)	0.5g	1g	2g	5g
Linearity (\pm)	1g	2g	4g	10g
Pan size	250x180mm			

General Specifications

Typical stabilisation time	2 Sec
Units of measurement	Gram (g), Kilogram (kg), Pound (lb), Ounce (Oz), Pound-Ounce (lb-oz)
Operating temperature	0° - 40°C
Power supply	Mains power cord / internal rechargeable battery
Calibration	Automatic External
Display	Green backlit LCD display with 6 digits
Housing	ABS plastic with stainless steel platform
Overall dimensions (wxdxh)	250x307x110mm
Net weight	1.8kg

Key Accessories

- In-use Cover
- In-Use Cover pack of 5
- In-Use Cover pack of 10



Adam Equipment - offices worldwide

Pneutrol International Ltd, 5 Caulside Drive, Antrim, Northern Ireland, BT41 2DU
 www.pneutrolspares.com, sales@pneutrol.com, Tel: +44 (0) 28 9448 1800