GE Digital Energy

MDS PulseNET[™]

Network Management Software

Monitoring and managing the health of your network is a critical and up-front consideration when designing, purchasing, and deploying equipment for your communications system. Equally important is ensuring that you maximize your network's return on investments by increasing system throughput and uptime, improving the utilization of networked devices, and finally, supporting the deployment of maintenance resources when problems surface.

MDS PulseNET Network Management Software was designed specifically for MDS Industrial communication systems and satisfies the real-time needs of customers who are responsible for managing them. MDS PulseNET software is unique, as it requires no customization to get started – offering true, out-of-the box functionality.

Key Benefit - Return on Network Investments

MDS PulseNET software was designed to help companies maximize the return on their network investment by:

- Driving Resource Efficiency
 Notify and deploy maintenance resources with the intelligent data required to quickly resolve
- equipment and radio issues
 Improving Network Performance

Access historical network and equipment performance trending to optimize availability through predictive maintenance

• Leveraging MDS Expertise

Purpose built and pre-loaded with recommended performance thresholds, eliminating guesswork





Purpose Built

- Designed to provide out-of-the-box functionally for MDS devices
- Pre-loaded MDS devices performance rules and thresholds to eliminate customer guess work

Rapid Deployment

- Intuitive installation and administrative set-up
- Automatic devices discovery
- Out-of-box, pre-defined and manageable number of alerts

Robust Monitoring

Provides historical performance data and trending of...

- Received Signal Strength Indicator (RSSI)
- Signal Noise Ratio (SNR)
- Error Rate
- Data throughput
- Round trip delay time
- Transmitter power
- Changes in Modulation scheme
- Changes in GPS satellite connectivity and coordinate tracking

Easy to Use

- Management by exception
- Pre-built, intuitive work flows
- Navigation user configurable hyperlinks
- Multiple pre-defined report options

imagination at work

Purpose Built for MDS Devices

With over a million and a half devices installed around the world and twenty-five years of experience, GE is aware of the challenges our customers face when it comes to effectively managing their communication networks. MDS PulseNET software provides the insight and detailed system performance allowing you to intelligently and proactively manage your radio communications network.

Covering GE's MDS wireless product portfolio, from data acquisition to backhaul, MDS PulseNET is capable of creating, storing and software trending derived metrics using built-in program logic. The raw metrics collected from network devices must be correctly manipulated into meaningful data before the information can be presented to the end-user.

Easy Installation & Rapid Deployment

MDS PulseNET software requires minimal effort to install and operate, provides pre-built specific device warning thresholds to eliminate the guesswork, and provides visibility into communications that have historically been unmanaged.

MDS PulseNET software provides multiple, concurrent, role-based logins through a web interface so that each user is able to see exactly what they need to fulfill their individual responsibilities. MDS PulseNET also provides the operator with immediate access to performance trending graphs through the same simple navigation scheme. It normalizes the views for disparate technologies into simplistic and easy-to-use dashboards. The main dashboard provides a high level status of each set of functional components being monitored.

Once your system is properly configured, it can automatically discover your network devices, assign licenses to the devices and begin monitoring the network.

Below is an example of MDS PulseNET's device auto discovery screen which separates network devices into two groups - devices that MDS PulseNET can communicate with and devices that are currently ineligible. MDS PulseNET can auto discover devices by either entering a specific IP address or by providing a search range of IP addresses. In this example, MDS PulseNET has auto discovered several MDS iNETs and MDS Devices.

0	Long		la i	0 - €		Pinging Devices		
Discover Devices	1.00		Search		99%			
IP IP	Model	Role	Serial Number	Vendor	8%	SNMP Query		
10.0.1.14	Intrepid	n/a	I58FN23600528	GE MDS		orizable devices found: 0		Sto
10.0.1.237	Intrepid	n/a	I58FN23600528	GE MDS				50
10.0.1.204	MDS INET 900	Access Point	1001202	GE MDS	Ineligible Devi	tes		
10.0.1.85	MDS INET-II 900	Remote	1001084	GE MDS			Search	Ø•
10.0.1.87	MDS INET-II 900	Access Point	1001083	GE MDS	IP	Name	Device Description	Serial Number
10.0.1.39	MDS INET-II 900	Remote	100 10 35	GE MDS	10.0.1.255	AMI Device 1	AMI Device	n/a
10.0.1.47	Intrepid	n/a	I58FN23600527	GE MDS	10.0.1.50	AMI Device 2	AMI Device	n/a
10.0.1.17	MDS INET 900	Access Point	1001177	GE MDS	10.0.1.57	Comms Switch-1	Comms Switch	n/a
10.0.1.86	MDS INET-II 900	Remote	1001085	GE MDS	10.0.1.17	AMI Device 3	AMI Device	n/a
10.0.1.84	MDS INET-II 900	Remote	1001086	GE MDS	10.0.1.15	Comms Switch-2	Comms Switch	n/a
10.0.1.23	MDS INET 900	Remote	1001203	GE MDS	10.0.1.11	Comms Switch-3	Comms Switch	n/a
10.0.1.46	MDS INET 900	Remote	1001004	GE MDS	10.0.1.25	AMI Device 4	AMI Device	n/a
10.0.1.16	MDS INET-II 900	Remote	1001161	GE MDS	10.0.1.150	AMI Device 5	AMI Device	n/a
10.0.1.137	MDS INET 900	Access Point	1001131	GE MDS	10.0.1.750	AMI Device 6	AMI Device	n/a
10.0.1.154	MDS INET 900	Remote	1001157	GE MDS	10.0.1.56	AMI Device 7	AMI Device	n/a
10.0.1.14	MDS INET 900	Remote	1001104	GE MDS	10.0.1.75	Comms Switch-4 Comms Switch-5	Comms Switch Comms Switch	n/a n/a
10.0.1.532	MDS INET 900	Remote	1001053	GE MDS	10.0.1.12	Comms Switch-6	Comms Switch	n/a
10.0.1.18	MDS INET 900	Remote	1001182	GE MDS	10.0.1.12	Comms Switch-7	Comms Switch	n/a
10.0.1.228	Intrepid	n/a	158FN23600528	GE MDS	10.0.1.251	Comms Switch-8	Comms Switch	n/a
10.0.1.19	Intrepid	n/a	158FN23600528	GE MDS	10.0.1.226	Comms Switch-9	Comms Switch	n/a
10.0.1.17	Intrepid	n/a	158FN23600527	GE MDS	10.0.1.25	AMI Device 8	AMI Device	n/a
					10.0.1.126	Comms Switch-10	Comms Switch	n/a
10.0.1.20	MDS INET 900	Remote	1001204	GE MDS	10.0.1.725	AMI Device9	AMI Device	n/a
10.0.1.175	MDS INET 900	Remote	1001178	GE MDS	10.0.1.526	Comms Switch-11	Comms Switch	n/a
10.0.1.88	MDS INET 900	Access Point	1001081	GE MDS	10.0.1.20	AMI Device 10	AMI Device	n/a
10.0.1.15	MDS INET 900	Remote	1001105	GE MDS				
10.0.1.42	Intrepid	n/a	158FN23600528	GE MDS				
10.0.1.12	Intrepid	n/a	158FN23600527	GE MDS				
10.0.1.94	Intrepid	n/a	158FN23600528	GE MDS				
10.0.1.25	MDS INET 900	Remote	1001205	GE MDS				



Network devices are discovered and added to the tables

Robust Monitoring of Important MDS Performance Parameters

MDS PulseNET software is designed to monitor the critical elements of a communications network, from RSSI to SNR to device communication status. With vast amounts of raw data created and stored over time, it can be difficult to prioritize corrective actions. MDS PulseNET software provides warning performance thresholds that can trigger exception events, which in turn can trigger specific actions, such as sending messages to trouble ticketing systems or other management systems. Additionally, these event-triggering thresholds can be easily changed within the software to meet unique customer requirements.



MDS PulseNET provides easy to review device performance screens showing the critical radio parameters such as: RSSI, SNR, Throughput, and Availability. This example shows the performance screen for an MDS Mercury 900

													Search	,
alth	Device Name	Device Model	IP Address		Time (ms) Average		· ·		(dB) Average	Uplink Modulation	Downlink Modulation	Availability (%)	Last Poll	Health History
	ARCADI-1391iNet-R	iNET-II 900	10.0.141.54	23	48	-90.0	-85.1	4.0	18	QAM64 3/4	QPSK 1/2	~~ 100	Jul 15, 2010 8:25:03 AM	
	ARCADI-1714iNet-R	iNET-II 900	10.0.142.88	23	48	-90.0	-85.1	4.0	18	QPSK 3/4	QAM16 3/4	~~ 100	Jul 15, 2010 8:25:03 AM	
)	ARCADI-3246iNet-R	iNET-II 900	10.0.140.27	23	48	-90.0	-85.1	4.0	18	BPSK 1/2	QAM64 2/3	~~ 100	Jul 15, 2010 8:25:03 AM	
	ARCADI-3393iNet-R	iNET-II 900	10.0.142.24	23	48	-90.0	-85.1	4.0	18	QAM64 1/2	BPSK 1/2	~~ 100	Jul 15, 2010 8:25:03 AM	
	ARCADI-4551iNet-R	iNET-II 900	10.0.143.83	23	48	-90.0	-85.1	4.0	18	QAM16 1/2	QPSK 3/4	~~ 100	Jul 15, 2010 8:25:03 AM	
	ARCADI-4662iNet-R	iNET-II 900	10.0.140.90	23	48	-90.0	-85.1	4.0	18	QAM642/3	QAM 16 1/2	~~ 100	Jul 15, 2010 8:25:03 AM	
3	ARCADI-5149iNet-R	iNET-II 900	10.0.142.171	23	48	-90.0	-85.1	4.0	18	QPSK 3/4	QPSK 1/2	~~100	Jul 15, 2010 8:25:03 AM	
	ARCADI-5247iNet-R	iNET-II 900	10.0.141.14	23	48	-90.0	-85.1	4.0	18	QAM64 3/4	QPSK 1/2	~~ 100	Jul 15, 2010 8:25:03 AM	
	ARCADI-7845iNet-R	iNET-II 900	10.0.143.47	23	48	-90.0	-85.1	4.0	18	QPSK 3/4	QAM16 3/4	~~ 100	Jul 15, 2010 8:25:03 AM	
3	ARCADI-9636iNet-R	iNET-II 900	10.0.140.134	23	48	-90.0	-85.1	4.0	18	BPSK 1/2	QAM64 2/3	~~ 100	Jul 15, 2010 8:25:03 AM	
	BURSON-1476MR-R	Mercury 1800	10.0.142.92	134	884	-90.0	-85.1	4.0	18	QAM64 2/3	BPSK 1/2	~~ 100	Jul 15, 2010 8:25:04 AM	
	BURSON-2257MR-R	Mercury 1800	10.0.140.45	192	895	-90.0	-85.1	4.0	18	QAM16 1/2	QPSK 3/4	~~ 100	Jul 15, 2010 8:25:04 AM	
	BURSON-2848MR-R	Mercury 1800	10.0.141.141	1163	1225	-90.0	-85.1	4.0	18	QAM64 2/3	QAM 16 1/2	~~ 100	Jul 15, 2010 8:25:04 AM	
	BURSON-4219MR-R	Mercury 1800	10.0.140.122	1304	1126	-90.0	-85.1	4.0	18	QPSK3/4	QPSK 1/2	~~ 100	Jul 15, 2010 8:25:04 AM	
	BURSON-5463MR-R	Mercury 1800	10.0.143.233	1153	1176	-90.0	-85.1	4.0	18	QAM64 3/4	QPSK 1/2	~~ 100	Jul 15, 2010 8:25:04 AM	
	BURSON-5934MR-R	Mercury 1800	10.0.143.213	889	856	-90.0	-85.1	4.0	18	QPSK 3/4	QAM16 3/4	~~ 100	Jul 15, 2010 8:25:04 AM	
	BURSON-6357MR-R	Mercury 1800	10.0.143.143	956	978	-90.0	-85.1	4.0	18	BPSK3/4	QAM64 2/3	~~ 100	Jul 15, 2010 8:25:04 AM	
	BURSON-6873MR-R	Mercury 1800	10.0.142.152	1114	891	-90.0	-85.1	4.0	18	QAM64 2/3	BPSK 1/2	~~ 100	Jul 15, 2010 8:25:04 AM	

For comparing and contrasting radio performance, MDS PulseNET provides the ability to quickly monitor the radio health for radio remotes including RSSI, SNR, and Roundtrip delay. In one view this table shows the current and historical performance for network remotes

Designed as an Easy to Use, Day-to Day Operational Tool

MDS PulseNET was designed with operator-intuitive screens and operational ease-of-use workflows in mind. This design provides the ability to view a comprehensive system overview while at the same time have the ability to drill-down from the network layer to the device level. This gives operation personnel the opportunity to enhance corrective business processes and improve productivity.

MDS PulseNET's main dashboard provides a high level status of each set of functional components being monitored by MDS PulseNET. With a quick glance, the operator can see which functional area is having availability and/or performance problems. Workflows allow the operator to either click on the alert to see more details or drill into the functional dashboard and see the operational status of the device(s) itself.



From any of the MDS PulseNET status screens, the operator can quickly access individual device performance as well as the alert history. Above is an example of the alert history provided by MDS PulseNET for a MDS Mercury 900 remote

PulseNET and PulseNET Enterprise

The MDS PulseNET platform was developed in two versions – MDS PulseNET and MDS PulseNET Enterprise in order to serve a wide variety of customer needs and environments. Both versions incorporate important performance parameters including management by exception, intuitive work flows and MDS network expertise.

PulseNET

MDS PulseNET provides for the fundamental system needs of device discovery, proactive monitoring and early warning for radio networks consisting of less than 500 MDS radios.

Common Platform Capabilities

PulseNET and PulseNET Enterprise

Capabilities

Supports MDS iNET and Mercury series wireless radios*

• Out-Of-The-Box pre-loaded data collection settings with recommended alert levels.

Exception-Based Alert System via Color Coded Icons

- Warns when out-of-bounds alert levels are exceeded
- Intuitive and color-based icons provides rapid evaluation of alert

Ease-of-Use

Single User Interface Installation Program Download

- Simplifies installation and reduces level of technical expertise
- Upgrade Wizard for Configuration, Diagnostic and Firmware*
- Ease of configuration, device software & firmware upgrade

Consolidates Performance Metrics and Displays Via Device Dashboards

Intuitive graphical presentation of data and alerts

Automatic system discovery based on range of IP addresses • Simplifies network deployment

Security

User ID and Password logins

User forced out when inactive for extended periods

Multiple Levels of User Access Control*

• Limits screen and configuration access by user type

Communication

Supports Polling of SNMP Version 1, 2c and 3

Network-wide Diagnostics – current and most legacy MDS devices • Built-in support for GE MDS proprietary communication protocol

Forward Alerts to 3rd Parties – SNMP Traps, API & Email

Capability to communicate alerts via multiple mediums

Remote Access Via Telnet, SSH and HTTP(S)

• Several options to communicate remotely to network and devices

PulseNET Enterprise

MDS PulseNET Enterprise version is designed for enterprise type network with greater than 500 devices and which require more robust monitoring that includes third party devices.*

MDS PNE simplifies work-flows by utilizing configuration information to automate radio maintenance. Configuration changes become a point and click user interface for bulk provisioning firmware upgrades. MDS PulseNET Enterprise can also apply its work flows and warning capabilities to non-MDS equipment. Through MDS PulseNET Enterprise, a complete end-to-end view of network performance is available from the field location to the operations facility including attached meters and Remote Terminal Units (RTUs). This provides a consistent view for management and operations to understand the root cause of current incidents, and allows proactive avoidance of potential new incidents.

Advanced Platform Capabilities

ulseNET Enterpris

Enterprise Operations Capable

Federation

• Allows multiple PulseNET Enterprise to operate as one regionally deployed network and for central console roll up

External Databases

Allows use of customer database or PulseNET supplied database

Self Monitoring

• Self monitoring - providing complete end to end support

Security

Supports Remote Authentication Dial In User Service (RADIUS) Protocol*

Provides centralized Authentication, Authorization, and Accounting (AAA) management for network services*

Configuration Management

Centralized Configuration Management

• Streamline security, auditing, storage and controls

Track and document changes to configurations

3rd Party Integrations

Allows customers to manage non MDS devices

- GE will continue to incorporate additional Out-Of-The-Box 3rd party device as requested by customers
- Customers can opt to incorporate non-MDS devices as a generic devices type for collections and reporting

Notification Application Programming Interface (API) to 3rd party manager of managers, I.e. HP, Quest, IBM, etc*

- Software communications via standard interface
- Flexibility to use and interface with other manager of managers

Out of the box capability for monitoring 3rd party devices is enhanced in each release. Please consult with MDS to determine if a specific 3rd party devices is supported by the current version of PulseNET Enterprise.

* These features are planned for the next release of PulseNET and PulseNET Enterprise currently targeted for late 2011

Product Function - PulseNET vs PulseNET	Enterprise	
Function	PulseNt	ET
System	Standard	Enterprise
Web based platform for easy user access	\checkmark	\checkmark
Windows & Linux installations supported	\checkmark	\checkmark
Single graphical user interface installation program	\checkmark	\checkmark
Downloadable software and updates	\checkmark	\checkmark
Automated discovery of IP based devices	\checkmark	\checkmark
Automated network topology maps	\checkmark	\checkmark
Purpose built work flows for mission critical networks	\checkmark	\checkmark
Supports SNMP versions 1, 2c and 3	\checkmark	\checkmark
OPC integration*		\checkmark
Integrated database supplied with installation	\checkmark	\checkmark
Predefined best practices management for MDS devices	\checkmark	\checkmark
Scalable network management via federation (parent/ child installs)	500 Device Limit	\checkmark
Can leverage external database repositories for storage vs. integrated		~
Predefined best practices management for 3rd parties (i.e. ltron)* Custom Integrations for 3rd parties onsite that are not		✓
yet available		 ✓
High availability server installation capable		\checkmark
GPS aware mapping - Automatic or manually located on GPS aware maps*		\checkmark
LAN Monitoring - basic fault/performance monitoring of network devices		×
Custom rules, dashboards and collections capable		\checkmark
Fault	Standard	Enterprise
Automated & intelligent alerting for MDS devices	\checkmark	✓
Real-time & historical display of exception alerts with severity indicators	\checkmark	 ✓
Alert notation capability for searchable historical notes		✓
Configurable filtering based on criteria, I.e. severity, status, location, etc.	\checkmark	\checkmark
Configurable notification alerts - email/SMS & SNMP	email/sms	✓

Product Function - PulseNET vs PulseNET	Enterprise	
Function	PulseN	ET
Fault (Continued)	Standard	Enterprise
Root cause correlation based on network dependencies	\checkmark	\checkmark
Alert integration of 3rd party Out-of-the-box (OOTB) & customizable		\checkmark
Notification API to 3rd party manager of managers, I.e. HP, Quest, IBM, etc		\checkmark
Fully integrated graphical interface for SNMP trap receiving*		\checkmark
Configuration	Standard	Enterprise
Installation wizard for configuration and firmware per MDS device basis*	\checkmark	\checkmark
Scheduling of updates within graphical user interface*	\checkmark	\checkmark
Configuration dashboard for central reposistory and controls*	\checkmark	\checkmark
Full audit of configuration changes*		 ✓
Deploy updates to MDS devices on a global basis *		 ✓
Performance	Standard	Enterprise
Performance dashboard with purpose built prescriptive diagnostic work flows Inherited performance collections based on vendor /	√	 ✓
Performance collections for diagnostics (I.e. RSSI, SNR,	v	
bandwidth, etc)	V	V
Scheduled reporting of availability, lowest performers, etc.	\checkmark	✓
Retains collections for comparison year over year	45 Day Limit	 ✓
Performance dashboards for 3rd parties OOTB		 ✓
Self monitoring of PulseNET Enterprise system		 ✓
Security	Standard	Enterprise
Tracking of configuration and firmware for MDS devices	\checkmark	 ✓
User forced out when inactive for extended periods	\checkmark	 ✓
Remote access shortcuts to devices for Telnet, SSH and HTTP(s)	\checkmark	✓
Centralized management - to streamline security and control	√	\checkmark
User level accounting	\checkmark	 ✓
Role based security (admin vs. operator)	\checkmark	 ✓
Radius support*		✓

Out of the box capability for monitoring 3rd party devices is enhanced in each release. Please consult with MDS to determine if a specific 3rd party devices is supported by the current version of PulseNET Enterprise.

* These features are planned for the next release of PulseNET and PulseNET Enterprise currently targeted for late 2011

PulseNET System Requirements

Recommended System:

- Dual Core CPU at 1.6 GHZ
- 2 GB of RAM available
- 30 GB of Disk

Supported Operating Systems:

- Windows Vista or Windows 7
- Windows Server 2003 and 2008
- Red Hat Linux AS/ES 5.x, SuSE9 and 10, CentOS AS/ES 5.3/5.4
- Virtualized environments supported

PulseNET Enterprise System Requirements

Recommended System:

- Quad Core CPU at 2.2 GHz
- 16 GB of RAM available
- 160 GB of Disk

Supported Operating Systems:

- Windows Server 2003 and 2008
- Red Hat Linux AS/ES 5.x, SuSE9 and 10, CentOS AS/ES 5.3/5.4
- Virtualized environments supported

Supported Web Browsers

- Microsoft Internet Explorer 7.x, 8.x+
- Mozilla Firefox 3.6.4+
- Apple Safari 4.x+



Digital Energy

Ordering

Software & Device License	1 Device	10 Devices	25 Devices	100 Devices	250 Devices
PulseNET	PN-1	PN-10	PN-25	PN-100	PN-250
PulseNET Enterprise	PNE-1	PNE-10	PNE-25	PNE-100	PNE-250
Maintenance (1 year)	1 Device	10 Devices	25 Devices	100 Devices	250 Devices
	1 Device PNM-1	10 Devices PNM-10	25 Devices PNM-25	100 Devices PNM-100	250 Devices PNM-250

30 Day Trial Copy	20 Devices
PulseNET	PNT-20
PulseNET	PNFT-20

Enterprise PNEI-20

Visit www.GEDigitalEnergy.com/Communications to:~

- Buy MDS PulseNET through the online store
 - Download guideform specifications
 - Download user documentation
 - Read application notes and white papers