

Product Features:

Construction:	Dimensions:	Plank: 6" x 48" (152.4mm x 1219.2mm)
	Overall Thickness:	3mm
	Wear Layer Thickness:	20 mils
	Raw Material:	100% Virgin Vinyl
	Edge Detail:	4-Sided Square Edge
	Surface:	Ceramic with Anti-bacterial finish
Packaging:	Pieces p/Carton	18 Planks
	Coverage p/Carton	36 sq.ft.
	Weight p/Carton	37.17 Lbs.
Installation Method:		Glue Down
Recommended Adhesive:		Franklin 670 for wet lay or pressure sensitive Silencer Quicklay Spray Adhesive
Warranty:		Lifetime Residential / 10 Year Commercial See complete warranty guide for details.
Country of Origin:		Korea

ASTM Data Reference F 1700 - Shall meet or exceed performance specifications

ASTM F 1914 Residual Indentation	Passes	ASTM F 1514 Resistance to Heat	4.3
ASTM F 137 Flexibility	Passes	ASTM F 970 Static Load Limit	250 p.s.i
ASTM F 2199 Dimensional Stability	0.0038 in/lin.ft.	ASTM E 662 Smoke Chamber Test	< 450
ASTM F 925 Resistance to Chemicals	Passes	ASTM E 648 Radiant Flux	Class 1 CRF > .45

Our LVT Products will contribute value to a building's LEED Scorecard in the following categories recognized by the USGBC:

LEED Scorecard

- LEED NC 2.2 & CI 2.0 Rating System
- LEED EB 2.0 Rating System
- LEED Schools, NC & Major Renovations Rating System

Other environmental attributes: ISO 14001 - Environmental Manufacturing Standard Post Consumer Recycling Program - 2.2 & CI2.0

- MR 4.1- Post Consumer 10% (post-consumer + ½ pre-consumer)
- MR 4.2- Post Consumer 20% (post-consumer + ½ pre-consumer)

EB 2.0
MR 2.1- Optimize Use of Alternative Materials
- Post Consumer Recycled Content

LEED Retail, Schools, NC & Major Renovations Rating System

- MR 4.1- Post Consumer 10% (post-consumer + ½ pre-consumer)
- MR 4.2- Post Consumer 20% (post-consumer + ½ pre-consumer)

Compliance:

Formaldehyde Emission:	E0
Ortho Phthalate Free:	Free of DBP, BBP, DEHP, DNOP, DINP, DIDP & DIBP
All Reward flooring products are manufactured in compliance with California and US safety standards.	

