





Product Features:

Size:	1/2" x 7.5" x Random Length (23" - 75" or 18-84")			
Wood Grade:	Character			
Wear Layer Thickness:	2 mm			
Texture/Edge:	Varies by item; Handscraped, Wire Brushed, or Smooth, Micro-beveled edges			
Coating/Gloss Level:	UV urethane w/ Aluminum Oxide, Satin			
Species Available/ Janka Hardness:	Maple - 1450 European Oak - 1360 Walnut - 1010 Hickory - 1820			
Colors:	Maple Somerton (<i>REW1275CLMS</i>) European Oak Dover (<i>REW1275CLODS</i>) Hickory Barnwell (<i>REW1275CLHB</i>) Walnut Upton (<i>REW1275CLWU</i>) European Oak Clifton (<i>REW1275CLOC</i>) Walnut Hastings (<i>REW1275CLWH</i>) European Oak Warwick (<i>REW1275CLOW</i>) Walnut Oxford (<i>REW1275CLWO</i>)			
Moldings:	 <p>Quarter Round</p>	 <p>T-Mold</p>	 <p>Stair Nose</p>	 <p>Reducer</p>

Technical Specifications:

Packaging:	30.92 SF/CT - European Oak (23" - 75" Lengths) 34.67 SF/CT - Hickory, Walnut, Maple (18" - 84" Lengths) 52 CT/Pallet
Warranty:	Lifetime Structural Warranty 25 Year Finish Residential Warranty 3 Year Finish Commercial Warranty
Installation:	Glue down, staple, or float. Please refer to Installation Instructions and Care & Maintenance Guide for complete instructions.
Maintenance:	Bona Hardwood Floor Cleaners, please refer to Reward Care & Maintenance Guide for complete instructions.
Compliance:	All Reward Hardwood products are manufactured in compliance with the <u>Food, Conservation, and Energy Act of 2008</u> (Lacey Act amendment), and are in full compliance with California's Airborne Toxic Control Measure (CARB).
MSDS:	Not required for UV cured finish.
Formaldehyde Emissions (per ASTM D6007)*:	0.021ppm