

Product Features:		
Construction:	Dimensions:	Plank: 10" x 60" (254mmx1530mm)
	Overall Thickness:	3mm
	Wear Layer Thickness:	20 mils
	Raw Material:	100% Virgin Vinyl
	Edge Detail:	4-Sided Bevel
	Surface:	Embossed in Register, Ceramic with Antimicrobial Finish
Packaging:	Pieces p/Carton	8 Planks
	Coverage p/Carton	33.33 sq.ft.
	Weight p/Carton	42.59 Lbs.
Installation Method:		Glue Down
Recommended Adhesive:		Franklin 670 for wet lay or pressure sensitive Silencer Quicklay Spray Adhesive
Warranty:		Lifetime Residential / 10 Year Commercial See complete warranty guide for details.
Country of Origin:		China

Performance:		
Squareness, Straightness and Length	EN ISO 24342:2012	Specification: 304.8 (+/- 0.10) mm * 1530 (+/- 0.50) mm Squareness ≤ 0.25mm
Residual Indentation	EN ISO 24343-1:2012	≤0.03mm
Peel Resistance	EN ISO 24345:2012	Longitudinal: 65N Cross: 80N
Dimensional Stability	EN ISO 23999:2012	≤0.05%
Slip Resistance	EN 13893:2002 / EN 14041	Class DS
Stain Resistance	EN ISO 26987:2012	Class 0, Not Affected
Resistance to Light	EN 649:1997 = A1:2003	Pass (6 or better)
Reaction to Fire	EN 13501-1:2007	Bfl - S1
Flame Spread	EN ISO 11925-2	Pass
Smoke Generation	EN ISO 9239-1	Class s1, < 750
Scratch Resistance	General Industry Standard	≥ 2500g
Wear Resistance	EN 660-2:1999 + A1:2003	≤ 1.2mm ³ /100 rotations

Compliance:	
Ortho Phthalate Free:	Free of DBP, BBP, DEHP, DNOP, DINP, DIDP & DIBP
All Reward flooring products are manufactured in compliance with California and US safety standards.	

