

Product Features:

Construction:	Dimensions:	Plank: 6" x 48" (152.4mm x 1219.2mm)
	Overall Thickness:	2mm
	Wear Layer Thickness:	12 mils (0.3mm)
	Raw Material:	100% Virgin Vinyl
	Edge Detail:	4-Sided Bevel
	Surface:	Natural Emboss with Quartz-enhanced UV Coat
Packaging:	Pieces p/Carton	24 Planks
	Coverage p/Carton	48.00 sq.ft.
	Weight p/Carton	40.2 Lbs.
Installation Method:		Glue Down
Recommended Adhesive:		Franklin 670 for wet lay or pressure sensitive Silencer Quicklay Spray Adhesive
Warranty:		25 Year Residential / 5 Year Light Commercial See complete warranty guide for details.

Performance:

Thickness	EN 428:1993	2.0 +/- 0.15MM
Squareness, Straightness and Length	EN 427:1994	Specification: 152.4 (+/- 0.10) mm * 914.4 (+/- 0.50) mm Squareness ≤ 0.25mm
Residual Indentation	EN 433:1994	≤0.1mm
Flexibility	EN 435:1994	Pass
Dimensional Stability	EN 434:1994	≤0.20%
Slip Resistance	EN 13893:2002 / EN 14041	Class DS
Stain Resistance	EN 423:2002 ASTM F 925-02: 2008	Not Affected Average = 0 (No Change)
Resistance to Light	EN 649:1997 = A1:2003	Pass (6 or better)
Reaction to Fire	EN 13501-1:2007	Bfl - S1
Flammability	ASTM D2859-06/CPSC FF 1-7	Pass
Surface Burning Characteristics	ASTM E84:2010b	Meets Class C Interior Wall & Ceiling Finish Category
Smoke Density	ASTM E 662-06	< 450
Static Load	ASTM F 970	1000 psi: 0.023mm
Effect of Castor Chair	EN 425:2002	Pass
Scratch Resistance	General Industry Standard	≥ 2500g
Wear Resistance	EN 660-2:1999 + A1:2003	≤ 0.015g/1000 rotations

Compliance:

Formaldehyde Emission:	EN 14041:2004 Pass (Below E1)
Ortho Phthalate Free:	Free of DBP, BBP, DEHP, DNOP, DINP, DIDP & DIBP
All Reward flooring products are manufactured in compliance with California and US safety standards.	

