

SPECIFICATION SHEET

Product Features:				
Size:	1/2" x 6.5" x Random Length (16" - 71")			
Wood Grade:	Elite			
Wear Layer Thickness:	2 mm			
Texture/Edge:	Wire-brushed, Micro-beveled edges			
Coating/Gloss Level:	UV urethane w/ Aluminum Oxide, Ultra-Matte			
Species Available/ Janka Hardness:	Red Oak - 1290			
Colors:	Oak Senato (REW 1265MOSN) Oak Giordano (REW 1265MOGR) Oak Marino (REW 1265MOMR) Oak Andrea (REW 1265MOAD)			
Moldings:	Quarter Round	$ \begin{array}{c c} & 2" & \longrightarrow \\ \hline 5/16^{\dagger} & & \longrightarrow \\ \hline 5/16^{\dagger} & & \longrightarrow \\ \hline -1/2" \longrightarrow \\ \hline T-Mold $	1/2" ↓ 3-1/8" ↑ 13/16" Stair Nose	1/2" 2" 1/8" Reducer

Technical Specifications:			
Packaging:	25.58 SF/CT 45 CT/Pallet		
Warranty:	Lifetime Structural Warranty 25 Year Finish Residential Warranty 3 Year Finish Commercial Warranty		
Installation:	Glue down, float or staple. Please refer to Installation Instructions and Care & Maintenance Guide for complete instructions.		
Maintenance:	Bona Hardwood Floor Cleaners, please refer to Reward Care & Maintenance Guide for complete instructions.		
Compliance:	All Reward Hardwood products are manufactured in compliance with the Food, Conservation, and Energy Act of 2008 (Lacey Act amendment), and are in full compliance with California's Airborne Toxic Control Measure (CARB). FloorScore® Certified. FloorScore® is a certification program established by the Resilient Floor Covering Institute (RFCI) for hard surface flooring and flooring adhesive products that meet strict indoor air quality (IAQ) requirements. Products bearing the FloorScore label meet the indoor air quality emissions criteria of LEED, CHPS, the Green Guide for Health Care, and are recognized by a long list of healthy building programs.		

^{*}All test results come from an independent, CARB-accredited U.S. testing laboratory and are verified/updated periodically.



Visit us at rewardflooring.com