







### Product Features:

<b>Size:</b>	1/2" x Random Widths (4" - 6" - 8") x Random Length (20" - 94")			
<b>Wood Grade:</b>	Character			
<b>Wear Layer Thickness:</b>	2 mm			
<b>Texture/Edge:</b>	Hand-scraped, Micro-beveled edges			
<b>Coating/Gloss Level:</b>	UV urethane w/ Aluminum Oxide, Satin			
<b>Species Available/ Janka Hardness:</b>	Hickory - 1820 Maple - 1450	Walnut - 1010		
<b>Colors:</b>	Hickory Rutherford (REW12468NRF8) Hickory Skyline (REW12468NSK8) Hickory Silverado (REW12468NSV8) Hickory Monticello (REW12468NMC8)	Maple Hennessy (REW12468NHN8) Maple York Creek (REW12468NYC8) Maple Orville (REW12468NRV8) Walnut Quail Ridge (REW12468NQR8)		
<b>Moldings:</b>	 Quarter Round	 T-Mold	 Stair Nose	 Reducer

### Technical Specifications:

<b>Packaging:</b>	47.24 SF/CT 36 CT/Pallet		
<b>Warranty:</b>	Lifetime Structural Warranty 25 Year Finish Residential Warranty 3 Year Finish Commercial Warranty		
<b>Installation:</b>	Glue down, staple, or float. Not approved for use over radiant heat systems. Please refer to Installation Instructions and Care & Maintenance Guide for complete instructions.		
<b>Maintenance:</b>	Bona Hardwood Floor Cleaners, please refer to Reward Care & Maintenance Guide for complete instructions.		
<b>Compliance:</b>	All Reward Hardwood products are manufactured in compliance with the <u>Food, Conservation, and Energy Act of 2008</u> (Lacey Act amendment), and are in full compliance with California's Airborne Toxic Control Measure (CARB).   FloorScore® Certified. FloorScore® is a certification program established by the Resilient Floor Covering Institute (RFCI) for hard surface flooring and flooring adhesive products that meet strict indoor air quality (IAQ) requirements. Products bearing the FloorScore label meet the indoor air quality emissions criteria of LEED, CHPS, the Green Guide for Health Care, and are recognized by a long list of healthy building programs.   CERTIFIED BY SCS Global Services		
<b>Formaldehyde Emissions (per ASTM D6007)*:</b>	0.009ppm		

\*All test results come from an independent, CARB-accredited U.S. testing laboratory and are verified/updated periodically.

Visit us at [rewardflooring.com](http://rewardflooring.com)