







PROVENCE II COLLECTION SPECIFICATION SHEET

Product Features:	
Size:	1/2" x 7-1/2" x Random Length (20" - 75")
Wood Grade:	Rustic
Wear Layer Thickness:	2 mm
Texture/Edge:	Handscraped, Wire-brushed or Smooth finish (style varies by color), Micro-beveled edges
Coating/Gloss Level:	UV urethane w/ Aluminum Oxide, Ultra-matte
Species Available/ Janka Hardness:	European Oak - 1360 Walnut - 1010 Hickory - 1820
Colors:	European Oak Andon (REW1275P2EOAD) European Oak Gardanne (REW1275P2EOGD) European Oak Avene (REW1275P2EOAV) European Oak Tallard (REW1275P2EOTL) European Oak Caday (REW1275P2EOCD) Hickory Pelcourt (REW1275P2HPC) European Oak Colette (REW1275P2EOCL) Walnut Arzens (REW1275P2WAZ) European Oak Revel (REW1275P2EORV) Walnut Palmiers (REW1275P2WPM) European Oak Leran (REW1275P2EOLR)
Moldings:	 Quarter Round  T-Mold  Stair Nose  Reducer

Technical Specifications:	
Packaging:	31.09 SF/CT 40 CT/Pallet
Warranty:	Lifetime Structural Warranty 25 Year Finish Residential Warranty 3 Year Finish Commercial Warranty
Installation:	Glue down, nail + glue, or float. Please refer to Installation Instructions and Care & Maintenance Guide for complete instructions.
Maintenance:	Bona Hardwood Floor Cleaners, please refer to Reward Care & Maintenance Guide for complete instructions.
Compliance:	<p>All Reward Hardwood products are manufactured in compliance with the Food, Conservation, and Energy Act of 2008 (Lacey Act amendment), and are in full compliance with California's Airborne Toxic Control Measure (CARB).</p>  <p>FloorScore® Certified. FloorScore® is a certification program established by the Resilient Floor Covering Institute (RFCI) for hard surface flooring and flooring adhesive products that meet strict indoor air quality (IAQ) requirements. Products bearing the FloorScore label meet the indoor air quality emissions criteria of LEED, CHPS, the Green Guide for Health Care, and are recognized by a long list of healthy building programs.</p> 
Formaldehyde Emissions (per ASTM D6007)*:	0.006ppm

*All test results come from an independent, CARB-accredited U.S. testing laboratory and are verified/updated periodically.



Visit us at rewardflooring.com

where luxury and value meet