

SPECIFICATION SHEET

Product Features:				
Size:	1/2" x 6" x Random Length (16" - 75")			
Wood Grade:	Rustic			
Wear Layer Thickness:	1.5 mm			
Texture/Edge:	Wire Brushed, Micro-beveled edges			
Coating/Gloss Level:	UV urethane w/ Aluminum Oxide, Satin			
Species Available/ Janka Hardness:	European Oak - 1360			
Colors:	European Oak Cayman (<i>REW126SHOCM</i>) European Oak Nevis (<i>REW126SHONV</i>) European Oak Aruba (<i>REW126SHOAR</i>) European Oak Curacao (<i>REW126SHOCC</i>)		European Oak Barbados (<i>REW126SHOBB</i>) European Oak Bonaire (<i>REW126SHOBN</i>) European Oak Tortola (<i>REW126SHOTT</i>) European Oak Trinidad (<i>REW126SHOTR</i>)	
Moldings:	Quarter Round	$5/16^{\uparrow}_{1}$ $5/16^{\uparrow}_{1}$ $5/16^{\uparrow}_{1}$ $+1/2^{n}$ T-Mold	^{1/2} , 3·1/8", 13/16" Stair Nose	1/2"t3/16" Reducer

Technical Specifications:			
Packaging:	24.87 SF/CT 42 CT/Pallet		
Warranty:	Lifetime Structural Warranty 25 Year Finish Residential Warranty 3 Year Finish Commercial Warranty		
Installation:	Glue down, staple, or float. Please refer to Installation Instructions and Care & Maintenance Guide for complete instructions.		
Maintenance:	Bona Hardwood Floor Cleaners, please refer to Reward Care & Maintenance Guide for complete instructions.		
Compliance:	All Reward Hardwood products are manufactured in compliance with the Food, Conservation, and Energy Act of 2008 (Lacey Act amendment), and are in full compliance with California's Airborne Toxic Control Measure (CARB). FloorScore® Certified. FloorScore® is a certification program established by the Resilient Floor Covering Institute (RFCI) for hard surface flooring and flooring adhesive products that meet strict indoor air quality (IAQ) requirements. Products bearing the FloorScore label meet the indoor air quality emissions criteria of LEED, CHPS, the Green Guide for Health Care, and are recognized by a long list of healthy building programs.		

Visit us at rewardflooring.com

, where luxury and value meet

Galleher⁻

Revised 08.2018 Page 1 of 1