





Product Features:	
Size:	3/8" x 3" and 5" x Random Length (12" - 75")
Wood Grade:	Red Oak Natural, White Oak Natural and Maple Natural: Elite Grade White Cap, Sable & Sunray: Natural Grade
Wear Layer Thickness:	2 mm
Texture/Edge:	Smooth, micro-beveled edges
Coating/Gloss Level:	UV urethane w/ Aluminum Oxide, Ultra-matte
Species Available/ Janka Hardness:	Maple - 1450 Red Oak - 1290 White Oak - 1360 Hickory - 1820
Colors:	Maple Natural 3" (REW383SMM) Hickory Sunray 5" (REW385SMHT) Maple Natural 5" (REW385SMM) Maple Sable 5" (REW385SMCN) Red Oak Natural 3" (REW383SMRO) White Oak Natural 5" (REW385SMWO) Red Oak Natural 5" (REW385SMRO) White Oak White Cap 5" (REW385SMWOC)
Moldings:	 Quarter Round  T-Mold  Stair Nose  Reducer

Technical Specifications:		
Packaging:	3" Width - 28.05 SF/CT 44 CT/Pallet	5" Width - 31.17 SF/CT 44 CT/Pallet
Warranty:	Lifetime Structural Warranty 25 Year Finish Residential Warranty 3 Year Finish Commercial Warranty	
Installation:	Glue down, nail down, or float. Approved for use over radiant heat systems, except Hickory & Maple items - review Installation Instructions thoroughly for system requirements before finalizing flooring selection.	
Maintenance:	Bona Hardwood Floor Cleaners, please refer to Reward Care & Maintenance Guide for complete instructions.	
Compliance:	<p>All Reward Hardwood products are manufactured in compliance with the <u>Food, Conservation, and Energy Act of 2008</u> (Lacey Act amendment), and are in full compliance with California's Airborne Toxic Control Measure (CARB).</p>  <p>FloorScore® Certified. FloorScore® is a certification program established by the Resilient Floor Covering Institute (RFCI) for hard surface flooring and flooring adhesive products that meet strict indoor air quality (IAQ) requirements. Products bearing the FloorScore label meet the indoor air quality emissions criteria of LEED, CHPS, the Green Guide for Health Care, and are recognized by a long list of healthy building programs.</p>	
Formaldehyde Emissions (per ASTM D6007)*:	<0.005ppm	

*All test results come from an independent, CARB-accredited U.S. testing laboratory and are verified/updated periodically.



Visit us at rewardflooring.com

where luxury and value meet