56

NIAGARA SPRING BATHING SYSTEM

The Niagara Springs Bathing System is designed to bathe highly dependent residents safely and comfortably and is compatible with a wide range of transport and lifting devices. The key-hole shape enhances patient comfort with extra room for the shoulders and arms, plus, allows the caregiver closer and greater access to bathe the resident. The smooth and soft lines enhance the look of the bathing area and allow for easy maintenance and cleaning. The Niagara Spring (Model DB-NIAGARA-1400, DB-NIAGARA-1500 and DB-NIAGARA-1600 ONLY) can be raised and lowered at the touch of a button and allows the caregiver to work at the proper height, thus eliminating back strain.

۲

600) lb.	
EIGHT	CAPA	CITY 丿

/		
	DB-NIAGARA-1000	Freestanding Supine with Thermostatic Mixing Valve and Auto-Fill
	DB-NIAGARA-1200	Fixed Height Supine with Thermostatic Mixing Valve, Disinfectant System and Auto-Fill
	DB-NIAGARA-1300	Freestanding Supine with Thermostatic Mixing Valve, Disinfectant System, Air Spa and Auto-Fill
	DB-NIAGARA-1400	Height Adjustable Supine with Thermostatic Mixing Valve and Auto-Fill
	DB-NIAGARA-1500	Height Adjustable Supine with Thermostatic Mixing Valve, Disinfectant System and Auto-Fill
	DB-NIAGARA-1600	Height Adjustable Supine with Thermostatic Mixing Valve, Disinfectant System, Air Spa and Auto-Fill

FEATURES:

- Auto-fill Eliminates waiting and/or observation time when pre-filling the bathtub to a pre-set level.
- Thermostatic mixing valve Provides an anti-scald protection that dispenses 15 gallons per minute for fast tub fill.
- Built-in disinfection system The most time-efficient solution for disinfection of the bath's external surfaces and minimizes the risk of cross-infection. The built-in disinfection system cabinet is conveniently located on the side of the tub for easy access. The lockable cabinet provides a secure place for cleaning supplies and disinfectants.
- Handheld shower wand- Hair and upper body washing can be used at the same time the tub is filling.
- Water temperature display Monitors tub-fill and shower wand temperatures.
- 3/4" supply lines Constructed of stainless steel mesh clad.
- The CleanDrive Air Spa System Variable speeds and pulse modes designed to enhance the bathing experience for the resident and caregiver.

Additional features of the CleanDrive Air System include:

- The hydro massage provides millions of preheated air bubbles in the water which increases stimulation of peripheral blood circulation, reduces pain and inflammation in the joints, gently massages away dirt, and induces deeper relaxation.
- The CleanDrive Air Spa System is a hygienic and low maintenance hydro massage system featuring 12 air jets with spring loaded check valves for back flow prevention. It prevents water from entering the air lines, eliminating the extra step to disinfect air lines. The CleanDrive Air Spa System simplifies disinfection and reduces the possibility of cross-contamination.
- Unlike most other whirlpool and air spa systems, the CleanDrive Air Spa System does not allow water to enter the air lines to reduce the growth of bacteria and mold.
- The motor is quiet, efficient, and has a ceramic heating element that blows warm air to help maintain the water temperature and warm the surface of the tub.

.

• Warranty: 5 Years on finishes and composite shell, 3 years on all moving and stationary parts.



۲



۲

The built-in disinfection system cabinet is conveniently located on the side of the tub for easy access. The lockable cabinet provides a secure place for cleaning supplies and disinfectants.



The Niagara Spring features an easy-to-use control panel which includes: the tub-fill and shower valves, water temperature display, thermostatic mixing valve, raise / lower controls, and CleanDrive Air Spa System control pad.



۲

57

SPECIFICATIONS

Width (Fixed Height):	35.5"
Length (Fixed Height):	84"
Height (Fixed Height):	32.5"
Transfer Device Access:	(Fixed Height): 10"
Width (Height Adjustable):	35.5"
Length (Height Adjustable):	90"
Height (Height Adjustable):	30" - 42"
Transfer Device Access:	(Height Adjustable): 5.5" - 7"
Water Supply Inlet:	3/4" diameter
Drain Size:	1.5"
Water Capacity (Occupied):	64 gallons
Fill Time:	4 minutes, 16 seconds
Drain Time:	1 minute, 36 seconds
Weight Capacity (resident):	600 lbs
Electrical Supply:	115V AC; 60Hz; 15 amp



Senior Mart 15791 Rockfield Blvd. Suite E. Irvine, CA 92691 (949) 340-9100