SAFETY DATA SHEET

1. Identification

Product number 1000002357

Product identifier **CAMIE 385 WEBBING SCREEN PRINTERS' ADHESIVE**

Company information Camie-Campbell, Inc.

1005 S. Westgate Drive

Addison, IL 60101 United States

www.camie.com

Company phone General Assistance 1-800-325-9572

Emergency telephone US 1-866-836-8855 Emergency telephone outside

1-952-852-4646

Version # 01

ADHESIVE Recommended use Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1 Skin corrosion/irritation Category 2 Health hazards Serious eye damage/eye irritation Category 2A

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. Hazard statement

Causes serious eye irritation. May cause drowsiness or dizziness.

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

> flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.

Wear protective gloves. Wear eye/face protection.

Response If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If

inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Specific treatment (see this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

Not classified.

Environmental hazards Hazardous to the aquatic environment, acute Category 3

Category 3 Hazardous to the aquatic environment,

long-term hazard

Supplemental information

Hazard statement Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Prevention Avoid release to the environment.

3. Composition/information on ingredients

Mixtures

Hazardous components

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	20 - 40
Dimethyl Ether		115-10-6	20 - 40
2-Methylpentane		107-83-5	10 - 20
3-Methylpentane		96-14-0	2.5 - 10
2,2-Dimethylbutane		75-83-2	1 - 2.5
2,3-Dimethylbutane		79-29-8	1 - 2.5
Other components below reportable	e levels		20 - 40

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical Skin contact

attention if irritation develops and persists. Wash clothing separately before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

General information

Aspiration may cause pulmonary edema and pneumonitis. Skin irritation. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Provide general supportive measures and treat symptomatically.

Take off all contaminated clothing immediately. Wash contaminated clothing before reuse. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect

themselves.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire-fighting equipment/instructions Water fog. Dry chemical powder. Alcohol resistant foam. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the MSDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Environmental manager must be informed of all major releases.

7. Handling and storage

Precautions for safe handling Do not handle or store near an open flame, heat or other sources of ignition. All equipment used

when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not spray on a naked flame or any other incandescent material. Use only in

well-ventilated areas. Provide adequate ventilation. Avoid breathing

dust/fume/gas/mist/vapors/spray. Avoid contact with skin, eyes and clothing. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective.

Do not re-use empty containers. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Keep away from heat, sparks and open flame. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the MSDS). Level 2 Aerosol.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Components	Type	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm	
US. ACGIH Threshold Limit Value	·s		
Components	Туре	Value	
2,2-Dimethylbutane (CAS 75-83-2)	STEL	1000 ppm	
,	TWA	500 ppm	
2,3-Dimethylbutane (CAS 79-29-8)	STEL	1000 ppm	
,	TWA	500 ppm	
2-Methylpentane (CAS 107-83-5)	STEL	1000 ppm	
35 37	TWA	500 ppm	
3-Methylpentane (CAS 96-14-0)	STEL	1000 ppm	
	TWA	500 ppm	
Acetone (CAS 67-64-1)	STEL	750 ppm	
,	TWA	500 ppm	
US. NIOSH: Pocket Guide to Cher	nical Hazards		
Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	
US. AIHA Workplace Environmen	tal Exposure Level (WEEL) Gui	des	
Components	Туре	Value	
Dimethyl Ether (CAS 115-10-6)	TWA	1880 mg/m3	
1.0.00,			

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time	
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*	

^{* -} For sampling details, please see the source document.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear protective gloves.

Other Wear appropriate chemical resistant clothing.

If engineering controls do not maintain airborne concentrations below recommended exposure Respiratory protection

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

1000 ppm

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Color Not available.
Form Aerosol.
Physical state Gas.

Boiling point $-115.6 \, ^{\circ}\text{F} \, (-82 \, ^{\circ}\text{C})$ estimated Flash point $82.98 \, ^{\circ}\text{F} \, (28.32 \, ^{\circ}\text{C})$ estimated

Melting point/freezing point Not available.

Odor Not available.

pH Not available.

Solubility(ies) Not available.

Vapor density Not available.

Vapor pressure 484.05 psig @70F estimated

Viscosity Not available.

Other information

Specific gravity 0.84 estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.

Hazardous decomposition

products

Avoid fleat, Sparks, open flames and other ignition sources. Contact with incompatible materia

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion Smallest quantities reaching the lungs through swallowing or subsequent vomiting may result in

lung edema or pneumonia. However, ingestion is not likely to be a primary route of occupational

exposure.

Inhalation No adverse effects due to inhalation are expected.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause central nervous system effects. Symptoms

of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Acute toxicity Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Product Species Test Results

12 OZ 385 WEBBING SCREEN PRINT LT 12PK (CAS Mixture)

Acute Dermal

LD50 Rabbit 74571.2188 mg/kg, estimated

74.5712 ml/kg, estimated

Rat 14388 mg/kg

Inhalation

LC50 Mouse 2115.3616 mg/l, 15 Minutes, estimated

1651.4335 mg/l, 30 Minutes, estimated

Rat 1320.0685 mg/l, 4 Hours, estimated

381 mg/l/4h

Product name: 12 OZ 385 WEBBING SCREEN PRINT LT 12PK

Product #: 1000002357 Version #: 01 Issue date: 05-29-2014

Product	Species	Test Results	
		186.8009 mg/l, 8 Hours, estimated	
Oral			
LD50	Mouse	11185.6826 mg/kg, estimated	
	Rabbit	19910.5137 mg/kg, estimated	
	Rat	7681 mg/kg	
Other			
LD50	Mouse	4835.9434 mg/kg, estimated	
	Rat	20507.084 mg/kg, estimated	
Components	Species	Test Results	
Acetone (CAS 67-64-1)			
Acute			
Dermal LD50	Dobbit	20000 mg/kg	
LD30	Rabbit	20000 mg/kg	
Laboratoria d		20 ml/kg	
Inhalation LC50	Rat	76 mg/l, 4 Hours	
2000	ria	50.1 mg/l, 8 Hours	
Oral		30.1 mg/i, 0 Hours	
LD50	Mouse	3000 mg/kg	
	Rabbit	5340 mg/kg	
	Rat	5800 mg/kg	
Other	· tat	ooo mg/kg	
LD50	Mouse	1297 mg/kg	
	Rat	5500 mg/kg	
Dimethyl Ether (CAS 115-10-6)		3 3	
Acute			
Inhalation			
LC50	Mouse	494.36 mg/l, 15 Minutes	
		385.94 mg/l, 30 Minutes	
	Rat	308.5 mg/l, 4 Hours	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye irritation	Causes serious eye irritation.		
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.		
Specific target organ toxicity - single exposure	Narcotic effects.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	May be fatal if swallowed and enters airways		
12. Ecological information	า		
Ecotoxicity	The product is not classified as environmenta	ally hazardous. However, this does not exclude the	

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product		Species	Test Results
12 OZ 385 WEBBING SCREEN PRINT LT 12PK (CAS Mixture)			
Algae	IC50	Algae	1551 mg/L, 72 Hours
Crustacea	EC50	Daphnia	10909 mg/L, 48 Hours
Fish	LC50	Fish	30.0485 mg/L, 96 Hours

Components Species Test Results

Acetone (CAS 67-64-1)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 21.6 - 23.9 mg/l, 48 hours
Fish LC50 Rainbow trout,donaldson trout 4740 - 6330 mg/l, 96 hours

(Oncorhynchus mykiss)

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

 Dimethyl Ether
 0.1

 Acetone
 -0.24

 2,3-Dimethylbutane
 3.42

 3-Methylpentane
 3.6

 2-Methylpentane
 3.74

 2,2-Dimethylbutane
 3.82

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

US RCRA Hazardous Waste U List: Reference

Acetone (CAS 67-64-1) U002

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es) 2.1

Subsidiary class(es) Not available. Packing group Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Labels required None
Special provisions N82
Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es) 2.1 Subsidiary class(es) -

Packaging group Not available.

Environmental hazards No Labels required 2.1 ERG Code 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions LTD QTY

IMDG

UN number UN1950 UN proper shipping name AEROSOLS Transport hazard class(es) 2.1 Subsidiary class(es)

Packaging group Not available.

Environmental hazards

No Marine pollutant Labels required None

EmS Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Packaging Exceptions LTD QTY

Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable.

the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) LISTED

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

SARA 304 Emergency release notification

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

> Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely No

hazardous substance

SARA 311/312 Hazardous No

chemical

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Dimethyl Ether (CAS 115-10-6)

Safe Drinking Water Act Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 % weight/volumn

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

Food and Drug Not regulated.

Administration (FDA)

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

Dimethyl Ether (CAS 115-10-6) 500 lbs

US. Pennsylvania RTK - Hazardous Substances

2,2-Dimethylbutane (CAS 75-83-2) 2,3-Dimethylbutane (CAS 79-29-8) 2-Methylpentane (CAS 107-83-5) 3-Methylpentane (CAS 96-14-0)

Acetone (CAS 67-64-1) Dimethyl Ether (CAS 115-10-6)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reprod harm.

International Inventories

Country(s) or region Inventory name On inventory (yes/no)* Australian Inventory of Chemical Substances (AICS) Australia Nο Canada Domestic Substances List (DSL) Yes Canada Non-Domestic Substances List (NDSL) No Inventory of Existing Chemical Substances in China (IECSC) China No Nο

European Inventory of Existing Commercial Chemical Europe

Substances (EINECS)

European List of Notified Chemical Substances (ELINCS) Europe No Inventory of Existing and New Chemical Substances (ENCS) Japan No Korea Existing Chemicals List (ECL) No New Zealand New Zealand Inventory No **Philippines** Philippine Inventory of Chemicals and Chemical Substances Nο

(PICCS)

Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

05-29-2014 Issue date

Version # 01

United States & Puerto Rico

Further information Not available.

Disclaimer The information in the sheet was written based on the best knowledge and experience currently

available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with

any other materials or in any process, unless specified in the text.

Revision Information Product and Company Identification: Product Codes

Product name: 12 OZ 385 WEBBING SCREEN PRINT LT 12PK Product #: 1000002357 Version #: 01 Issue date: 05-29-2014 Yes