



Safety Data Sheet 900 Nylon Catalyst

SDS Revision Date:

02/24/2015

1. Identification

1.1. Product identifier

Product Identity 900 Nylon Catalyst
Alternate Names 900 Catalyst

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Screen Printing.
Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name International Coatings Company, Inc.
13929 East 166th Street
Cerritos, CA 90702-7666

Emergency

24 hour Emergency Telephone No. (800) 255-3924
Customer Service: International Coatings Company, Inc. (562) 926-1010

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Acute Tox. 3;H331	Toxic if inhaled.
Skin Irrit. 3;H316	Causes mild skin irritation. (Not adopted by US OSHA)
Skin Sens. 1;H317	May cause an allergic skin reaction.
Resp. Sens. 1;H334	May cause allergy or asthma symptoms of breathing difficulties if inhaled.
Carc. 2;H351	Suspected of causing cancer.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

H316 Causes mild skin irritation.
H317 May cause an allergic skin reaction.
H331 Toxic if inhaled.

Safety Data Sheet

900 Nylon Catalyst

SDS Revision Date:

02/24/2015



H334 May cause allergic or asthmatic symptoms or breathing difficulties if inhaled.

H351 Suspected of causing cancer.

[Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P308+313 IF exposed or concerned: Get medical advice / attention.

P321 Specific treatment (see information on this label).

P333+313 If skin irritation or a rash occurs: Get medical advice / attention.

P341 If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P342+311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor / physician.

P363 Wash contaminated clothing before reuse.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Toluene di-isocyanate CAS Number: 0026471-62-5	0.1 - 1	Carc. 2;H351 Acute Tox. 2;H330 Eye Irrit. 2;H319 STOT SE 3;H335 Skin Irrit. 2;H315 Resp. Sens. 1;H334 Skin Sens. 1;H317 Aquatic Chronic 3;H412	[1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

Safety Data Sheet

900 Nylon Catalyst

SDS Revision Date:

02/24/2015



4. First aid measures

4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If the person is conscious, induce vomiting immediately by giving 2 glasses of water and pressing finger down the throat. Repeat until vomit is clear, then give milk. Contact a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Overview	<p>Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.</p> <p>Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 3 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure. See section 2 for further details.</p>
Inhalation	Toxic if inhaled. May cause allergy or asthma symptoms of breathing difficulties if inhaled.
Skin	May cause an allergic skin reaction. Causes mild skin irritation. (Not adopted by US OSHA)

5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.
Do not use: water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Hydrogen chloride (if heated), carbon monoxide and carbon dioxide.

Safety Data Sheet

900 Nylon Catalyst

SDS Revision Date:

02/24/2015



Avoid breathing dust / fume / gas / mist / vapors / spray.

5.3. Advice for fire-fighters

In the event of fire, wear full protective clothing and NIOSH Approved Self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode. Move container from fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapors.

ERG Guide No. ----

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment as listed in Section 8 during clean up operations.

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations. (See section 13).

Clean, preferably with a detergent. Do not use solvents.

Do not allow spills to enter drains or watercourses.

If drains, sewers, streams or lakes are contaminated, inform the local water company immediately. In the case of contamination of rivers, streams or lakes the Environmental Protection Agency should also be informed.

7. Handling and storage

7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Store in cool dry place. Elevated temperatures thicken product and shorten useful life.

Incompatible materials: Composition: Avoid contact with strong acids, alkali or oxidizing agents.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

Safety Data Sheet

900 Nylon Catalyst

SDS Revision Date:

02/24/2015



8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0026471-62-5	Toluene di-isocyanate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0026471-62-5	Toluene di-isocyanate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: Yes
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory

Not Required

Eyes

Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids.

Skin

Neoprene gloves are recommended.

Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance

Smooth thick Liquid

Odor

Faint

Odor threshold

Not Measured

pH

Not Measured

Melting point / freezing point

Not Measured

Initial boiling point and boiling range

>420 F @5mmhg

Flash Point

>400 F C.O.C.

Safety Data Sheet

900 Nylon Catalyst

SDS Revision Date:

02/24/2015



Evaporation rate (Ether = 1)	< 1
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: Not Measured Upper Explosive Limit: Not Measured
Vapor pressure (Pa)	Not Measured
Vapor Density	> 1 (Air=1)
Specific Gravity	1.05 - 1.15
Solubility in Water	Insoluble
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
VOC Content	< 0.1 lb/gallon
% Volatile	< 1

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid exposure to heat and humidity.

10.5. Incompatible materials

Composition: Avoid contact with strong acids, alkali or oxidizing agents.

10.6. Hazardous decomposition products

Hydrogen chloride (if heated), carbon monoxide and carbon dioxide.

Safety Data Sheet

900 Nylon Catalyst

SDS Revision Date:

02/24/2015



11. Toxicological information

Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Toluene di-isocyanate - (26471-62-5)	3,360.00, Rat - Category: 5	No data available	0.35, Rat - Category: 1	No data available	13.90, Rat - Category: 1

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	3	Toxic if inhaled.
Skin corrosion/irritation	3	Causes mild skin irritation. (Not adopted by US OSHA)
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	1	May cause allergy or asthma symptoms of breathing difficulties if inhaled.
Skin sensitization	1	May cause an allergic skin reaction.
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	2	Suspected of causing cancer.
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

12. Ecological information

12.1. Toxicity

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and GHS and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details

Safety Data Sheet

900 Nylon Catalyst

SDS Revision Date:

02/24/2015



Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Toluene di-isocyanate - (26471-62-5)	133.00, Oncorhynchus mykiss	12.50, Daphnia magna	3,230.00 (96 hr), Skeletonema costatum

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable		
14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: No		
14.6. Special precautions for user	No further information		

Safety Data Sheet

900 Nylon Catalyst

SDS Revision Date:

02/24/2015



15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA Inventory.

WHMIS Classification D1B

US EPA Tier II Hazards

Fire: No
Sudden Release of Pressure: No
Reactive: No
Immediate (Acute): Yes
Delayed (Chronic): Yes

EPCRA 311/312 Chemicals and RQs (lbs):

Toluene di-isocyanate (100.00)

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

Toluene di-isocyanate

Proposition 65 - Carcinogens (>0.0%):

Toluene di-isocyanate

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%):

Toluene di-isocyanate

Pennsylvania RTK Substances (>1%):

Toluene di-isocyanate

Safety Data Sheet

900 Nylon Catalyst

SDS Revision Date:

02/24/2015



16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H334 May cause allergic or asthmatic symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H412 Harmful to aquatic life with long lasting effects.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

International Coatings Co., Inc. believes to the best of its knowledge that the information provided herein, is factual and the recommendations made are accurate as of the date shown. However, no representation or warranty is made as to their completeness or accuracy.

End of Document