CG-2 Press Wash

## **General Desciption**

CG-2 is best suited for clean-up of plastisol ink. Use this product as a screen opener, as a screen wash when saving the emulsion, and as a press wipe during continuous printing. This product is also an excellent cleaner for the removal of pallet or belt printers' adhesive.

This product can be used in a wide variety of innovative cleaning processes ranging from re-circulation machines, dip tanks, or precision immersion cleaning processes. It may also be applied manually by a brush or a hand held sprayer. CG-2 is fast drying and leaves no film or oil residue so that the clean surface is in excellent condition for tape adhesion.

## **Advantages**

- High Solvency
- Low Odor
- Mesh Safe
- Emulsion Safe
- Low Vapor Pressure
- · High Load Capacity To Reduce Usage
- Multiple Applications

## **Application**

Always card excessive ink from screen. Use one of the following applications.

## PRESS WASH AND SCREEN OPENER



**Step 1**. Spray **CG-2** on the squeegee side of screen.



**Step 2**. Scrub ink with a non-absorbent pad until liquified.



**Quick Tip:** 

To cut down on

the number or rags

it takes to clean a

screen, use a non

absorbent scrub

pad to liquify the

ink and a squee-

gee to pull all the

ink to one end of

wipe up with one

the screen and

or two rags.

**Step 3**. Use rags or towels to wipe up ink residue. Re-apply to clean up ink residue in image area.



Recirculating Wash:

Card excessive ink from the screen. **CG-2** can be continuously recirculated until product becomes too heavily soiled with solids. Used product may be filtered and reused.

SQ-1000

Sizes Available:

Quart Gallon 4 x 1 Gallon 5 Gallon Pail 55 Gallon Drum