



EASISTRIP

ONE STEP INK CLEANER & EMULSION REMOVER

FOR MANUAL USE

EasiStrip One Step Ink Cleaner & Emulsion Remover is designed to dissolve plastisol inks and remove emulsion from the screen printing mesh-at the same time. This product is for use in a dip tank-for superior time and chemical savings. EasiStrip is a concentrated liquid and designed to be mixed with water 1:2 while remaining homogenous.

SPECIAL FEATURES:

- Dissolves and cleans ink, emulsion & blockout in one step which makes the job of screen reclaiming much faster and more efficient.
- Has no odor which makes the job of screen reclaiming more pleasant.
- EasiStrip has no VOC's making this product safer than solvents for air quality concerns.

APPLICATION FOR MANUAL USE:

- Scrape excess ink from screen.
- Apply EasiStrip (full strength) by brush, wipe, scrub pad or spray to the print side of the screen and scrub.
- High pressure rinse from the print side, follow with opposite side
- Flood rinse entire screen with low pressure rinse.
- If stubborn stains remain, apply an Easiway Systems approved stain remover, scrub & rinse.

PHYSICAL AND CHEMICAL DATA:

Appearance & Odor:

Clear liquid with mild odor

Specific Gravity:

1.02 @ 20° C / 68° F

pH:

2-3

VOC:

None

Flash Point:

None

Ink Types:

Plastisol

Product Families:

Textile



EASISTRIP

ONE STEP INK CLEANER & EMULSION REMOVER

FOR MANUAL USE

EasiStrip One Step Ink Cleaner & Emulsion Remover is designed to dissolve plastisol inks and remove emulsion from the screen printing mesh-at the same time. This product is for use in a dip tank-for superior time and chemical savings. EasiStrip is a concentrated liquid and designed to be mixed with water 1:2 while remaining homogenous.

SPECIAL FEATURES:

- Dissolves and cleans ink, emulsion & blockout in one step which makes the job of screen reclaiming much faster and more efficient.
- Has no odor which makes the job of screen reclaiming more pleasant.
- EasiStrip has no VOC's making this product safer than solvents for air quality concerns.

APPLICATION FOR USE IN A DIP TANK:

- Mix EasiStrip SUPRA at a ratio of up to 1:5 with water in a plastic tank.
- Scrape excess ink from screen.
- Place screen in dip tank.
- Let soak in tank until the emulsion/film loosens from the screen. Usually 2-3 mins.
- High pressure rinse screen, then flood rinse.
- If stubborn stains remain, apply an Easiway Systems approved stain remover.

PHYSICAL AND CHEMICAL DATA:

Appearance & Odor:

Clear liquid with mild odor

Specific Gravity:

1.02 @ 20° C / 68° F

pH:

2-3

VOC:

None

Flash Point:

None

Ink Types:

Plastisol

Product Families:

Textile