# SAFETY DATA SHEET

## FOR INDUSTRIAL USE ONLY

#### **EPOXY HARDENER 2001**

# Section 1. Product and company identification

**GHS product identifier** : Epoxy Hardener 2001

Product type : Curing Agent

Manufacturer/Supplier/

**Importer** 

Douglas and Sturgess, Inc.

1023 Factory Street Richmond, Ca, 94801

**Telephone** : 510-235-8411

**Emergency telephone number** : CHEMTREC 1-(800)-424-9300

# Section 2. Hazards identification

Classification of the substance or mixture

ACUTE TOXICITY:oral - Category 4
ACUTE TOXICITY:dermal - Category 4

SKIN CORROSION/IRRITATION - Category 1B

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

RESPIRATORY SENSITIZATION - Category 1

SKIN SENSITIZATION - Category 1

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)

[Respiratory tract irritation, Narcotic effects] - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED

EXPOSURE) [skin, central nervous system (CNS), respiratory tract] -

Category 1

**GHS label elements** 

Hazard pictograms



Signal word : Dange

Epoxy Hardener 2001 Page: 2/14

**Hazard statements** 

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties

if inhaled.

H317 May cause an allergic skin reaction.

H335 H336 May cause respiratory irritation.

May cause drowsiness and dizziness.

H372 Causes damage to organs through prolonged or repeated exposure: (skin, central nervous system (CNS), respiratory tract)

#### **Precautionary statements**

General Not applicable.

Prevention Wear protective gloves.

Wear eye or face protection.

Wear protective clothing.

In case of inadequate ventilation wear respiratory protection.

Use only outdoors or in a well-ventilated area.

Do not breathe vapor.

Do not eat, drink or smoke when using this product.

Wash hands thoroughly after handling.

Contaminated work clothing should not be allowed out of the

workplace.

Get medical attention if you feel unwell. Response

IF INHALED:

Remove victim to fresh air and keep at rest in a position comfortable

for breathing.

Immediately call a POISON CENTER or physician.

If experiencing respiratory symptoms: Call a POISON CENTER or physician.

IF SWALLOWED:

Immediately call a POISON CENTER or physician.

Rinse mouth.

Do NOT induce vomiting.

IF ON SKIN (or hair):

Take off immediately all contaminated clothing.

Rinse skin with water or shower.

Wash contaminated clothing before reuse.

Immediately call a POISON CENTER or physician.

IF ON SKIN:

Wash with plenty of soap and water.

Call a POISON CENTER or physician if you feel unwell.

If skin irritation or rash occurs:

Get medical attention.

IF IN EYES:

Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or physician.

Storage Store locked up.

Date of previous issue: 11/20/2010 Version. 11.0 Date of issue/Date of revision: 05/19/2015

Epoxy Hardener 2001 Page: 3/14

**Disposal** 

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not result in classification

None known.

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% by weight	CAS
		number
Isophorone Diamine	35 - 50	2855-13-2
Benzyl Alcohol	35 - 50	100-51-6
Amine-Epoxy Resin Adduct (Proprietary)	15 - 20	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### **Description of necessary first aid measures**

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. In the event of any complaints or symptoms, avoid further exposure.

Skin contact

Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician.

Epoxy Hardener 2001 Page: 4/14

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments
Protection of first aid personnel

No specific treatment.

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# **Section 5. Fire-fighting measures**

### **Extinguishing media**

Suitable extinguishing media Unsuitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

None known.

Specific hazards arising from the chemical

Hazardous thermal decomposition products

: In a fire or if heated, a pressure increase will occur and the container may burst.

 Decomposition products may include the following materials: carbon oxides nitrogen oxides

other organic compounds

Special protective actions for firefighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and

Epoxy Hardener 2001 Page: 5/14

unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

 Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13 of SDS). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

# Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** 

Put on appropriate personal protective equipment (see section 8 of SDS). Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Store locked up. Keep container tightly closed and sealed

Epoxy Hardener 2001 Page: 6/14

until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

### **Control parameters**

### **Occupational exposure limits**

Ingredient name		Exposure limits
Benzyl Alcohol		AIHA WEEL (1999-01-01) Time Weighted Average (TWA) 10 ppm NIOSH REL (2005-09-30)
Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures  Eye/face protection	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

### **Skin protection**

Hand protection : Chemical-resistant, impervious gloves complying with an approved

Epoxy Hardener 2001 Page: 7/14

standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection**: Personal protective equipment for the body should be selected based

on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

**Respiratory protection**: Use a properly fitted, air-purifying or air-fed respirator complying with

an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the

selected respirator.

# Section 9. Physical and chemical properties

#### **Appearance**

Physical state : Liquid
Color : Not available

Odor : amine.

Odor threshold : Not available

pH : Not available

**Melting point**/ Freezing point : Not available

**Boiling point** : 205 - 248 °C (401.00 - 478.40 °F)

**Flash point** : 93.4 °C (200.12 °F)

Burning time: Not availableBurning rate: Not availableEvaporation rate: Not available

Flammability (solid, gas) : Not available

Lower and upper explosive : Lower: Not available (flammable) limits : Upper: Not available

Vapor pressure : Not available

Vapor density : Not available

**Relative density** : Not available

Solubility : Not available

**Solubility in water** : Partial

Epoxy Hardener 2001 Page: 8/14

Partition coefficient: n-

octanol/water

Auto-ignition temperature

Not available

Not available

**Decomposition temperature** 

SADT

Not available
Not available

Viscosity

: **Dynamic:** Not available

Kinematic: Not available

#### Other information

No additional information.

# Section 10. Stability and reactivity

**Reactivity** : Stable under normal conditions.

**Chemical stability** : The product is stable.

**Possibility of hazardous reactions**: Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid : Avoid exposure - obtain special instructions before use. Keep away

from heat, sparks, flame and other ignition sources.

**Incompatible materials** : strong oxidizing agents,

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Other hazards Heating this substance above 300 deg. F in the presence of air may

cause slow oxidative decomposition; above 500 deg. F polymerization

may occur.

Some combinations of resins and curing agents can produce exothermic reactions which in large masses can cause runaway

polymerization and charring of the reactants

Fumes and vapors from the thermal and chemical decompositions

vary widely in composition and toxicity.

# Section 11. Toxicological information

### **Information on toxicological effects**

## **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure		
Isophorone Diamine	Isophorone Diamine					
	LD50 Oral	Rat	1,030 mg/kg	-		
Benzyl Alcohol	Benzyl Alcohol					
	LD50 Oral	Rat	1,230 mg/kg	-		
	LC50 Inhalation	Rat	> 4.178 mg/l	4 h		
	LD50 Dermal	Rabbit	2,000 mg/kg	-		

Conclusion/Summary : Not available

Epoxy Hardener 2001 Page: 9/14

## **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Benzyl Alcohol	Skin - Moderate	Rabbit		24 hrs	-
	irritant				

Conclusion/Summary

Skin:Not availableeyes:Not availableRespiratory:Not available

**Sensitization** 

Conclusion/Summary

Skin : Not available Respiratory : Not available

Mutagenicity

Conclusion/Summary : Not available

Carcinogenicity

Conclusion/Summary : Not available

**Reproductive toxicity** 

Conclusion/Summary : Not available

**Teratogenicity** 

Conclusion/Summary : Not available

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Isophorone Diamine	Category 3		Respiratory tract irritation
Benzyl Alcohol	Category 3		Respiratory tract irritation Narcotic effects
Amine-Epoxy Resin Adduct (Proprietary)	Category 3		Respiratory tract irritation

**Specific target organ toxicity (repeated exposure)** 

Product/ingredient name	Category	Route of exposure	Target organs
Benzyl Alcohol	Category 1		central nervous system (CNS)
Amine-Epoxy Resin Adduct (Proprietary)	Category 1		skin respiratory tract

## **Aspiration hazard**

Not available

Epoxy Hardener 2001 Page: 10/14

Information on the likely routes of

exposure

: Not available

#### Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation** : Can cause central nervous system (CNS) depression. May cause

drowsiness and dizziness. May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Exposure to decomposition products may cause a health hazard.

Serious effects may be delayed following exposure.

Skin contact : Causes severe burns. Harmful in contact with skin. May cause an

allergic skin reaction.

**Ingestion**: Harmful if swallowed. Can cause central nervous system (CNS)

depression. May cause burns to mouth, throat and stomach.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain watering redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

wheezing and breathing difficulties

asthma

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

**Ingestion** : Adverse symptoms may include the following:

stomach pains

#### Delayed and immediate effects and also chronic effects from short and long term exposure

### **Short term exposure**

Potential immediate effects: Not availablePotential delayed effects: Not available

Long term exposure

Potential immediate effects: Not availablePotential delayed effects: Not available

**Potential chronic health effects** 

Conclusion/Summary : Not available

Epoxy Hardener 2001 Page: 11/14

**General** : Causes damage to organs through prolonged or repeated exposure:

Once sensitized, a severe allergic reaction may occur when

subsequently exposed to very low levels.

Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

#### Acute toxicity estimates

Not available

# **Section 12. Ecological information**

### **Toxicity**

Product/ingredient name	Result	Species	Exposure
benzyl alcohol			
	Acute LC50 10,000 μg/l Fresh water	Fish - Bluegill	96 h

Conclusion/Summary : Not available

Persistence/degradability

Conclusion/Summary : Not available

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Benzyl Alcohol	1.1	-	low

#### **Mobility in soil**

Soil/water partition coefficient

: Not available

(KOC)

Other adverse effects

: No known significant effects or critical hazards.

# **Section 13. Disposal considerations**

### Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered

Epoxy Hardener 2001 Page: 12/14

when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

#### **International transport regulations**

Regulatory information	UN/NA number	Proper shipping name	Classes/*PG	Reportable Quantity (RQ)
CFR	2289	ISOPHORONEDIAMINE SOLUTION	Class 8 III	
IMO/IMDG	2289	ISOPHORONEDIAMINE SOLUTION	Class 8 III	
IATA (Cargo)	2289	ISOPHORONEDIAMINE SOLUTION	Class 8 III	

\*PG: Packing group

Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.'

# **Section 15. Regulatory information**

#### **United States**

U.S. Federal regulations : United States - TSCA 12(b) - Chemical export notification: None

required.

United States - TSCA 5(a)2 - Final significant new use rules: Not listed United States - TSCA 5(a)2 - Proposed significant new use rules: Not

listed

United States - TSCA 5(e) - Substances consent order: Not listed

<u>California Prop. 65:</u> : None required.

**United States inventory (TSCA**: All components are listed or exempted.

8b)

Epoxy Hardener 2001 Page: 13/14

#### Canada

WHMIS (Canada) : Class D-1B: Material causing immediate and serious toxic effects (Toxic).

Class D-2A: Material causing other toxic effects (Very toxic). Class D-2B: Material causing other toxic effects (Toxic).

**Canadian lists** 

Canadian NPRI : None required.

CEPA Toxic substances : None required.

### **International regulations**

International lists : Australia inventory (AICS): All components are listed or exempted.

**Taiwan inventory (CSNN):** All components are listed or exempted.

Canada inventory: All components are listed or exempted. Japan inventory: All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

**Korea inventory:** All components are listed or exempted.

New Zealand Inventory (NZIoC): All components are listed or exempted. Philippines inventory (PICCS): All components are listed or exempted. United States inventory (TSCA 8b): All components are listed or exempted.

## **Section 16. Other information**

Hazardous Material Information System III (U.S.A.):

Health	*	2
Flammability		1
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Full text of abbreviated H

statements

: Not applicable.

### **History**

Date of printing: 05/20/2015Date of issue/Date of revision: 05/19/2015Date of previous issue: 11/20/2010Version: 11.0

Prepared by

Key to abbreviations

: Product Safety Stewardship

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

Epoxy Hardener 2001 Page: 14/14

IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL 73/78 = International Convention for the Prevention of Pollution From
Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
RID = The Regulations concerning the International Carriage of Dangerous Goods by

Rail

UN = United Nations

**References** : Not available

#### Notice to reader

**Training Advice:** Train personnel using this product in proper chemical handling, engineering controls and protective equipment.

**Recommended Uses and Restrictions:** This product is intended for industrial/professional use only.

**Disclaimer:** This data is offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.