830-5515 CAL-TINT®II PHTHALO GREEN

Specification: 000000139799 Revision Date:

Version Number: 01



1. Identification

Product identifier 830-5515 CAL-TINT®II PHTHALO GREEN

Other means of identification

SAP Specification 000000139799
Recommended use Aqueous colorant
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company Chromaflo Technologies Corporation

2600 Michigan Avenue Ashtabula, OH 44005-0816

USA

 Telephone
 440-997-5137

 Telefax
 440-992-3613

 US: CHEMTREC
 800-424-9300

EMERGENCY NUMBER

CANADA: CANUTEC 613-996-6666

EMERGENCY NUMBER

Product Regulatory 440-536-9691

Services

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information If product is in liquid or paste form, physical or health hazards listed related to dust are not

considered significant. However, product may contain substances that could be potential hazards

if caused to become airborne due to grinding, sanding or other abrasive processes.

3. Hazardous components

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ethanediol; ethylene glycol		107-21-1	20 - 40
Talc, Magnesium silicate hydrate		14807-96-6	20 - 40
Diethylene glycol		111-46-6	2.5 - 10
Silica, crystalline (quartz)		14808-60-7	0.1 - 1
Other components below reportable le	evels		40 - 60

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Material name: 830-5515 CAL-TINT®II PHTHALO GREEN

17119 Version #: 01 Issue date: 05-16-2015

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Rinse with water. Get medical attention if irritation develops and persists. Eve contact

Rinse mouth. Get medical attention if symptoms occur. Ingestion Most important Direct contact with eyes may cause temporary irritation.

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

Treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters During fire, gases hazardous to health may be formed.

Do not use water jet as an extinguisher, as this will spread the fire.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Fire-fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Methods and materials for containment and cleaning up

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. For personal protection, see section 8 of the SDS.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid prolonged exposure. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Silica, crystalline (quartz) (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
		2.4 millions of particle	Respirable.
Talc, Magnesium silicate hydrate (CAS 14807-96-6)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3 20 millions of particle	Respirable.
		2.4 millions of particle	Respirable.

Material name: 830-5515 CAL-TINT®II PHTHALO GREEN

17119 Version #: 01 Issue date: 05-16-2015 2/7

US. ACGIH Threshold Limit Values				
Components	Туре	Value	Form	
ethanediol; ethylene glycol (CAS 107-21-1)	Ceiling	100 mg/m3	Aerosol.	
Silica, crystalline (quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.	
Talc, Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.	
US. NIOSH: Pocket Guide to Cher	nical Hazards			
Components	Туре	Value	Form	
Silica, crystalline (quartz) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.	

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Talc, Magnesium silicate hydrate (CAS 14807-96-6)

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been

2 mg/m3

Respirable.

established, maintain airborne levels to an acceptable level.

TWA

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves.

Other Wear appropriate chemical resistant clothing.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to

vapor/mist at levels exceeding the exposure limits.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color Green.
Odor Mild.

Odor threshold Not available.

PH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point 247.6 °F (119.8 °C) estimated

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.
Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature Decomposition temperature Not available. Not available. Not available.

Other information

Viscosity

19.32 lbs/gal Density

Flammability class Combustible IIIB estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials. Strong oxidizing agents. Peroxides. Phenols.

Incompatible materials Hazardous decomposition

No hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Ingestion Expected to be a low ingestion hazard. Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected. Eye contact Direct contact with eyes may cause temporary irritation. Symptoms related to the Direct contact with eyes may cause temporary irritation.

physical, chemical and toxicological characteristics

Information on toxicological effects

Acute toxicity

Product	Species Test Results	
330-5515 CAL-TINT®II PH	THALO GREEN (CAS Mixture)	
Acute		
Dermal		
LD50	Rabbit	38169.582 mg/kg estimated
Inhalation		
LC50	Mouse	16560 mg/l, 4 Hours estimated
		16000 mg/l, 2 Hours estimated
	Rat	32800 mg/l, 0.5 Hours estimated
Oral		
LD50	Cat	7058.5518 mg/kg estimated
	Dog	22961.5586 mg/kg estimated
	Guinea pig	39.4415 g/kg estimated
	Mouse	55.134 g/kg estimated
	Rabbit	515.0168 g/kg estimated
	Rat	28.3415 g/kg estimated
Other		
LD50	Mouse	24.2505 g/kg estimated
	Rabbit	38347.7227 mg/kg estimated
	Rat	12308.7715 mg/kg estimated
Components	Species	Test Results

ethanediol; ethylene glycol (CAS 107-21-1)

Acute Dermal

LD50 Rabbit 9530 mg/kg

Components	Species	Test Results	
Oral			
LD50	Cat	1650 mg/kg	
	Dog	5500 mg/kg	
	Guinea pig	8.2 g/kg	
	Mouse	14.6 g/kg	
	Rat	5.89 g/kg	
Other			
LD50	Mouse	5.8 g/kg	
	Rat	2800 mg/kg	

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Silica, crystalline (quartz) (CAS 14808-60-7) 1 Carcinogenic to humans.

Talc, Magnesium silicate hydrate (CAS 14807-96-6)

2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Silica, crystalline (quartz) (CAS 14808-60-7)

Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product		Species	Test Results
830-5515 CAL-TINT	®II PHTHALO GREE	N (CAS Mixture)	
Fish	LC50	Fish	50419.5742 mg/l, 96 hours estimated
Components		Species	Test Results

ethanediol; ethylene glycol (CAS 107-21-1)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) 8050 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

ethanediol; ethylene glycol -1.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

Material name: 830-5515 CAL-TINT®II PHTHALO GREEN

17119 Version #: 01 Issue date: 05-16-2015 5 /

^{*} Estimates for product may be based on additional component data not shown.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions)

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not available.

the IBC Code

15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ethanediol; ethylene glycol (CAS 107-21-1)

Listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

quantity planning quantity planning quantity, planning lower value upper v
--

formaldehyde 50-00-0 100 500 lbs

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
ethanediol; ethylene glycol	107-21-1	20 - 40	
formaldehyde	50-00-0	0 - 0.1	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ethanediol; ethylene glycol (CAS 107-21-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

ethanediol; ethylene glycol (CAS 107-21-1) Silica, crystalline (quartz) (CAS 14808-60-7)

Material name: 830-5515 CAL-TINT®II PHTHALO GREEN

17119 Version #: 01 Issue date: 05-16-2015

Talc, Magnesium silicate hydrate (CAS 14807-96-6)

US. New Jersey Worker and Community Right-to-Know Act

ethanediol; ethylene glycol (CAS 107-21-1) 500 lbs

US. Pennsylvania RTK - Hazardous Substances

ethanediol; ethylene glycol (CAS 107-21-1) Silica, crystalline (quartz) (CAS 14808-60-7)

Talc, Magnesium silicate hydrate (CAS 14807-96-6)

US. Rhode Island RTK

ethanediol; ethylene glycol (CAS 107-21-1)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

formaldehyde (CAS 50-00-0) Listed: January 1, 1988 Silica, crystalline (quartz) (CAS 14808-60-7) Listed: October 1, 1988 Titanium dioxide (CAS 13463-67-7) Listed: September 2, 2011

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

05-16-2015 Issue date

Version # 01

United States & Puerto Rico

Disclaimer The information contained herein is based on data believed to be reliable and the manufacturer

disclaims any liability incurred from the use or reliance upon the same. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses. The information in the sheet was written based on the best

knowledge and experience currently available.

Toxic Substances Control Act (TSCA) Inventory

Product and Company Identification: Product and Company Identification Revision Information

Physical & Chemical Properties: Multiple Properties

Material name: 830-5515 CAL-TINT®II PHTHALO GREEN 17119 Version #: 01 Issue date: 05-16-2015

Yes