

## SAFETY DATA SHEET #2420 REVISION #8 DATE REVISED: 05/05/2015

**1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION** 

Trade Name(s): (CELITE<sup>®</sup> = C) C219, C233, C263, C281, C388, C427A, C499, SUPER FINE SUPER FLOSS<sup>®</sup>, SUPER FLOSS<sup>®</sup>, WHITE MIST<sup>®</sup> (ALL), CWPP8

 Generic Name:
 FLUX CALCINED DIATOMACEOUS EARTH

 Chemical Name:
 SILICA

 Manufacturer:
 Imerys

 Address:
 1732 North First Street, Suite 450

 City:
 San Jose
 State:
 CA
 Zip: 95112

CAS: 68855-54-9 EINECS: 272-489-0 Formula: SiO<sub>2</sub> Telephone: (805) 737-1239 Emergency: CHEMTREC – USA: (800) 424-9300 International: +01 (703) 527-3887 (collect)

2. HAZARD IDENTIFICATION



SIGNAL WORD: DANGER

HAZARD PHRASE H372: CAUSES DAMAGE TO LUNGS THROUGH PROLONGED OR REPEATED EXPSOSURE BY INHALATION. PRECAUTIONARY PHRASE P260: DO NOT BREATHE DUST. PRECAUTIONARY PHRASE P285: IN CASE OF INADEQUATE VENTILATION, WEAR RESPIRATORY PROTECTION.

PRECAUTIONARY PHRASE P205. IN CASE OF INADEQUATE VENTILATION, WEAR RESPIRATORY PROTECTION PRECAUTIONARY PHRASE P501: DISPOSE OF CONTENTS IN ACCORDANCE WITH LOCAL REGULATIONS.

THIS PRODUCT CONTAINS CRYSTALLINE SILICA (CS) WHICH IS CONSIDERED A HAZARD BY INHALATION. IARC HAS CLASSIFIED INHALATION OF CS AS A CARCINOGEN FOR HUMANS (GROUP 1). CS IS LISTED BY NTP AS A KNOWN HUMAN CARCINOGEN. INHALATION OF CS IS ALSO A KNOWN CAUSE OF SILICOSIS, A NON-CANCEROUS LUNG DISEASE.

3. COMPOSITION/INFORMATION ON INGREDIENTS							
INGREDIENT NAME:	CAS NUMBER:	%	PEL AND TLV (except as noted)				
FLUX CALCINED DIATOMACEOUS EARTH (DE)	68855-54-9	100					
THIS PRODUCT MAY CONTAIN UP TO 72.5% CRYSTALLINE SILICA:							
CRISTOBALITE	14464-46-1	< 70	.025mg/M₃RESPIRABLE CRISTOBALITE, ACGIH				
QUARTZ	14808-60-7	< 2.5	.025mg/M₃RESPIRABLE QUARTZ, ACGIH				
4. FIRST AID MEASURES							
Inhalation: REMOVE TO FRESH AIR. DRINK WATER TO CLEAR THROAT AND BLOW NOSE TO EVACUATE DUST.							
Eyes: FLUSH EYES WITH LARGE QUANTITIES OF WATER. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.							
Skin Contact: NA Skin Absorption: NA	A In	gestion: NA					
5. FIRE FIGHTING MEASURES							
Flash Point (Method): NONFLAMMABLE NFPA Flammable/Combustible Liquid Classification: NA							
Flammable Limits: LEL: NA UEL: NA Auto-Ignition Temperature: NA							
Extinguishing Media: NA Unusual Fire or Explo	osion Hazards: NONE S	pecial Fire-F	Fighting Procedure: NONE				
6. ACCIDENTAL RELEASE MEASURES							
Procedure for Spill/ Leak: VACUUM CLEAN DUST WITH EQUIPMENT FITTED WITH HEPA FILTER. USE A DUST SUPPRESSANT SUCH AS WATER IF SWEEPING IS NECESSARY.							
7. HANDLING AND STORAGE							
MINIMIZE DUST GENERATION AND ACCUMULATION. AVOID BREATHING DUST. AVOID CONTACT WITH EYES. SEAL BROKEN BAGS IMMEDIATELY. CONTINUE TO FOLLOW ALL SDS/ LABEL WARNING WHEN HANDLING EMPTY CONTAINERS.							

SDS: 2420

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION							
Goggles: GOGGLES OR SAFETY GLASSES WITH SIDESHIELDS ARE RECOMMENDED.							
Gloves: NOT NORMALLY							
Respirator: <10X PEL, USE AN N95 QUARTER OR HALF MASK RESPIRATOR; <50X PEL, USE A FULL FACE RESPIRATOR EQUIPPED							
WITH N95 FILTERS; <200X PEL, USE A POWERED AIR PURIFYING RESPIRATOR (POSITIVE PRESSURE) WITH N95 FILTERS; >200X							
PEL, USE A FULL FACE, TYPE C SUPPLIED AIR RESPIRATOR (CONTINUOUS FLOW MODE).							
Ventilation: USE SUFFICIENT NATURAL OR MECHANICAL VENTILATION TO KEEP DUST LEVEL BELOW PEL.							
Other: Special Considerations for Repair/Maintenance of Contaminated Equipment: INSURE PROPER RESPIRATORY PROTECTION.							
				2			
				2			
		Safety Glasse	S Duct M	ock.			
9. PHYSICAL AND CHEMICAL PROPERTIES							
9. PHYSICAL AND CHEMICAL PROPERTIES Appearance and Odor: FINE WHITE POWDER, NO ODOR.							
Boiling Point:	NA	Evaporation Rate (	=1): NA	Specific Gravity (water = 1	): 2.3		
-			,				
Vapor Pressure:	NA	Melting Point:	NE		NIL		
Water Solubility (%):	NEGLIGIBLE	Vapor Density (Air=1):	NA	pH:	9.0-10.5		
10. STABILITY AND REACTIVITY							
MATERIAL IS STABLE.			HAZARDO	OUS POLYMERIZATION CANNOT OC	CUR		
Chemical Incompatibilitie			Condition	s to Avoid: NONE IN DESIGNED US	F		
enemiear meenipalionne		11. TOXICOLO					
				NSIDERED A HAZARD BY INHALATI			
				YNTP AS A KNOWN HUMAN CARCIN	NOGEIN. CS IS ALSO		
A KNOWN CAUSE OF SIL	ICOSIS, A NONCI						
12. ECOLOGICAL INFORMATION							
				MATERIAL WHICH HAS BECOME CO			
HAVE SIGNIFICANTLY DIFFERENT CHARACTERISTICS BASED ON THE CONTAMINANT AND SHOULD BE EVALUATED ACCORDINGLY							
13. DISPOSAL CONSIDERATIONS							
WASTE IS NOT HAZARDO	OUS AS DEFINED	BY RCRA (40 CFR 261).	OTHER STAT	E AND LOCAL REGULATIONS MAY	VARY, CONSULT		
LOCAL AGENCIES AS NEEDED. USED MATERIAL WHICH HAS BECOME CONTAMINATED MAY HAVE SIGNIFICANTLY DIFFERENT CHARACTERISTICS BASED ON THE CONTAMINANTS AND SHOULD BE EVALUATED ACCORDINGLY.							
14. TRANSPORTATION INFORMATION							
	D.O.T. Proper Shipping Name: EARTH, DIATOMACEOUS, CRUDE OR GROUND Hazard Classification: Not Classified						
Reportable Quantities:	NA		UN (Unite	d Nations), NA (North America) Num	nber: NA		
15. REGULATORY INFORMATION							
OSHA Hazard Communications Standard, 29 CFR 1910.1200: MATERIAL IS CONSIDERED HAZARDOUS, SEE SECTION 3.							
RCRA: THIS MATERIAL IS NOT DEFINED AS HAZARDOUS WASTE PER 40 CFR 261.							
TSCA: THIS MATERIAL IS LISTED IN THE TSCA INVENTORY, AND IS NOT OTHERWISE REGULATED BY TSCA SEC. 4, 5, 6, 7 OR 12.							
CERCLA: MATERIAL IS NOT REPORTABLE UNDER CERCLA, LOCAL REQUIREMENTS MAY VARY.							
SARA: 311/312 HAZARD CATEGORIES -IMMEDIATE AND DELAYED HEALTH, 313 REPORTABLE INGREDIENTS - NONE.							
Canada: THIS PRODUCT IS LISTED ON THE DSL.							
California Proposition 65: THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.							
EU (REGULATION (EC) N° ° 1272/2008): THIS MATERIAL IS LABELED AND SUPPORTED ACCORDINGLY WITH GHS STANDARDS.							
European Inventory of Existing Chemicals (EINECS): ALL OF THE COMPONENTS OF THIS PRODUCT ARE INCLUDED ON EINECS.							
16. OTHER INFORMATION							
Storage Segregation Hazard Classes: NA							
Special Handling/Storage: REPAIR ALL BROKEN BAGS IMMEDIATELY.							
Special Workplace Engin	eering Controls:	ADEQUATE VENTILATIO	N TO KEEP D	UST LEVEL BELOW PEL.			
-,							
Drepared/Deviced http://	D. Drugo Consis	Conjor FUS Manager Lassa		norale (805) 727 1020			
		Senior EHS Manager, Imery		nerais, (805) 737-1239			
Revisions Made Since Last Version: Includes full GHS compliance and format.							

As of the date of preparation of this document, the foregoing information is believed to be accurate and is provided in good faith to comply with applicable federal and state law(s). However, no warranty or representation with respect to such information is intended or given. Always assume that unless this document is viewed on the Imerys Filtration technical library, this document may not be fully current and up-to-date Please log onto www.worldminerals.com and find the technical library section for the most recent and up-to-date SDS. End of SDS.