SECTION 1 - IDENTIFICATION

PRODUCT NAME: PANAX YELLOW F10G

US D.O.T. / UN NAME: NOT REGULATED FOR TRANSPORT

RECOMMENDED USES: ORGANIC YELLOW PIGMENT FOR USE IN PAINTS, COATINGS, ARTIST COLORS AND INKS COMPANY:

UNITED MINERAL & CHEMICAL CORPORATION 1050 Wall Street West, Ste. 660, Lyndhurst, NJ 07071 Tel: 201-507-3300 Fax: 201-507-1506 e-mail: inquiry@umccorp.com

CAS NO.

6486-23-3

7732-18-5

%

≤ 100

≤ 2

EMERGENCY TELEPHONE NO.:

USA – CHEMTREC: 1-800-424-9300 OUTSIDE USA: +1 703-527-3887

SECTION 2 – HAZARD IDENTIFICATION

GHS HAZARD CLASSIFICATION: NOT CLASSIFIED GHS LABEL ELEMENTS: SIGNAL WORD: NO SIGNAL WORD LABEL CODES / PICTOGRAMS: NO PICTOGRAMS HAZARD STATEMENTS: NONE UNDER GHS CLASSIFICATION

PRECAUTIONARY STATEMENTS :

PREVENTION : NONE ASSIGNED UNDER GHS RESPONSE : NONE ASSIGNED UNDER GHS STORAGE : NONE ASSIGNED UNDER GHS DISPOSAL : NONE ASSIGNED UNDER GHS

OTHER HAZARDS / U.S. - HAZARDS NOT OTHERWISE CLASSIFIED / UN GHS - OTHER HAZARDS WHICH DO NOT RESULT IN CLASSIFICATION: THIS MATERIAL IS AN ORGANIC PIGMENT/ FINE POWDER. DUST CLOUD FORMATION FROM PIGMENT POWDER MAY CREATE A DUST CLOUD EXPLOSION HAZARD. MAINTAIN GOOD HOUSEKEEPING TECHNIQUES TO CONTROL THE BUILDUP OF DUST. PROPERLY GROUND/BOND ALL PROCESSING/ HANDLING EQUIPMENT. AVOID CONTACT WITH ALL SOURCES OF IGNITION (FLAME / STATIC SPARK). NO COMBUSTIBLEDUST TEST RESULTS AVAILABLE.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL COMPOSITION: COMPONENTS:

C.I. PIGMENT YELLOW 3 WATER (AS POSSIBLE MOISTURE)

SYNONYMS: CI PIGMENT YELLOW 3, C.I. #;11710; HANSA YELLOW 10G;

BUTANAMIDE, 2-[(4-CHLORO-2-NITROPHENYL)AZO]-N-(2-CHLOROPHENYL)-3-OXO-

CHEMICAL FAMILY: INSOLUBLE MONOAZO ORGANIC PIGMENTS

SECTION 4 – FIRST AID MEASURES

FIRST AID/ RESPONSE FIRST AID RESPONDERS SHOULD WEAR PERSONAL PROTECTIVE EQUPMENT

SKIN :IF ON SKIN: PROMPTLY WASH OFF WITH SOAP & WATER.REMOVE CONTAMINATED CLOTHING. GET
MEDICAL ADVICE/ATTENTION IF IRRITATION OCCURS. WASH CONTAMINATED CLOTHING BEFORE REUSE.EYES :IF IN EYES: DO NOT RUB EYES. RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES.REMOVE
CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING. GET MEDICAL ADVICE/ATTENTION IF
IRRITATION OCCURS.INHALATION :IF INHALED: REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR
BREATHING. GET MEDICAL ADVISE / ATTENTION IF ANY ADVERSE SYMPTOMS OCCUR.INGESTION :IF SWALLOWED: RINSE MOUTH WITH WATER, THEN DRINK WATER TO DILUTE.INDUCE VOMITING ONLY
UNDER THE DIRECTION OF MEDICAL PERSONNEL.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

AS DUST, MAY CAUSE MECHANICAL IRRITATION TO SKIN, EYES, NOSE AND THROAT. CONTACT WITH SKIN WILL CAUSE TEMPORARY COLORATION OF CONTACTED AREA.

UNCONSCIOUS. GET MEDICAL ATTENTION IF LARGE QUANTITY IS INGESTED OR IF YOU FEEL UNWELL.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED, IF NECESSARY

CALL A POISON CENTER/DOCTOR/PHYSICIAN IF YOU FEEL UNWELL.

SECTION 5 – FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA :	WATER : (X-AS SPRAY/FOG) FOAM : (X) CO₂: (X) DRY CHEMICAL: (X) DO NOT USE HIGH PRESSURE WATER JET.			
SPECIFIC HAZARDS IN CASE OF FIRE :	HEAT/ FIRE CONDITIONS CAN EMIT HIGHLY TOXIC, IRRITATING, FLAMMABLE GASES / FUMES UPON BURNING. STAY UPWIND. TREAT AS A FLAMMABLE DUST IN THE FINELY DIVIDED AND SUSPENDED STATE. DUST CLOUD FORMATION FROM PIGMENT POWDER MAY CREATE A DUST CLOUD EXPLOSION HAZARD. PREVENT RUN OFF TO SEWERS AND BODIES OF WATER.			
SPECIAL PROTECTIVE EQUIPMENT & PRECAUTION FOR FIRE FIGHTERS :	IN CASE OF FIRE INVOLVING THIS MATERIAL, DO NOT ENTER THE FIRE AREA WITHOUT PROPER PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS.			

SECTION 6 – ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: VENTILATE CLOSED SPACES BEFORE ENTERING. WEAR FULL PROTECTIVE EQUIPMENT (SEE SECTION 8). KEEP UNPROTECTED PERSONNEL OUT OF THE AREA. KEEP AWAY FROM HIGH HEAT AND ALL SOURCES OF IGNITION. MAINTAIN GOOD HOUSEKEEPING / CONTROL PIGMENT POWDER DUST CLOUD FORMATION TO PREVENT POSSIBLE DUST/AIR EXPLOSION HAZARD.

ENVIRONMENTAL PRECAUTIONS: AVOID RELEASE TO SEWERS, WATERWAYS AND THE ENVIRONMENT. DISPOSE OF PROPERLY VIA LICENSED CHEMICAL WASTEHAULER.

METHODS AND MATERIAL FOR CONTAINMENT AND CLEAN UP: VACUUM OR SCOOP INTO A PROPERLY LABELED CONTAINER AND SEAL FOR PROPER DISPOSAL. AVOID GENERATING DUST.

SECTION 7 – HANDLING & STORAGE

PRECAUTIONS FOR SAFE HANDLING: AVOID BREATHING DUST AND CONTACT WITH SKIN & EYES. WEAR FULL PROTECTIVE EQUIPMENT (SEE SECTION 8). USE WITH ADEQUATE VENTILATION. AVOID SCATTERING INTO THE AIR. AVOID RELEASE TO THE SEWER SYSTEM. EMPLOY GOOD HOUSEKEEPING TECHNIQUES TO CONTROL DUST BUILD-UP ON EQUIPMENT AND WORK AREA. AVOID DUSTING IN AREAS OF FLAME, SPARKS, & STATIC BUILDUP. PROPERLY GROUND PROCESSING / HANDLING EQUIPMENT. WASH THOROUGHLY AFTER HANDLING.

CONDITIONS FOR SAFE STORAGE, INCLUDING INCOMPATIBILITIES: STORE IN A SEALED CONTAINER IN A COOL, DRY, WELL-VENTILATED AREA. PREVENT FROM PHYSICAL SHOCK/DAMAGE. KEEP AWAY FROM DIRECT HEAT, DIRECT SUNLIGHT & SOURCES OF IGNTION.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

CONTROL PARAMETERS:

CONTROL FARAMETERO.	
EXPOSURE LIMITS: U.S. OSHA PEL :	NONE ESTABLISHED FOR PIGMENT; AS NUISANCE DUST OR PARTICULATES NOT OTHERWISE REGULATED: 15 mg/m ³ TWA TOTAL DUST, 5 mg/m ³ RESPIRABLE FRACTION
U.S. ACGIH TLV :	NONE ESTABLISHED FOR PIGMENT
APPROPRIATE ENGINEERING CONTROLS :	USE LOCAL / MECHANICAL EXHAUST TO MAINTAIN AIR CONCENTRATIONS BELOW OCCUPATIONAL EXPOSURE STANDARDS (SEE ABOVE)
PERSONAL PROTECTIVE EQUIPMENT:	
RESPIRATORY PROTECTION :	USE NIOSH APPROVED RESPIRATOR SUITABLE TO MEET PERMISSIBLE EXPOSURE LIMIT. SEE U.S. OSHA RESPIRATORY STANDARD (20 CFR 1910.134).
HAND PROTECTION :	USE CHEMICAL RESISTANT GLOVES (RUBBER, PVC)
EYE PROTECTION :	SAFETY GOGGLES OR GLASSES WITH SIDE SHIELDS OR FULL FACE SHIELD; ACCESS TO AN EYEWASH FOUNTAIN
OTHER PROTECTIVE EQUIPMENT :	LABCOAT; COVERALLS TO PROTECT SKIN; ACCESS TO A SAFETY DRENCH SHOWER

SECTION 9- PHYSICAL AND CHEMICAL PROPERTIES

ODOR : ODOR THRESHOLD : pH (10% IN WATER) : MELTING POINT / FREEZING POINT (°C) : BOILING POINT (°C) : FLASH POINT (°C) : EVAPORATION RATE :	YELLOW FINE POWDE NO ODOR N/A 6-8 360 (680ºF) N/A N/A N/A N/A N/A NO DATA AVAILABLE	ER FLAMMABLE LIMITS : VAPOR PRESSURE (mm Hg@25°C) : VAPOR DENSITY (AIR=1) : RELATIVE DENSITY/SPECIFIC GRAVITY : SOLUBILITY IN WATER (@20°C) : PARTITION COEFFICIENT(n-OCTANOLWATER) : AUTO IGNITION TEMP. (°C) : DECOMPOSITION TEMP. (°C) : VISCOSITY :	LEL:& UEL: (N/A) NOT KNOWN N/A 1.3 NEGLIGIBLE Log Kow = 4.12 NOT KNOWN NOT KNOWN N/A
--	---	---	--

SECTION 10 – STABILITY AND REACTIVITY

CHEMICAL STABILITY :STABLE WHEN STORED IN SEALED PACKAGE UNDER RECOMMENDED STORAGE CONDITIONSPOSSIBLITY OF HAZARDOUS REACTIONS :STABLE WHEN STORED IN SEALED PACKAGE UNDER RECOMMENDED STORAGE CONDITIONSCONDITIONS TO AVOID :CONTACT WITH INCOMPATIBLES; HIGH HEAT; DUST IN VICINITY OF IGNITION SOURCES,
ELECTRICAL OR SPARK GENERATING EQUIPMENTINCOMPATIBLE MATERIALS :STRONG OXIDIZING AGENTSHAZARDOUS DECOMPOSITION PRODUCTS :MAY INCLUDE TOXIC/ FLAMMABLE VAPORS, FUMES, SMOKE, CHLORINE. OXIDES OF CARBON
& NITROGEN

SECTION 11 – TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS:	SKIN, EYES, INHALATION, INGESTION
ROUTES OF EXPOSURE :	AS DUST, MAY CAUSE MECHANICAL IRRITATION TO SKIN, EYES, NOSE AND THROAT.
SKIN, EYES, INHALATION :	CONTACT WITH SKIN WILL CAUSE TEMPORARY COLORATION OF CONTACTED AREA.
INGESTION :	THIS ROUTE OF EXPOSURE IS NOT LIKELY. NO KNOWN EFFECTS.
CHRONIC :	NO KNOWN EFFECTS
ACUTE TOXICITY :	EXPECTED TO BE ORAL(RAT) LD ₅₀ :>5000 mg/kg – BASED ON TESTING OF SIMILAR PRODUCTS
SKIN CORROSION / IRRITATION :	NO TEST RESULTS AVAILABLE- NOT EXPECTED TO BE CLASSIFIED AN A GHS IRRITANT
SERIOUS EYE DAMAGE / IRRITATION :	NO TEST RESULTS AVAILABLE
RESPIRATORY OR SKIN SENSITIZATION :	NO TEST RESULTS AVAILABLE- NOT EXPECTED TO BE CLASSIFIED AN A GHS SENSITIZER
GERM CELL MUTAGENICITY :	NO TEST DATA AVAILABLE
CARCINOGENICITY :	U.S. LISTED CARCINOGEN: NONE (X) OSHA () NTP () IARC () OTHER ()
REPRODUCTIVE TOXICITY :	NO TEST DATA AVAILABLE
SPECIFIC TARGET ORGAN TOXICITY :	SINGLE: NONE KNOWN; REPEATED: NONE KNOWN
ASPIRATION HAZARD :	NO TEST DATA AVAILABLE
INTERACTIVE EFFECTS:	NO INFORMATION AVAILABLE

SECTION 12 – ECOLOGICAL INFORMATION

ECOTOXICITY :	AVOID RELEASE TO THE ENVIRONMENT AS THIS PRODUCT HAS NOT BEEN FULLY TESTED
TOXICITY - AQUATIC :	NO TEST DATA AVAILABLE
TOXICITY TO DAPHNIA :	NO TEST DATA AVAILABLE
TOXICITY - TERRESTIAL :	NO TEST DATA AVAILABLE
PERSISTANCE & DEGRADABILITY:	Log Kow = 4.12
BIOACCUMULATIVE POTENTIAL :	THE POTENTIAL FOR BIOCONCENTRATION IN AQUATIC ORGANISMS IS LOW (BCF10)
MOBILITY IN SOIL :	EXPECTED TO BE IMMOBILE IN SOIL
OTHER ADVERSE EFFECTS :	NO DATA AVAILABLE

SECTION 13 – DISPOSAL CONSIDERATIONS

DISPOSAL METHODS:

DISPOSE OF CONTENTS / CONTAINER IN ACCORDANCE WITH ALL LOCAL, REGIONAL, NATIONAL, INTERNATIONAL REGULATIONS. DISPOSE OF IN SEALED CONTAINERS, USING A LICENSED CHEMICAL WASTE HAULER.

SECTION 14 – TRANSPORT INFORMATION

BY ROAD OR RAIL - U.S. D.O. IF REGULATED, UN PROPE UN IDENTIFICATION NO.: U.S. MARINE POLLUTANT: EMERGENCY RESPONSE (INLAND B/L:	ER SHIPPING NA () YES ()		NO (X) PACKING GROUP: () SEVERE U.S. MARINE POLLU
BY SEA - IMDG REGULATED: BY AIR - IATA REGULATED: SPECIAL PRECAUTIONS:	YES ()	NO (X) NO (X) FORE HANDLING	STOWAGE CATEGORY: N/A PKG INSTRUCTION NO.: N/A

ROUP: () S. MARINE POLLUTANT: RQ: (N/A) HAZÀRD CLASS: () LABEL REQUIRED: () YES () NO (X)

SECTION 15 – REGULATORY INFORMATION

U.S. TSCA: WE CERTIFY THAT ALL COMPONENTS OF THIS PRODUCT ARE REGISTERED UNDER THE REGULATIONS OF THE TOXIC SUBSTANCES CONTROL ACT.

U.S. SARA TITLE III, SE	CT. 313 :	LISTED ()		NOT LISTED (X)
U.S. RCRA HAZARDOU	IS WASTE :	NO (X)	YES ()	RCRA # : ()
U.S. CERCLA :	NO (X)	YES ()	RQ ()	
U.S. CALIFORNIA PRO	POSITION 65	LISTED :	YES ()	NO (X)
HMIS: HEALTH ((1)	FLAMMABILIT	⁻ Y (1)	REACTIVITY (0)

SECTION 16 – OTHER INFORMATION

REVISION DATE: MAY 28, 2015 PREPARED BY: EHSA COORDINATOR / UNITED MINERAL & CHEMICAL CORP.

ABBREVIATIONS / ACRONYMS:N/A=NOT APPLICABLE; LEL=LOWER EXPLOSION LIMIT; UEL=UPPER EXPLOSION LIMIT;PEL=PERMISSIBLE EXPOSURE LIMIT; STEL=SHORT TERM EXPOSURE LIMIT; TLV=THRESHOLDLIMIT VALUE; TWA=TIME WEIGHTED AVERAGE OVER 8 HOUR WORKDAY; LD50 OR LC50=LETHALDOSE OR LETHAL CONCENTRATION THAT KILLS 50% OF DOSED GROUP; mg=MILLIGRAM; g=GRAM;kg=KILOGRAM; PPM=PARTS PER MILLION; m=METER; LOAEL=LOWEST OBSERVED ADVERSEEFFECT LEVEL; C.I.=COLOUR INDEX

IN ACCORDANCE WITH GOOD PRACTICES OF PERSONAL HYGIENE, HANDLE WITH DUE CARE AND AVOID ANY UNNECESSARY CONTACT WITH THIS PRODUCT. USE RECOMMENDED PERSONAL PROTECTION WHEN HANDLING (SEE SECTION 8).

THIS INFORMATION IS BEING SUPPLIED TO YOU UNDER OSHA "RIGHT TO KNOW" REGULATION 29 CFR 1910.1200 AND IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS PRODUCT SPECIFICATION. THE INFORMATION IS BELIEVED TO BE TRUE AND ACCURATE. NO WARRANTY, EXPRESSED OR IMPLIED, REGARDING THE ACCURACY OF THIS DATA, THE HAZARD CONNECTED WITH USE OF THE MATERIAL, OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, IS MADE. UNITED MINERAL & CHEMICAL CORPORATION AND ITS SUPPLIERS ASSUME NO RESPONSIBILITY FOR DAMAGE OR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN. UNITED MINERAL & CHEMICAL CORPORATION