



SAFETY DATA SHEET

Yellow Mortar Color

1. Identification

Product identifier

Product name Yellow Mortar Color

Product number MC52,MC58

Recommended use of the chemical and restrictions on use

Application Industrial color

Details of the supplier of the safety data sheet

Supplier Huntsman Pigments Americas LLC
P.O. Box 4980
The Woodlands, TX 77387
+1 301 210 3400 / +1 323 269 7311
MSDS@huntsman.com

Emergency telephone number

Emergency telephone CHEMTREC: (800) 424-9300 (Contract No: 191118)

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Carc. 1A - H350

Environmental hazards Not Classified

Label elements

Pictogram



Signal word Danger

Hazard statements H350 May cause cancer.

Precautionary statements P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313 If exposed or concerned: Get medical advice/attention.
P405 Store locked up.
P501 Dispose of contents/container in accordance with national regulations.

Contains CRYSTALLINE SILICA

3. Composition/information on ingredients

Mixtures

Yellow Mortar Color

CALCIUM CARBONATE	< 75
CAS number: 1317-65-3	REACH registration number: Proprietary
Classification Not Classified	
C.I. PIGMENT YELLOW 42	< 50
CAS number: 51274-00-1	REACH registration number: Proprietary
Classification Not Classified	
C.I. PIGMENT RED 101	< 15
CAS number: 1309-37-1	REACH registration number: Proprietary
Classification Not Classified	
Umber	< 3
CAS number: 12713-03-0	REACH registration number: Proprietary
Classification Not Classified	
CRYSTALLINE SILICA	<1%
CAS number: 14808-60-7	REACH registration number: Proprietary
Classification Carc. 1A - H350 STOT RE 2 - H373	

The Full Text for all Hazard Statements are Displayed in Section 16.

Composition comments 'Burnt Umbers' / 'Raw Umbers' Naturally occurring mixture of Fe₂O₃/MnxOy/SiO₂/Al₂O₃/H₂O

4. First-aid measures

Description of first aid measures

Inhalation	If exposed to excessive levels of dust or fumes, remove to fresh air. Get medical attention if cough or other symptoms develop.
Ingestion	Rinse mouth thoroughly with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed by medical personnel. Get medical attention if symptoms occur.
Skin Contact	Wash with soap and water. Get medical attention if irritation develops or persists.
Eye contact	Rinse with water. Get medical attention if any discomfort continues.

5. Fire-fighting measures

Extinguishing media

Yellow Mortar Color

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire. Extinguish with the following media: Water spray, foam, dry powder or carbon dioxide.

Special hazards arising from the substance or mixture

Flammability Class No Uniform Fire Code noted.

Advice for firefighters

Protective actions during firefighting As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Special protective equipment for firefighters Wear self-contained breathing apparatus as combustion may produce hazardous fumes.

6. Accidental release measures

Methods and material for containment and cleaning up

Methods for cleaning up If dust is generated, use appropriate respiratory protection. Vacuum or sweep up material and place in a disposal container. Avoid generation and spreading of dust. Large Spillages: Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Avoid runoff into storm sewers and ditches which lead to waterways.

7. Handling and storage

Precautions for safe handling

Usage precautions Minimize dust generation and accumulation. Do not breathe dust. Avoid contact with skin and eyes. Wash contaminated skin thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage precautions Store dry at ambient temperature away from food and beverages, excessive heat or flame sources (furnace, kilns, boilers etc.). Store away from substances subject to catalytic decomposition by dust, e.g. peroxides

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

C.I. PIGMENT RED 101

Long-term exposure limit (8-hour TWA): OSHA 10 mg/m³ fume
 Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust
 Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ respirable fraction
 Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m³ respirable fraction

A4

CRYSTALLINE SILICA

Long-term exposure limit (8-hour TWA): ACGIH 0.025 mg/m³ respirable fraction

A2

OSHA = Occupational Safety and Health Administration.

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

A2 = Suspected Human Carcinogen.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Yellow Mortar Color

Appearance	Dusty powder.
Color	Tan. to Red-brown.
Odor	Odorless.
Odor threshold	Not available.
pH	pH (diluted solution): 4-9 @10%
Melting point	> 1000 deg C / 1832 deg F
Initial boiling point and range	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Evaporation factor	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Not available.
Other flammability	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	Not available.
Bulk density	Not available.
Solubility(ies)	Insoluble in water.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Volatile organic compound	None.

10. Stability and reactivity

Reactivity	No information available.
Stability	No particular stability concerns.
Materials to avoid	Substances subject to catalytic decomposition caused by dust such as peroxides. Further avoid contact with aluminum dust, calcium hypochlorite, hydrazine, ethylene oxide, caesium carbide.

11. Toxicological information

Information on toxicological effects

Toxicological effects	No specific toxicity tests have been carried out on this product.
------------------------------	---

Yellow Mortar Color

Inhalation	Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases.
Ingestion	No harmful effects expected from quantities likely to be ingested by accident.
Skin Contact	Substance may cause slight skin irritation.
Eye contact	May cause slight irritation.

12. Ecological Information

Ecotoxicity	There are no data on the ecotoxicity of this product.
<u>Persistence and degradability</u>	
Persistence and degradability	The product is not readily biodegradable.
<u>Bioaccumulative potential</u>	
Bio-Accumulative Potential	Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.
Partition coefficient	Not available.
<u>Mobility in soil</u>	
Mobility	The product is insoluble in water.
<u>Results of PBT and vPvB assessment</u>	
Results of PBT and vPvB assessment	This product does not contain any substances classified as PBT or vPvB.
<u>Other adverse effects</u>	
Other adverse effects	None known.

13. Disposal considerations

Waste treatment methods

General information	Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.
----------------------------	---

14. Transport information

General	The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DoT).
----------------	--

Transport hazard class(es)

Transport labels

15. Regulatory information

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed or exempt.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None of the ingredients are listed or exempt.

SARA 313 Emission Reporting

Manganese Compound
1.0 %

Yellow Mortar Color

CAA Accidental Release Prevention

Manganese Compound
1.0 %

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

CRYSTALLINE SILICA

<1%

Massachusetts "Right To Know" List

C.I. PIGMENT YELLOW 42

Not listed.

C.I. PIGMENT RED 101

Present.

CRYSTALLINE SILICA

Present.

CALCIUM CARBONATE

Yes.

Umber

Not listed.

Rhode Island "Right To Know" List

C.I. PIGMENT YELLOW 42

Not listed.

C.I. PIGMENT RED 101

Present.

CRYSTALLINE SILICA

Present.

CALCIUM CARBONATE

Yes.

Umber

Not listed.

Minnesota "Right To Know" List

C.I. PIGMENT YELLOW 42

Not listed.

C.I. PIGMENT RED 101

Present.

CRYSTALLINE SILICA

Present.

CALCIUM CARBONATE

Yes.

Umber

Not listed.

New Jersey "Right To Know" List

C.I. PIGMENT YELLOW 42

Not listed.

Yellow Mortar Color

C.I. PIGMENT RED 101

Present.

CRYSTALLINE SILICA

Present.

CALCIUM CARBONATE

Yes.

Umber

Not listed.

Pennsylvania "Right To Know" List

C.I. PIGMENT YELLOW 42

Not listed.

C.I. PIGMENT RED 101

Present.

CRYSTALLINE SILICA

Present.

CALCIUM CARBONATE

Yes.

Umber

Not listed.

Inventories

EU - EINECS/ELINCS

EINECS

All the ingredients are listed or exempt.

Canada - DSL/NDSL

C.I. PIGMENT YELLOW 42

Domestic Substance List

C.I. PIGMENT RED 101

DSL

CRYSTALLINE SILICA

DSL

CALCIUM CARBONATE

Non Domestic Substance List

Umber

Domestic Substance List

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

No.

Australia - AICS

All the ingredients are listed or exempt.

Japan - MITI

Yellow Mortar Color

C.I. PIGMENT YELLOW 42

No.

C.I. PIGMENT RED 101

Yes

CRYSTALLINE SILICA

CALCIUM CARBONATE

No.

Umber

No.

Korea - KECI

All the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines - PICCS

All the ingredients are listed or exempt.

New Zealand - NZIOC

All the ingredients are listed or exempt.

16. Other information

Revision date	8/19/2015
Revision	2
Supersedes date	6/3/2015
SDS No.	21067
Hazard statements in full	H350 May cause cancer. H373 May cause damage to organs (Lungs) through prolonged or repeated exposure.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.