

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations Revision Date: 05/26/2015 Date of issue: 05/26/2015

Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Hoover 778BN

Product Code: 778BN

Synonyms: Synthetic Van Dyke Brown L.2. Intended Use of the Product

Use of the substance/mixture: Inorganic pigment used as a colorant in industrial, commercial, and consumer applications.

1.3. Name, Address, and Telephone of the Responsible Party

Company

Hoover Color Corporation 2170 Julia Simpkins Road P.O. Box 218 Hiwassee, VA 24347

www.hoovercolor.com

540-980-7233

1.4. Emergency Telephone Number

Emergency Number : 800-424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Classification (GHS-US)

Carc. 1A H350 STOT RE 1 H372

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US) : Danger

Hazard Statements (GHS-US) : H350 - May cause cancer (Inhalation).

H372 - Causes damage to organs (lung/respiratory system) through prolonged or

repeated exposure (Inhalation).

Precautionary Statements (GHS-US) : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe dust.

P264 - Wash hands, forearms and exposed areas thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P280 - Wear eye protection, protective clothing, protective gloves. P308+P313 - If exposed or concerned: Get medical advice/attention.

P314 - Get medical advice/attention if you feel unwell.

P405 - Store locked up.

P501 - Dispose of contents/container according to local, regional, national, and

international regulations.

2.3. Other Hazards

Other Hazards: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

05/26/2015 EN (English US) 1/6

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification (GHS-US)
Bituminous Coal	Not Applicable	45-55	Not classified
Talc	(CAS No) 14807-96-6	15 - 20	Not classified
Magnesium carbonate	(CAS No) 546-93-0	10 - 15	Not classified
Umber	(CAS No) 12713-03-0	7 - 10	Not classified
Sienna (Earth Minerals)	(CAS No) 1317-63-1	3 - 6	Not classified
Quartz, crystalline silica	(CAS No) 14808-60-7	0.4 – 0.8	Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

First-aid Measures After Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Rinse immediately with plenty of water. Remove contaminated clothing. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.

First-aid Measures After Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

First-aid Measures After Ingestion: Do NOT induce vomiting. Rinse mouth. Call a doctor/physician if any problems arise.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/Injuries: Repeated or prolonged inhalation may damage lungs. May cause cancer.

Symptoms/Injuries After Inhalation: Repeated exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis.

Symptoms/Injuries After Skin Contact: May cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause eye irritation.

Symptoms/Injuries After Ingestion: Ingestion is not likely to be harmful or have adverse effects.

Chronic Symptoms: May cause cancer by inhalation.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire. Application of water stream to hot product may cause frothing and increase fire intensity.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. **Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Other information: Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Avoid breathing dust.

6.1.1. For Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Stop leak if safe to do so. Eliminate ignition sources. Ventilate area.

05/26/2015 EN (English US) 2/6

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Products: Strong acids. Strong bases. Strong oxidizers.

7.3. Specific End Use(s)

Wood stains, paint, and coatings. For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

T 1- /4 4007 05 6\

Quartz (14808-60-7)		
USA ACGIH	ACGIH TWA (mg/m³)	0.025 mg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	0.05 mg/m³
USA IDLH	US IDLH (mg/m³)	50 mg/m ³
USA OSHA	OSHA PEL (STEL) (mg/m³)	250 mppcf/%SiO ₂ +5, 10mg/m ³ /%SiO ₂ +2

Talc (14807-96-6)		
USA ACGIH	ACGIH TWA (mg/m³)	2 mg/m³ (particulate matter containing no asbestos and <1%
		crystalline silica, respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	2 mg/m³ (containing no Asbestos and <1% Quartz-respirable dust)
USA IDLH	US IDLH (mg/m³)	1000 mg/m³ (containing no asbestos and <1% quartz)
Magnesium carbonate (546-93-0)		
USA NIOSH	NIOSH REL (TWA) (mg/m³)	10 mg/m³ (total dust)
		5 mg/m³ (respirable dust)
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust)
		5 mg/m³ (respirable fraction)
Particulates not otherwise classified (PNOC) (RR-00072-6)		
USA ACGIH	ACGIH TWA (mg/m³)	3 mg/m ³ Respirable fraction
		10 mg/m ³ Total Dust
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m ³ Respirable fraction
		15 mg/m ³ Total Dust

8.2. Exposure Controls

Appropriate Engineering Controls

: Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

Personal Protective Equipment

: Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.









Materials for Protective Clothing

: Chemically resistant materials and fabrics.

05/26/2015 EN (English US) 3/6

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hand Protection : Wear chemically resistant protective gloves.

Eye Protection : Chemical goggles or safety glasses. **Skin and Body Protection** : Wear suitable protective clothing.

Respiratory Protection : Use a NIOSH-approved respirator or self-contained breathing apparatus whenever

exposure may exceed established Occupational Exposure Limits.

Environmental Exposure Controls: Do not allow the product to be released into the environment.

Consumer Exposure Controls : Do not eat, drink or smoke during use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State : Solid

Appearance : Dark Brown Powder

Odor : None

Odor Threshold : No data available

pH : 7-8

Tap Density : 0.6 g/cm³

Melting Point: > 1000 °C (1832.00 °F)Freezing Point: No data availableBoiling Point: No data availableFlash Point: No data availableAuto-ignition Temperature: No data availableDecomposition Temperature: No data available

Flammability (solid, gas) : Combustible solid (Bituminous Coal)

Ignition in Air : ▶ 1,300° F (704° C)

Relative Vapor Density at 20 °C : No data available
Relative Density : No data available

Specific Gravity : 2.0
Solubility : Insoluble

Partition coefficient: n-octanol/water: No data availableViscosity: Not applicable

9.2. Other Information No additional information available

SECTION 10: STABILITY AND REACTIVITY

- **10.1 Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2 Chemical Stability: Stable under recommended handling and storage conditions (see section 7).
- 10.3 Possibility of Hazardous Reactions: Hazardous polymerization will not occur.
- **10.4** Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials.
- 10.5 Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.
- 10.6 Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Silicon oxides. Sulfur oxides (SO & SO₂). Methane.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects

Acute Toxicity: Not classified

Quartz (14808-60-7)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 5000 mg/kg

Skin Corrosion/Irritation: Not classified
Serious Eye Damage/Irritation: Not classified
Respiratory or Skin Sensitization: Not classified
Germ Cell Mutagenicity: Not classified

Carcinogenicity: May cause cancer (Inhalation).

Quartz (14808-60-7)	
IARC group	1
National Toxicity Program (NTP) Status	Known Human Carcinogens.

05/26/2015 EN (English US) 4/6

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): Causes damage to organs (lung/respiratory system) through prolonged or

repeated exposure (Inhalation). **Aspiration Hazard:** Not classified

Symptoms/Injuries After Inhalation: Repeated exposure to respirable (airborne) crystalline silica dust will cause lung damage in

the form of silicosis. Long term inhalation of coal dust may lead to the development of pneumoconiosis.

Symptoms/Injuries After Skin Contact: May cause skin irritation. **Symptoms/Injuries After Eye Contact:** May cause eye irritation.

Symptoms/Injuries After Ingestion: Ingestion is not likely to be harmful or have adverse effects.

Chronic Symptoms: May cause cancer by inhalation.

SECTION 12: ECOLOGICAL INFORMATION

12.1. **Toxicity**

Talc (14807-96-6)		
	LC50 Fish 1	> 100 g/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])

12.2. Persistence and Degradability: No additional information available

12.3. **Bioaccumulative Potential:** No additional information available

Talc (14807-96-6)	
BCF fish 1	(no known bioaccumulation)

12.4. Mobility in Soil No additional information available

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

Ecology – Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT Not regulated for transport 14.2 In Accordance with IMDG Not regulated for transport 14.3 In Accordance with IATA Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1 **US Federal Regulations**

Hoover 778BN	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard
Quartz (14808-60-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Umber (12713-03-0)	

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Sienna (1317-63-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Talc (14807-96-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Magnesium carbonate (546-93-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2 **US State Regulations**

Quartz (14808-60-7)	
U.S California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of
	California to cause cancer.

05/26/2015 EN (English US)

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Quartz (14808-60-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Talc (14807-96-6)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Magnesium carbonate (546-93-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List

15.3 INTERNATIONAL REGULATIONS:

EINECS (EU) All of the ingredients contained in this product are either listed or exempt. Those exemptions are in

accordance with (EC) No. 1907/2006, Article 2(7)(b), for naturally occurring ores.

DSL (Canada) All components of this blend are listed, including those listed by way of a naturally occurring ore. CEPA,

1999, Section 2.2.1.4.

China (IECSC) All ingredients are listed

Japan (METI) All ingredients are either listed, or exempt as naturally occurring minerals.

Australia (AICS) All ingredients are listed

Philippines (PICCS) All ingredients are listed or exempt as naturally occurring substances.

New Zealand (NZloC) All ingredients are listed; Limonite (1317-63-1) may be used as a component in a product covered by a

group standard, but it is not approved for use as a chemical in its own right.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date : 05/26/2015

 Other Information
 : This document has been prepared in accordance with the SDS

requirements of the OSHA Hazard Communication Standard 29 CFR

1910.1200.

GHS Full Text Phrases:

Carc. 1A	Carcinogenicity Category 1A
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H335	May cause respiratory irritation
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure

HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 0 Minimal Hazard
Physical : 0 Minimal Hazard

Personal Protection : E (Glasses, Gloves, & Dust Respirator)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)

05/26/2015 EN (English US) 6/6