

WG MIDSEASON

WIRELINER GREASE MIDSEASON

TEMPERATURE RANGE: -23°C TO -1°C (-10°F TO 30°F)

DESCRIPTION

WGMIDSEASON wireline lubricant and sealant affects a seal, reduces friction and provides protection against corrosion during high-pressure, wireline operations. Applied under pressure through a grease injection head, WGMIDSEASON penetrates to the inner core of the braided wireline to provide residual lubrication. WGMIDSEASON prevents well site contamination. The adhesive properties are ideal for minimizing drip and splatter. WGMIDSEASON contains inhibitors to protect against the corrosive effects of salt water, acids, caustics, and H₂S during the midseason months.

BENEFITS

- Maintains viscosity at temperature range
- Corrosion inhibitors for long range protection
- Protects corrosive effects of acids, caustics, salt water, and H₂S

TYPICAL OBSERVATIONS

Color	Yellow
Texture	Tacky Liquid
Odor	Mild
Density, lb/gal @ 77°F (25°C)	7.00–7.50
Specific Gravity Range, @ 77°F (25°C)	0.839–0.899
Flash Point, ASTM D-92	390°F (198°C)
Viscosity, Kinematic, cSt @ 40°C	175–185
Viscosity Index	115
Rust Preventive Test ASTM D-3603 @ 140°F (60°C)	Pass
Temperature Range	-10°F to 30°F (-23°C to -1°C)
Shelf Life (unopened container)	Two years

PACKAGING

- 5 gal (19 L)
- 55 gal (208 L)



7615 Edgar Industrial Drive | To re-order call (403) 356-1127
Red Deer, AB T4P 3R2 Canada

Made in U.S.A.