

WGS-S

WIRELINER GREASE SUMMER-SWEET

TEMPERATURE RANGE: 16°C TO 43°C (60°F TO 110°F)

DESCRIPTION

WGS-S was developed to meet the wireline industry's most demanding needs in warm temperatures. Unmatched in performance and protection against the corrosive effects of oilfield brines and chemicals, WGS-S is the answer for moderate well conditions where standard grade grease seal is required. WGS-S meets the needs for all braided line operations including logging, perforating, and pump down operations.

TYPICAL OBSERVATIONS

Color	Golden Yellow
Texture	Tacky Liquid
Odor	Mild
Density, lb/gal @ 77°F (25°C)	7.2-7.3
Specific Gravity @ 77°F (25°C)	0.87-0.88
Kinematic Viscosity	5,000
Flash Point, ASTM D-92	390°F (198°C)
Rust Preventive Test, ASTM D-3603 @ 140°F (60°C)	Pass
Shelf Life (unopened container)	Two years

BENEFITS

- **Cost effective**
- **Additive package**
- **Adhesive and cohesive properties**

PACKAGING

5 gal (19 L)
55 gal (208 L)
275 gal (1041 L)

APPLICATION

Recommended as a pump down grease for braided wireline, cables, and wire rope. Apply using grease injector control heads and cable lubricators.



7615 Edgar Industrial Drive | To re-order call (403) 356-1127
Red Deer, AB T4P 3R2 Canada

Made in U.S.A.