

// ORDER CODES

The order codes for RSB clamp-halves as well as for complete tube clamps incorporate the serial indication, material description and interior surface.

Example of description:

Clamp bodies

R	A	N	G	M	-	3	20	/	F
									Features F = Flame-protected CR = corrosion retardant e.g. Sh64° = 64°Shore
									Diameter
									Clamp size
									Version M = Multi, E = Noise protection insert, S = Square (Sensor), A = Different from the standard
									Interior surface R = Grooved, G = Smooth, E = Suitable for insert, A = Different from the standard
									Material P = Polypropylene, N = Polyamide, V = TPE, A = Aluminium, X = Stainless steel
									Series A = Light construction series, B = Twin-tube series, C = Heavy duty series, O = Tube clamps series O
Tube clamp									

Accessories / metal parts

AP	K	Z1	-	A	3	/	CRVIF
							Features Zn = zinc plated; CRVIF = chromium VI free; Phos = phosphated; /1.4571 = stainless steel / screws Mat. A4; /1.4301 = stainless steel / screws Mat. A2; AL = Aluminium; UNC = UNC thread
							Size or different measure (e.g. screws)
							Series A = Light construction series, B = Twin-tube series, C = Heavy duty series, O = Tube clamps series O
							Version Z1, Z2, Z3
							Types D = double, R = multiple, W = angle, M = multi, K = short, L = long/elongated
							Name AP = Weld plate, DP = Cover plate, TS = Mounting rail, SB = Locking plate, TM = Rail nut, TM-A/B = Visitec rail nut, US = Locking washer, SP = Locking plate, SL = Slotted head screw, SSL/SS = Hexagon head screw, IS = Hexagon socket head screw, AS = Stacking bolt, SBR = Locking plate

// Rubber for series A and B, inside smooth
 // Aluminium for series A size 0 to 6 and series C size 1 to 8
 // Smooth interior surface in series C to size 8, Aluminium clamps in a grooved design (R), Inside smooth series A size 1 to 8

Registration
 DNV-GL, Lloyd's Register of Shipping, Bureau Veritas, ABS (American Bureau of shipping)