



Novanex Model OAX2-24VP

24Volt / PoE Emergency Messaging LED Display/Clock

Our 24 volt Emergency Messaging Display / PoE Clock is visible from 150' (45.7m) in two line mode and 90' (27.4m) in single line mode, and displays the day, date, time and text on one or two lines. Send text from a web page or integrate to major mass notification providers. Made in the USA by Novanex, using US and imported components. 5 year warranty.

Specifications

LED Characteristics	16 x 96 pixel array; 3 colors (red, yellow, green) 5mm (.02") diameter, 7.62mm (.03") spacing
Case Material and Dimensions	Black powder-coated aluminum case, non-glare polycarbonate lens 7" H x 36" W x 1.75" D (17.8cm x 91.5cm x 4.5cm)
Weight	6 lbs.
Mounting	VESA 100mm tilt wall mount bracket included
Presentation Modes	Scroll up, ribbon left, disappear, others
Characters	Two-line mode: 2" height, 18 per line Single line mode: 4.1" height, 8 per line
Operating Environment	Temperature 32-104 F (0-40 C) Humidity: 95% max, non-condensing
Network Interface	10/100 BaseT Ethernet NIC, SSH configuration, DHCP or static addressing, MAC Address label with barcode
DHCP Support	Standard options; Option 42, 100
Operating Voltage	24V DC, 11 watts, pluggable terminal block
Timekeeping	SNTP, +/- 200ms