



Novanex Model ONTADS12-BK

**(2) Power-over-Ethernet (PoE) Analog Clocks Fully Assembled
Black Injection Molded ABS Plastic Cases
Powder-Coated Steel Mounting Ring**

Specifications

DIMENSIONS	ASSEMBLY: 12.3/4" (29.5cm) diameter; 4" (10.16 cm) depth
WEIGHT	7 lb (3.2 kg) including mounting ring
FEATURES	Auto DST adjustment, DHCP or Static IP addressable, monitoring system available; theft/earthquake resistant mounting slot, low power consumption, requires only one PoE cable
TIME SYNCHRONIZATION	SNTP (Simple Network Time Protocol); time server configurable
VIEWING DISTANCE	150+ feet (50+ meters)
OPERATING ENVIRONMENT	32-104 degrees F (0-40 C) 95% max humidity, non-condensing
ACCURACY	Within + / - 1 second
POWER CONSUMPTION	4 watts
TECHNICAL STANDARDS	ANSI/UL 60950-1, CAN/C22 IEEE 802. 3af-2003; IEEE 802.3 at (PoE+) 2009 ETL listed, CE marked
SUPPORT	https://support.novanexsolutions.com
WARRANTY	5 years
COUNTRY OF ORIGIN	USA