

Inova OnAlert®

A Visual Messaging Appliance for Emergency & Mass Notification Systems



Features

- Highly visible from over 150 feet (50 meters) providing excellent visual alerting in high noise environments
- Continuous emergency message retrieval from leading emergency notification systems:
 - Omnilert and e2Campus
 - Rave Mobile Safety
 - Blackboard Mass Notification
- Direct integrations to Simplex Grinnell and Honeywell Notifier fire panels
- Reliable and energy efficient Power over Ethernet (PoE) technology
- Connects through the cloud - no local server requirement
- Default date and time display
- Linux SSH security features built-in

Specifications

LED Characteristics	16x96 pixel array 3 colors (red, yellow, green) 5mm (0.2") diameter 7.62mm (0.3") spacing	Network Interface	10/100 BaseT Ethernet NIC; Scripting support; SSH configuration; DHCP or static IP addressing; MAC Address label with barcode
Case Dimensions	7"H x 36" W x 1.75" D (17.8cm x 91.5cm x 4.5 cm)	DHCP Support	Standard options; Option 42, 100
Weight	6 lbs	Operating Voltage Model OAX2-EC	IEEE 802.3af Power over Ethernet (PoE/ PoE+) compatible, 11 watts, RJ-45
Mounting	Tilt wall mount bracket, VESA 100mm incl	Operating Voltage Model OAX2-24V	24VDC, 11 Watts, pluggable terminal block
Presentation Modes	Scroll up, ribbon left, appear, others	Speaker	Volume: 74.5 dBA @ 1 meter
Characters	Two line mode: 2" height, 16 per line Single line mode: 4.1" height, 8 per line	Alerting Light	
Operating Environment	Temperature in degrees: 32 to 104 F (0 to 40 C) Humidity: 95% max, non-condensing	ENS Provider Integrations	e2Campus, Omnilert, RAVE Mobile Safety, Blackboard Mass Notification
Warranty	3 years standard	Certifications	UL/CSA 60950-1, ETL Listed, CE Marked, RoHS Compliant