



## MAGNETIC TANK BAGS

### GENERAL FEATURES AND ADVICE TO USERS

1. Always make sure, the tank is absolutely clean because even very fine particles can scratch the tank. Make sure you also clean the bottom of the tank bag before mounting it (traces of metal might have been attracted to the magnets)
2. Fitting instructions: Unclip the magnetic flap and hold the bag in a way that the headstock strap faces the headstock, set the bag gently on the tank making sure you adjust the position of the bag according to the shape of the tank.
3. Now simply pass the headstock strap around the headstock and clip together. This provides extra safety while riding.
4. Do not over load luggage at any time. Do not use the rucksack feature while riding the motorcycle, it may cause serious death or injury. If bungee cords are used to attach luggage make sure you check them often enough for regular wear and tear every time before riding .



### If your magnetic tank bag comes with Tail Bag attachment (This option is there only in few tank bag models).

Always fit your tail bag on the rear seat or passenger seat of a motorcycle. Make sure the surface is clean and dust free to avoid any kind of markings later on.

Unzip the detachable magnetic flap and fix the tail bag flap below the bag. Unclip the flaps from beneath and unlock or lift seat or passenger seat pad if any then pass the Velcro seat strap through the cuts provided in the fold out flaps (Figure 1). Secure the bag with the Velcro straps to go beneath the seat (Figure 2). Replace seat and lock in place.

Although bungee cords have been provided you might need to buy the suitable length of bungies to suit your motorcycle so the tail bag is secured well.

Ensure that two of the bungee cords provided, should pass through the fabric loops beneath the bag and form a cross (Figure 1) Next ensure that these bungee cords pass through the D rings provided on the flap. (Figure 3) Attach these bungee cords under tension to suitable secure parts of the motorcycle frame (Dedicated luggage hooks or foot rest).

Attach the balance four bungee cords to the top two D ring on each side of the bag and then pass through the lower D rings fixed on the folding flaps (Figure 3). Finally hook them to suitable secure parts of the Motorcycle frame.

Never stretch bungee beyond their elastic limit.

Make sure bungee is secured well and does not touch any moving part of the motorcycle as it might damage the motorcycle or paint. A secure fit is essential for riding safety.



Figure - 3



Figure - 1



Figure - 2

**LOADING:** Make sure the luggage is installed and loaded evenly and within the stated maximum capacity and weight limits. Do not carry sharp, pointed or flammable objects in the luggage. Always keep heavy articles at the bottom.

**FITMENT:** The luggage should be securely attached to the motorcycle and should be mounted clear off moving parts and sources of heat such as engine exhaust systems.

Make sure the motorcycle is clean and smooth while mounting the luggage to avoid any possibility of abrasion.

**PRODUCT CARE & USAGE:** To clean any dirt off your luggage use a wet sponge or cloth with a mild detergent on it. Do not use harsh chemicals. Extra precaution has to be taken with luggage that uses magnetic mountings as it might affect items containing magnetic data such as credit cards, film etc.

**WARRANTY:** All luggages are warranted to the original purchaser to be free of manufacturing defects for a period of 12 months. This warranty however does not extend to ancillary parts such as rain covers, bungee cords, buckles and rivets. Our liability extends to material and workmanship only.

This warranty is void if product failure is due to misuse, abuse, neglect, accident and improper installation. Also not covered are consequential damages, incidental damages or damage to person or property due to above factors. All warranties are covered only by an original proof of purchase. Your sale contract is with the dealership where the product was purchased and therefore it has to be returned there.