# Emu-Graph 7 Emulator CI 142

The Emu-Graph 7 chemical emulator strips are designed for use in pre-vacuum steam sterilizers operating at either 121°C for 20 minutes or 134°C for 7 minutes. In the presence of quality steam, the Emu-Graph 7 shows the attainment of proper sterilization conditions.





## **Key Features**

- 7 minutes at 134°C or 20 minutes at 121°C
- Sterilant specific must have steam to change
- Lead and toxic heavy metal free

## **Performance Characteristics**

The Emu-Graph 7 indicator changes color when exposed to steam sterilization conditions.

#### **Physical Characteristics**

Dimensions: L 89mm x W 18mm

#### **Color Change**

Purple to green

**Stated Values** (as determined in a steam resistometer)

- 7.5 min at 134°C
- 18.5 min at 121°C

## Storage

The storage conditions are printed on the product packaging. Store in the sealed bag provided

## **Shelf Life**

24 months from date of manufacture. The expiry date is printed on the product packaging

## **Standards Classification**

ISO 11140-1, Type 6

#### SteriTec Part No.

Cl 142, Emu-Graph 7 Emulator

Packaging

20 bags of 250



FTP-210 Rev. G

SteriTec Products Mfg. Co., Inc., Member of the Getinge Group 74 Inverness Drive East Englewood, CO 80112 USA

www.getinge.com/steritec