

“SuperPatch” Repair Patches

This perforation-resistant and highly elastic adhesive patching tape was designed for the specific purpose of patching holes and tears in plastic sheets.

- High adhesive strength, guaranteed leakproof seal
- Resistant to UV light
- Also works on textured materials
- Easy to cut to size
- Resistant to moisture, sand, salt, wind, and high temperatures

Item	Folien Reparatur-Klebeband
Materials	0.1 mm polyurethane film with 0.3 mm of adhesive
Thickness	0,40 mm
Protective sheet	Paper
Color	Matte transparent
Tensile strength	560 N/100 mm
Elongation at break	500 %
Maximum temperature	93°C (199.4 °F)
Available dimensions	7 cm x 1,0 m / 15 cm x 1 m (2.76 in x 39.4 in / 5.9 in x 39.4 in)
Application	Patching tape for plastic sheet products

Instructions:

- Clean any dirt, oils, and greases off of the surface the patch will be applied to and dry as far as possible.
- Cut a patch to the appropriate size and carefully remove the protective paper. Avoid touching the adhesive surface if possible. Place the patch over the spot to be repaired, making sure there is enough overlap. We recommend using at least 20 mm of overlapping material for larger holes or tears.
- Using a plastic squeegee or similar, apply pressure to the patch firmly and evenly (the harder you press, the faster the material will adhere to the surface).
- Allow to dry for a few minutes, then you're done.

Please note:

These adhesive repair patches are primarily designed for use on plastic sheets.

The values and applications cited above are based our experience and testing. Due to the wide variety of possible applications and different materials, we cannot give any guarantee that the product will work as it does in these specific conditions. You should always test the material on your own before attempting to use it. We can offer no guarantee for material that has already been handled and applied.