
4"LED SLIM PANEL DOWNLIGHT



Weight 320g Dimensions 4.7" x 0.5"



VOLTAGE



The Parmida LED Slim Panel Downlight is an ultra-thin recessed downlight with a remote driver junction box for quick, simple, and housing free installations. It's low profile design makes it the ideal solution for new construction or remodels projects without the requirement of a housing can. Since a housing can is not required, this light is ideal for shallow ceiling plenums. Constructed with a durable aluminum trim, this product is built with Steady-Dim technology and is compatible with most modern LED dimmers.







REPLACEMENT

LUMENS



ON

BUZZING



PRODUCT SPECIFICATIONS

	PLED-PDN9W27K	PLED-PDN9W3K
Wattage	9W	9W
Lumens	550lm	550lm
Voltage	100-130V AC	100-130V AC
Equivalent	90W	90W
Beam Angle	110°	110°
Dimmable	Yes	Yes
Material	Aluminum	Aluminum
CCT	2700K, Warm White	3000K, Soft White
CRI	>80	>80
LED Driver Type	DOB (Driver on Board)	DOB (Driver on Board)
Base type	Direct Wire	Direct Wire
Life	25,000 Hours	25,000 Hours
Efficiency	88%	88%
Certification	ES, ETL	ES, ETL
Warranty	5 Years	5 Years

HOURS

PLED-PDN9W4K	PLED-PDN9W5K
9W	9W
550lm	550lm
100-130V AC	100-130V AC
90W	90W
110 [°]	110 [°]
Yes	Yes
Aluminum	Aluminum
4000K, Cool White	5000K, Day Light
>80	>80
DOB (Driver on Board)	DOB (Driver on Board)
Direct Wire	Direct Wire
25,000 Hours	25,000 Hours
88%	88%
ES, ETL	ES, ETL
5 Years	5 Years
Direct Wire 25,000 Hours 88% ES, ETL	Direct Wire 25,000 Hours 88% ES, ETL