
LED WALL PACK LIGHT

PHOTOCELL COMPATIBLE



The Parmida LED Technologies™ LED Wall Pack is designed to efficiently illuminate any outdoor area with its impressive light performance. Constructed with a heat and shock-resistant borosilicate glass lens, as well as a rust and corrosion proof die-cast aluminum housing, this product will be protected against fade and wear and maintain its durability over time. Optional shade available to help lessen light pollution.

Weight 3800g





































INSTANT



BUZZING

Dimensions 5.5" x 3.5" x 8.2"

Intertek EAR

PRODUCT SPECIFICATIONS

	PLED-WP45W5000K	PLED-WP60W5000K	PLED-WP80W5000K	PLED-WP100W5000K
Wattage	45W	60W	80W	100W
Lumens	5400lm	7200lm	9600lm	12000lm
Voltage	100-277V AC	100-277V AC	100-277V AC	100-277V AC
Equivalent	150W MH	250W MH	350W MH	400W MH
Beam Angle	120° H X 90° V			
Dimmable	Yes. 1-10V	Yes. 1-10V	Yes. 1-10V	Yes. 1-10V
Material	Aluminium & Borosilicate Glass			
ССТ	5000K, Day Light	5000K, Day Light	5000K, Day Light	5000K, Day Light
CRI	>70	>70	>70	>70
LED Driver Type	Isolated Driver	Isolated Driver	Isolated Driver	Isolated Driver
Base type	Direct Wire	Direct Wire	Direct Wire	Direct Wire
Life	50,000 Hours	50,000 Hours	50,000 Hours	50,000 Hours
Efficiency	70%	76%	78%	80%
Certification	DLC, ETL	DLC, ETL	DLC, ETL	DLC, ETL
Warranty	5 Years	5 Years	5 Years	5 Years





LOCATION RATED

100-277V AC VOLTAGE

5400-12000 LUMENS







BEAM ANGLE

106 PARMIDA LED TECHNOLOGIES