



INSTALLATION GUIDE

4.5 INCH 5W LED RV LIGHT - 3CCT

PLED-RVPL-MCCT-5W

IMPORTANT: Please read carefully and save these instructions, as you may need them at a later date. When using electrical equipment, basic safety precautions should always be followed as below:

- 1. Before beginning installation, ensure power is turned off at the main breaker.
- 2. Ensure your eyes are properly protected

GENERAL: All electrical connections must be in accordance with local and National Electric Code (NEC) standards. All electrical connections, installation and service should be performed by a qualified licensed electrician.

READ AND FOLLOW BELOW SAFETY INSTRUCTIONS

To prevent wiring damage or abrasion do not expose wiring to edges of sheet metal or other sharp objects.

This light is dimmable. Please refer to our website for the most up-to-date compatible dimmer list.

Suitable for damp locations. For use in Recreational Vehicles. Use Class 2 Supply or 5A Fuse. DISCONNECT POWER BEFORE SERVICING.

REQUIRED TOOLS: (not included) Safety glasses and gloves, tape measure, screwdriver.

UNPACKING: Thoroughly inspect the fixture for freight damage. Freight damage should be reported to the delivery carrier.

SELECTING COLOR TEMPERATURE

To avoid risk of damage, ensure wall switch connected to the light is turned to off position before changing or selecting desired color temperature (CCT) on the selector switch. Select the color temperature via the CCT switch located on the face of the light when the lens has been removed. Using the color (CCT) selector switch, select the desired color temperature (3500K Neutral White, 4000K Cool White, 5000K Day Light).

USING A DIMMER

DIMMING

This light is compatible with a 12V PWM dimmer.

Dimming performance may depend on the dimmer, the dimmer range adjustment setting (for dimmers with brightness range adjustments), the wiring method, and/or the number of LED fixtures installed onto the dimmer circuit.

Before turning on the LED lights, set dimmer position at maximum before adjusting to a lower light level.

Please follow the Dimming Control Manufacturer's instructions for the installation of all dimming controls.

Please visit our website www.parmida.com or contact our customer support team for more details.

info@parmida.com www.parmida.com

STEPS FOR INSTALLATION


- 1. Disconnect the power before installing the light.
- Detach the cover from the base of the light by rotating it counterclockwise.
- 3. Connect the light's wires to the power source. Connect the white wire to the negative line and the black wire to the positive.
- 4. Mount the base of the light using the screws provided with the light.
- 5. Set the preferred color temperature using the switch on the base.
- 6. Replace the cover. Rotate cover clockwise to lock into place.






STEP 2






STEP 4




STEP 5



STEP 6

0



WARNING

RISK OF FIRE OR ELECTRIC SHOCK

DISCONNECT MAIN POWER AT FUSE OR CIRCUIT BREAKER BEFORE INSTALLING OR SERVICING THE LIGHT

DO NOT USE ANY OTHER DRIVER EXCEPT PARMIDA LIGHTING DRIVER THAT IS INCLUDED WITH THE FIXTURE.

info@parmida.com www.parmida.com