

MX4 Race Fuel

Safety Data Sheet

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : MX4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Fuel

1.3. Details of the supplier of the safety data sheet

Valor, LLC/DBA Renegade
1200 Alsop Lane
Owensboro, KY 42303
T 270-683-2461

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 3	H226
Flam. Liq. 2	H225
Skin Irrit. 2	H315
Repr. 2	H361
STOT SE 3	H335
STOT SE 3	H336
STOT RE 2	H373
Asp. Tox. 1	H304

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Hazard statements (GHS-US) :

: Danger
: H225 – Highly flammable Liquid and vapor
: H226 – Flammable liquid and vapor
: H304 - May be fatal if swallowed and enters airways
: H315 - Causes skin irritation
: H335 – May cause respiratory irritation
: H336 - May cause drowsiness or dizziness
: H361 - Suspected of damaging fertility or the unborn child
: H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

: P201 - Obtain special instructions before use
: P202 - Do not handle until all safety precautions have been read and understood
: P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
: P233 - Keep container tightly closed
: P240 - Ground/bond container and receiving equipment
: P241 - Use explosion-proof electrical/ventilating/lighting/equipment
: P242 - Use only non-sparking tools
: P243 - Take precautionary measures against static discharge
: P261 – Avoid breathing dust/fume/gas/mist/vapors/spray
: P264 - Wash thoroughly after handling
: P271 - Use only outdoors or in a well-ventilated area
: P273 - Avoid release to the environment
: P280 - Wear protective gloves/protective clothing/eye protection/face protection
: P301+P310 - IF SWALLOWED: immediately call a POISON CENTER or doctor/physician
: P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

MX4 Race Fuel

Safety Data Sheet

P304+P340 - IF INHALED: remove victim to fresh air and keep at rest in a position comfortable for breathing
P312 - Call a POISON CENTER/doctor/physician if you feel unwell
P331 - If swallowed, do NOT induce vomiting
P362 - Take off contaminated clothing and wash before reuse
P370+P378 - In case of fire: Use CO₂, dry chemical, foam (AFFF/ATC) or water spray for extinction
P391 - Collect spillage
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

Repeated exposure may cause skin dryness or cracking

Toxic to aquatic life with long lasting effects

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
2-Methoxy-2-Methylpropane	(CAS No) 1634-04-4	10 – 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315
Methyl Benzene	(CAS No) 108-88-3	10 – 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373
C9-C11 Isoalkanes	(CAS No) 68551-16-6	15 – 50	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304
1 – Hexene	(CAS No) 592-41-6	5 - 20	Flam. Liq. 2 H225 Asp. Tox 1, H304 STOT SE 3, H335 STOT SE 3 , H336

MX4 Race Fuel

Safety Data Sheet

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air. If not breathing, Do not use mouth to mouth method if victim ingested or inhaled the substance; give artificial respirations with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical advice. Get immediate medical attention.
- First-aid measures after skin contact : After contact with skin, wash immediately with plenty of water and soap. If skin reddening or irritation develops, seek medical attention.
- First-aid measures after eye contact : Immediately flush the eyes with plenty of water for at least 15 minutes while holding eyelids apart to ensure flushing of the entire surface of the eye. Continue flushing for an additional 15 minutes if a physician is not immediately available. Seek medical attention, preferably an ophthalmologist, immediately.
- First-aid measures after ingestion : If the material is swallowed, get immediate medical attention or advice. DO NOT induce vomiting unless directed to do so by medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Breathing high concentrations may be harmful. May cause central nervous system depression or effects. Symptoms may include headache, excitation, euphoria, dizziness, incoordination, drowsiness, light-headedness, blurred vision, fatigue, tremors, convulsions, loss of consciousness, coma, respiratory arrest and death, depending on the concentration and duration of exposure. Breathing high concentrations of this material, for example, in a confined space or by intentional abuse, can cause irregular heartbeats which can cause death.
- Symptoms/injuries after skin contact : Contact may cause reddening, itching and inflammation.
- Symptoms/injuries after eye contact : Contact may cause pain and severe reddening and inflammation of the conjunctiva. Effects may become more serious with repeated or prolonged contact.
- Symptoms/injuries after ingestion : May cause irritation of the mouth, throat and gastrointestinal tract. May cause central nervous system depression or effects. Symptoms may include salivation, pain, nausea, vomiting and diarrhea. Exposure may also cause central nervous system symptoms similar to those listed under "Inhalation"

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : CO₂, dry chemical, foam (AFFF/ATC) or water spray, dry sand, alcohol-resistant foam
- Unsuitable extinguishing media : Water may be ineffective

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable liquid and vapor.
- Hazardous Combustion Products : Carbon Monoxide (CO) Carbon dioxide (CO₂)
- Explosion hazard : In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. Vapors may travel long distances along ground before igniting/flashing back to vapor source.

5.3. Advice for firefighters

- Protection during firefighting : Firefighters should wear full protective gear.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Use personal protection equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulate in low areas

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment. Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

- For containment : If possible, stop flow of product.

MX4 Race Fuel

Safety Data Sheet

Methods for cleaning up : Small spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

Large spill: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillage into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Comply with all applicable EPA, OSHA, NFPA and consistent state and local requirements. Use appropriate grounding and bonding practices. Store in properly closed containers that are appropriately labeled and in a cool well-ventilated area. Do not expose to heat, open flames, strong oxidizers or other sources of ignition. Do not cut, drill, grind or weld on empty containers since they may contain explosive residues. Avoid skin contact. Exercise good personal hygiene including removal of soiled clothing and prompt washing with soap and water. Smoking, eating and drinking should be prohibited in the application area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

7.3. Specific end use(s)

Fuel

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-Methoxy-2-Methylpropane (1634-04-4)			
USA ACGIH	ACGIH TWA (ppm)	50 ppm	
Methyl Benzene (108-88-3)			
USA ACGIH	ACGIH TWA (ppm)	20 ppm	
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm	
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm	
1 – Hexene (592-41-6)			
ACGIH TLV	ACGIH TWA (ppm)	50 ppm	
C9-C11 Isoalkanes (68551-16-6)			
Basis	Value	Control Parameters	Note
Manufacturer	TWA	1,200 mg/m ³	RCP, Reciprocal Calculation procedure

MX4 Race Fuel

Safety Data Sheet

8.2. Exposure controls

Appropriate engineering controls	: Local exhaust and general ventilation must be adequate to meet exposure standards. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation locations
Hand protection	: Wear impervious gloves to minimize skin contact. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough
Eye protection	: Safety glasses. Wear splash goggles if splashing is likely. Eye wash bottle with pure water.
Skin and body protection	: Wear suitable working clothes. Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.
Respiratory protection	: If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Odor	: Strong hydrocarbon
Odor threshold	: No data available
pH	: Neutral
Relative evaporation rate (butylacetate=1)	: No data available
Initial Boiling point	: < 150°F
Flash point	: No data available
Self ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available

Relative vapor density at 20 °C	: 5
Specific gravity	: .740
Solubility	: Negligible.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 100 %
-------------	---------

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

Heat, flames, and other ignition sources.

10.5. Incompatible materials

Strong oxidizing agents.

MX4 Race Fuel

Safety Data Sheet

10.6. Hazardous decomposition products

Combustion produces carbon monoxide, aldehydes, aromatic and other hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful in contact with skin. Harmful if inhaled.

2-Methoxy-2-Methylpropane (1634-04-4)	
LD50 oral rat	4 g/kg
LD50 dermal rabbit	> 10000 mg/kg
LC50 inhalation rat (ppm)	23576 ppm/4h
ATE US (oral)	4000000.00000000 mg/kg

Methyl Benzene (108-88-3)	
LD50 oral rat	636 mg/kg
LD50 dermal rabbit	8390 mg/kg
LC50 inhalation rat (mg/l)	12.5 mg/l/4h
ATE US (oral)	636.00000000 mg/kg
ATE US (dermal)	8390.0

1-Hexene (592-41-6)	
LD50 oral rat	>5600 mg/kg
LC50 inhalation rat	32000 ppm /4h
LD50 Dermal rabbit	>2000 mg/kg

C9-C11 Isoalkanes (68551-16-6)	
LD50 oral rat	>5,000 mg/kg
LC50 Inhalation Rat	>4.9 mg/l 4 hr
LD50 Dermal rabbit	>5,000 mg/kg

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : May cause genetic defects.
Carcinogenicity : May cause cancer.

2-Methoxy-2-Methylpropane (1634-04-4)	
IARC group	3 - Not classifiable

Methyl Benzene (108-88-3)	
IARC group	3 - Not classifiable

1-Hexene (592-41-6)	
IARC	Not listed
NTP	Not listed
ACGIH	Not listed
OSHA	Not listed
Mexico	Not listed

C9-C11 Isoalkanes (68551-16-6)	
Repeated dose Toxicity	Species: Rat, male and female Application route: Inhalation Dose: 0,2600,5200,10400 mg/3 Exposure time: 13 wk Number of exposures: 6 h/d, 5 d/w NOEL: >10,400 mg/m ³ Method: OECD Test Guideline 413
Developmental Toxicity	Species: Rat Application Route: Inhalation Dose: 0,29,817 ppm Number of exposures: 6 h/d

MX4 Race Fuel

Safety Data Sheet

	Test period: GD 6-15 NOAEL Teratogenicity: >817 ppm NOAEL Maternal: >817 ppm
Aspiration Toxicity	May be fatal if swallowed and enters airways
Further information	Concentrations substantially above the TLV value may cause narcotic effects. Solvents may degrease the skin.

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness. Central nervous system (CNS)

Specific target organ toxicity (repeated exposure): May cause damage to organs through prolonged or repeated exposure. Affected organs include: blood, kidneys, reproductive system, liver, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Aspiration hazard : May be fatal if swallowed and enters airways.

Symptoms / effects, both acute and delayed : Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Other Adverse Effects : The toxicological properties have not been fully investigated.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

2-Methoxy-2-Methylpropane (1634-04-4)	
LC50 fish 1	672 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	542 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 1	> 800 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)
LC50 fish 2	929 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 other aquatic organisms 2	184 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
Methyl Benzene (108-88-3)	
LC50 fish 1	15.22 - 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	5.46 - 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 other aquatic organisms 1	> 433 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
LC50 fish 2	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 2	12.5 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata [static])
1-Hexene (592-41-6)	
EC50 Freshwater Algae	>1000 mg/L, 96 h (pseudokirchneriella subcapitata)
LC50 Freshwater fish	5.6 mg/L , 96 h (rainbow trout)
EC50 Water Flea	=30 mg/L, 48 h Static (Daphnia magna) =230 mg/L,, 48 h (Daphnia magna)
Microtox	Not listed
C9-C11 Isoalkanes (68551-16-6)	
LL50 fish	3.5 ml/l 96 h orcorhynchus mykiss (rainbow trout)
EL50 water flea	22 – 46 46 mg/l 48 h daphnia magna (water flea)
ErL50 Algae	>1,000 mg/l 72 H pseudokirchneriella subcapitata (algae)
NOELR	0.132 mg/l Oncorhynchus mykiss (rainbow trout)
Biodegradability	Aerobic 53% Testing period: 28 D

12.2. Persistence and degradability

MX4 Race Fuel

Safety Data Sheet

12.3. Bioaccumulative potential

2-Methoxy-2-Methylpropane (1634-04-4)	
BCF fish 1	(no bioaccumulation expected)
Log Pow	1.06 (at 23 °C)
Methyl Benzene (108-88-3)	
Log Pow	2.65
1-Hexene (592-41-6)	
Log Pow	3.39

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Waste disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations. Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional and national hazardous waste regulations to ensure complete and accurate classification.
- Product : The products should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
- Contaminated Packaging : Empty Remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on the empty drum.

SECTION 14: Transport information

In accordance with DOT

- Transport document description : UN1203 Gasoline includes gasoline mixed with ethyl alcohol, with not more than 10% alcohol, 3, II
- UN-No.(DOT) : 1203
- DOT NA no. : UN1203
- DOT Proper Shipping Name : Gasoline
includes gasoline mixed with ethyl alcohol, with not more than 10% alcohol
- Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Hazard labels (DOT) : 3 - Flammable liquid



- Packing group (DOT) : II - Medium Danger

MX4 Race Fuel

Safety Data Sheet

DOT Special Provisions (49 CFR 172.102)	: 144 - If transported as a residue in an underground storage tank (UST), as defined in 40 CFR 280.12, that has been cleaned and purged or rendered inert according to the American Petroleum Institute (API) Standard 1604 (IBR, see 171.7 of this subchapter), then the tank and this material are not subject to any other requirements of this subchapter. However, sediments remaining in the tank that meet the definition for a hazardous material are subject to the applicable regulations of this subchapter. 177 - Gasoline, or, ethanol and gasoline mixtures, for use in internal combustion engines (e.g., in automobiles, stationary engines and other engines) must be assigned to Packing Group II regardless of variations in volatility. B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. B33 - MC 300, MC 301, MC 302, MC 303, MC 305, MC 306, and DOT 406 cargo tanks equipped with a 1 psig normal vent used to transport gasoline must conform to Table I of this Special Provision. Based on the volatility class determined by using ASTM D 439 and the Reid vapor pressure (RVP) of the particular gasoline, the maximum lading pressure and maximum ambient temperature permitted during the loading of gasoline may not exceed that listed in Table I. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: E - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length, but is prohibited from carriage on passenger vessels in which the limiting number of passengers is exceeded.

SECTION 15: Regulatory information

15.1. US Federal regulations

2-Methoxy-2-Methylpropane (1634-04-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on SARA Section 313 (Specific toxic chemical listings)

EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	1.0 %

Methyl Benzene (108-88-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on SARA Section 313 (Specific toxic chemical listings)

Methyl Benzene (108-88-3)

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

1-Hexene (592-41-6)

TSCA 12(b)	Not Applicable
SARA 313	Not Applicable
CWA (Clean Water Act)	Not Applicable
Clean Air Act	Not Applicable
CERCLA	Not Applicable

SARA 311/312 Hazards	See section 2 for more information
California Proposition 65	This product does not contain any Proposition 65 Chemicals

C9-C11 Isoalkanes (68551-16-6)

SARA 311/312 Hazards	Flammable (gasses, aerosols, liquids, or solids)
CERCLA Reportable Quantity	This material does not contain any components with a CERCLA RQ
Sara 302 Reportable Quantity	This material does not contain any components with a SARA 302 RQ

MX4 Race Fuel

Safety Data Sheet

SARA 302 Threshold Planning Quantity	No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 304 Reportable Quantity	This material does not contain any components with a section 304 EHS RQ
SARA 13 Ingredients	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) report levels established by SARA Title III, Section 313.
Ozone-Depletion Potential	<p>This product neither contains, nor was manufactured with a class I or class II ODS as defined by the U.S. Clean Air Act Sections 602 (40 CFR 82, Subpt, A, App. A +B).</p> <p>This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Sections 112 (40 CFR 61).</p> <p>This product does not contain any chemicals listed on the U.S. Clean Air Act Section 112® FOR Accidental Release Prevention (40 CFR 68, 130, Subpart F).</p> <p>This product does not contain any chemical listed under the U.S. Clean Air Act section 111 SOCMII Intermediate or Final VOC's (40 CFR 60.489).</p>

15.2. US State regulations

Methyl Benzene (108-88-3)

U.S. – California - Proposition 65 - Carcinogens List	U.S. – California - Proposition 65 - Developmental Toxicity	U.S. – California - Proposition 65 - Reproductive Toxicity - Female	U.S. – California - Proposition 65 - Reproductive Toxicity – Male	No significance risk level (NSRL)
	Yes	Yes		

2-Methoxy-2-Methylpropane (1634-04-4)

U.S. - Massachusetts - Right To Know List
 U.S. - Minnesota - Hazardous Substance List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

Methyl Benzene (108-88-3)

U.S. - Massachusetts - Right To Know List
 U.S. - Minnesota - Hazardous Substance List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

1-Hexene (592-41-6)

U.S. - Massachusetts - Right To Know List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) Lists

C9-C11 Isoalkanes (68551-16-6)

U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

California Prop. 65 Ingredients: This product does not contain any chemical known to the State of California to cause cancer, Birth, or any other reproductive defects.

MX4 Race Fuel

Safety Data Sheet

SECTION 16: Other information

Full text of H-phrases:

Asp. Tox. 1	Aspiration hazard Category 1
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

Trade Secret Provision: *In accordance with OSHA regulations and policies, the specific percentages and specific names of certain chemicals are being designated a trade secret and are not disclosed herein. In compliance with current regulations, this SDS provides the necessary properties and effects of the chemicals listed for this product. In cases of medical emergency, medical personnel can contact the emergency number listed and obtain the specifics of these chemicals. Should this need arise, we will request the attending physician provide to us, at such time as appropriate, a letter stating the medical necessity and a signature of confidentiality for the obtained information.*