

DET2/2

Auto Earth Tester



- **High resolution - 1 mΩ - ideal for large earthing systems**
- **High accuracy for earth electrode and soil resistivity testing**
- **Test voltage 50 V max. for safety**
- **Rechargeable battery power with long battery life and rapid re-charge**
- **A robust, versatile instrument with IP54 protection**
- **Filter and high current features to enable valid earth testing in difficult situations**

DESCRIPTION

The Megger® DET2/2 Auto Earth Tester is a robust compact instrument designed for measuring earth electrode resistance and soil resistivity. It uses the four terminal method of measurement which eliminates the resistance of the current circuit from the measurement. The circuit design ensures that the resistance of the potential circuit does not affect the measurement during practical testing.

The instrument is microprocessor controlled and provides a flexible, 'user-friendly' approach to earth testing by giving good error detection capabilities and full test information on a large easily readable alpha-numeric display. A simple key pad can be used to adjust the test frequency, the test current level and the filtering so that adverse conditions influencing the test may be overcome. The display indicates if:-

- the noise interference in the soil passing the test current is excessive.
- the current test spike resistance is too high.
- the potential test spike resistance is too high.
- the battery needs recharging.

Because these factors are indicated directly the whole testing procedure is accomplished easily and more rapidly.

A wide band of test current frequencies, with a resolution of 0,5 Hz, may be used to eliminate errors caused by noise in the earth. The chosen test current frequency, test current level and the increased filtering option are stored in memory for use in subsequent tests.

The display can be set to show its information in the following languages:- English, French, German, Portuguese and Spanish.

The maximum output voltage is limited to 50 V for safety when performing a test and convenience when repositioning test spikes. The instrument is auto-ranging relieving the operator of any concern as to which resistance range to use. The low service error and an

IP 54 environmental specification enable accurate results to be obtained in 'unfriendly' testing conditions.

Power for the instrument is supplied from a rechargeable lead acid battery which gives 5 hours of life per charge, equivalent to six hundred individual tests lasting 30 seconds each.

The DET2/2 is built into a robust plastic case and has its four terminals, equipped for spade or 4 mm connectors, mounted on the front panel.

APPLICATION

The DET2/2 Earth Tester is a reliable instrument designed for larger or more complex earthing systems, including communications earthing systems and difficult testing environments. It may be used to test in accordance with BS 7430 (1991), the IEE Wiring Regulations and VDE 0413 part 7 (1982). The instrument is suitable for soil resistivity measurements, which are used to establish the optimum electrode design and site, as well as perform archeological and geological investigations.

Resistivity tests assist in the design of a correct earth system and avoid the cost of re-working electrode installations.

Earth testing kits, which include suitable test spikes and test leads, are available separately.

SPECIFICATION

Earth / ground resistance range	0,010 Ω to 19,99 kΩ (auto-ranging), 1 mΩ resolution.
Accuracy	(23 °C ± 2 °C) ±0,5% of reading ±2 digits
Error	±5% of reading ±2 digits ±10 mΩ (meets VDE service error over 50 mΩ)
Compliance	BS 7430 (1991) VDE 0413 Part 7 (1982)
Test frequency	105 to 160 Hz reversing d.c. (50 Hz operation default to 128 Hz, 60 Hz operation default to 150 Hz) Set in steps of 0,5 Hz
Test current range	50 mA max (selectable high and low levels)
Maximum output voltage	< 50 V r.m.s.
Interference	Typically 40 V peak-to-peak (50/60 Hz, sinusoidal nature)
Display	Alphanumeric L.C.D. (130 x 35 mm) giving test information and a large (20 mm) 3½-digit reading)
Temperature co-efficient	< ±0.1% per °C over the temperature range -10 to +40 °C 0,05% per °F from 14 to 104 °F
Operating temperature range and humidity	-10 to +40 °C (14 to 104 °F)
Storage temperature range and humidity	-20 to +60 °C (-4 to +140 °F)
IP rating	The instrument is waterproof to IP54
Flash test	3 kV ac
Voltage withstand	In the event of a system fault, the instrument will withstand 240 V a.c. applied between any two terminals.
Power supply	Internal Rechargeable, sealed lead-acid battery. 12 V (nominal), 2,6-Ah capacity. Battery voltage over which basic accuracy is maintained is 11,0 to 13,5 V.
Battery life	Approximately 5 hours continuous use.
Battery charge time	6 hours max. (from completely exhausted), charging current automatically controlled to stop over-charging. Charging supply required: 100 to 130 V or 200 to 260 V, 50/60 Hz.
Power consumption	9 W max. at 12 V
Safety	The instruments meet the requirements of IEC61010-1.
EMC	In accordance with IEC 61326 -1.
Dimensions	245 mm x 344 mm x 158 mm

Weight	5kg		
Maximum current spike (loop) resistance			
High	Low	Current (RC)	Current (RC)
Range (RE)			
0,010 to 0,499 Ω	5 kΩ	1 kΩ	
0,500 to 1,999 Ω	5 kΩ	3 kΩ	
2,000 to 19,99 Ω	10 kΩ	5 kΩ	
(over 20 Ω RC > 20 kΩ)			
Maximum potential spike (loop) resistance			
High	Low	Current (RP)	Current (RP)
Range (RE)			
0,010 to 0,499 Ω	11 kΩ	11 kΩ	
0,500 to 1,999 Ω	21 kΩ	11 kΩ	
2,000 to 19,99 Ω	21 kΩ	11 kΩ	
(over 20 Ω RP > 20 kΩ)			

ORDERING INFORMATION

Description	Order Code
Auto Earth Tester	DET2-2
Included Accessories	
Mains supply lead for battery charging	
Operating instruction book	6171-728
Optional Accessories	
Comprising carrying case and pouch containing: Four galvanised steel spikes ('L' shape) 10 mm dia. (0.4 in. dia. approx) x 350 mm (14 in. approx) long 30 m (98,5 ft approx) of cable on a winder 50 m (164 ft approx) of cable on a winder Two 3 m leads complete with connectors and clips Hammer	
Earth testing kit	6310-755
Reel of cable, 50 m [164 ft. approx]	6121-119
Professional grounding testing kit 2 x 50 m, 2 x 30 m, 4 auger stakes, tape measure, in hard carry case	6320-245
Terminal post to 4mm skt adaptor set (x4)	1007-036

UK
Archcliffe Road Dover
CT17 9EN England
T +44 (0) 1304 502101
F +44 (0) 1304 207342
UKsales@megger.com

UNITED STATES
4271 Bronze Way
Dallas TX 75237-1019 USA
T 800 723 2861 (USA only)
T +1 214 333 3201
F +1 214 331 7399
USsales@megger.com

OTHER TECHNICAL SALES OFFICES
Valley Forge USA, College Station USA,
Sydney AUSTRALIA, Danderyd SWEDEN,
Ontario CANADA, Trappes FRANCE,
Oberursel GERMANY, Aargau SWITZERLAND,
Kingdom of BAHRAIN, Mumbai INDIA,
Johannesburg SOUTH AFRICA, Chonburi THAILAND

CERTIFICATION ISO
Registered to ISO 9001:2000 Cert. no. Q 09290

DET22_DS_en_V13
www.megger.com
Megger is a registered trademark