

SOLITEX FRONTA WA

Highly permeable 3-ply wall lining membrane with monolithic TEEE membrane, suitable for closed façades



Technical data

		Substance
Protective and covering fleece		Polypropylene microfibre
Membrane		monolithic TEEE
Attribute	Regulation	Value
Colour		black
Surface weight	BS EN 1849-2	100 ±5 g/m ²
Thickness	BS EN 1849-2	0.45 ±0.05 mm
Water vapour resistance factor μ	BS EN ISO 12572	110
sd-value	BS EN ISO 12572	0.05 ±0.02 m
g-value		0.25 ±0.1 MN-s/g
Reaction to fire	BS EN 13501-1	E
Exposure time		3 months
Water column	BS EN 20811	10 000 mm
Water resistance un-/aged*	BS EN 1928	W1 / W1
Tensile strength MD/CD	BS EN 12311-1	210 ±20 N/5 cm / 140 ±20 N/5 cm
Tensile strength MD/CD aged*	BS EN 12311-1	190 ±20 N/5 cm / 120 ±20 N/5 cm
Elongation MD/CD	BS EN 12311-1	90 ±10 % / 90 ±10 %
Elongation MD/CD aged*	BS EN 12311-1	70 ±10 % / 70 ±10 %
Nail tear resistance MD/CD	BS EN 12310-1	110 ±20 N / 140 ±20 N
*) Artificial ageing by long term	BS EN 1297 / BS EN 1296	passed
Flexibility at low temperature	BS EN 1109	-40 °C ; -40 °F
Temperature resistance		-40 °C to +100 °C ; -40 °F to 212 °F
Thermal conductivity		0.17 W/(m·K)
CE labelling	BS EN 13859-2	available

Area of application

For making walls externally windproof. Installation on boarding, wood-based panels and all insulation mats and boards.

Forms of delivery

Art. no.	GTIN	Length	Width	Contents	Weight	PU	Container
10132	4026639010612	50 m	1.5 m	75 m ²	7.5 kg	1	20
10133	4026639010605	50 m	3 m	150 m ²	15 kg	1	20

Advantages

- ✓ Strong, 3-ply structure for protecting the wall structure
- ✓ Protective function as a result of non-porous functional membrane that actively manages moisture
- ✓ High nail tear resistance
- ✓ For use behind closed façades
- ✓ 3 months of outdoor exposure

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about application and construction is given in the pro clima planning documentation and application recommendations. If you have any questions, please call the pro clima technical hotline Ireland and UK:
Phone: +353 46 9432104
Fax: +353 46 9432435
info@ecologicalbuildingsystems.com

For Stockists contact
Ireland
T. 046 9432104
F. 046 9432435
UK
T. 01228 711 511
F. 01228 712 280

Ecological Building Systems
info@ecologicalbuildingsystems.com

www.ecologicalbuildingsystems.com



General conditions

SOLITEX FRONTA WA membranes can be laid flat either at right angles to or along the sub-structure without sagging. Horizontal installation is preferable with regard to water tightness during the construction phase.

The membrane must not be secured in areas where water collectively drains off.

The membrane can be used behind closed facades with at least 20 mm of rear ventilation.

Additional measures during the building phase (e.g. covering with tarpaulin) should be taken in the case of occupied buildings or buildings that need particular protection. Covering with tarpaulin should also be considered in the case of extended interruptions to work.



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about application and construction is given in the pro clima planning documentation and application recommendations. If you have any questions, please call the pro clima technical hotline Ireland and UK:
Phone: +353 46 9432104
Fax: +353 46 9432435
info@ecologicalbuildingsystems.com

For Stockists contact
Ireland
T. 046 9432104
F. 046 9432435
UK
T. 01228 711 511
F. 01228 712 280

Ecological Building Systems
info@ecologicalbuildingsystems.com

www.ecologicalbuildingsystems.com

