



Technical data

Substance		
Material	Butyl rubber	
Release film	siliconized paper	
Attribute	Regulation	Value
Colour		black
Thickness		1.0 mm
Exposure time		6 months, installed under the counter battens
Application temperature		5 °C to +35 °C ; 41 °F to 95 °F
Temperature resistance		permanent -40 °C to 80 °C ; -40 °F to 176 °F
Storage		cool and dry

Area of application

Nail sealing tape under counter battens for sloped roof structures.

In accordance with the Central Association of the German Roofing Trade (ZVDH), the use of nail sealing tapes in combination with "underlays/sarking membranes with seam and perforation protection" (SOLITEX connect variants) is a required additional measure in the case of "more demanding requirements" (e.g. if the roof pitch is less than the standard roof pitch).

If required, TESCON NAIDECK also serves as a suitable additional measure to create a temporary covering.

Forms of delivery

Art. no.	GTIN	Length	Width	Weight	PU	Container
11737	4026639117373	20 m	50 mm	1.35 kg	6	576
11943	4026639119438	20 m	50 mm	33 kg	1	24

Advantages

- ✓ Very good sealing action – liquid butyl adhesives penetrate deep into the lining structure
- ✓ Water resistant
- ✓ Suitable for temporary roof coverings as specified in the ZVDH product data sheet
- ✓ Extra-strong thanks to a reinforcing layer
- ✓ Contains no bitumen

Substrates

Before sticking, subsurfaces should be brushed off, wiped clean with a cloth or cleaned using compressed air.

Adhesion to frozen surfaces is not possible. There must be no water-repellent substances (e.g. grease or silicone) on materials to be bonded.

Subsurfaces must be sufficiently dry and have sufficient load-bearing capacity.

Lasting nail-tightness is achieved on all pro clima exterior membranes and other underlay/sarking and wall lining membranes (e.g. those made of PP and PET) as well as MDF board and softwood fibre sub-roof panels.

The best results in terms of structural stability are achieved on high-quality subsurfaces.

It is your responsibility to check the suitability of the subsurface; adhesion tests are recommended in certain cases.

Pretreatment with TESCON PRIMER RP is recommended in the case of subsurfaces with insufficient load-bearing capacity.

General conditions

Perforation seals will only be effective on roof lining, underlay or sarking membranes that have been installed with no folds or creases, using a double-sided adhesive tape.

Daytime and nighttime temperatures must be >5 °C / >41 °F when working with this product.

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about application and construction is given in the pro clima planning documentation and application recommendations. If you have any questions, please call the pro clima technical hotline Ireland and UK:
 Phone: +353 46 9432104
 Fax: +353 46 9432435
info@ecologicalbuildingsystems.com

For Stockists contact
Ireland
 T. 046 9432104
 F. 046 9432435
UK
 T. 01228 711 511
 F. 01228 712 280

Ecological Building Systems
info@ecologicalbuildingsystems.com

www.ecologicalbuildingsystems.com

