

# Declaration of performance

## Majcoat 200 8760-150050/300050

### Majcoat 200 SOB 8765-150050 – Vers.2.0

Nr. DoP-20-876-00

#### 1. Unique identification code of the product-type

8760-150050  
8760-300050  
8765-150050

#### 2. Product labeling

Majcoat 200  
Majcoat 200 SOB

#### 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer

Roof membrane and Facade membrane  
Flexible sheets for waterproofing - Underlays for discontinuous roofing - EN 13859-1:2014  
and for walls - EN 13859-2:2014

#### 4. Name and contact address of the manufacturer

SIGA Cover AG  
Rüt mattstrasse 7  
6017 Ruswil  
Switzerland

#### 5. Name of the authorized representative whose mandate covers the tasks specified in Article 12, Paragraph 2

-

#### 6. System of assessment and verification of constancy of performance of the construction product

AVCP System 3

#### 7. Notified body

TECHNICKY A SKUSOBNY USTAV STAVEBNY n.O.  
NB 1301  
Has carried out the assessment and verification according to system "3" and issued a test reports

#### 8. Declared Performance

Essential characteristics	Performance	Bottom tolerance	Top tolerance	Unit	Test Standard EN 13859-1:2014
Length	<b>50</b>	50	50.5	m	EN 1848-2
Width	<b>1500</b>	1497	1503	mm	EN 1848-2
	<b>3000</b>	2995	3005		
Mass per unit area	<b>198</b>	192	217	g/m <sup>2</sup>	EN 1849-2
Reaction to fire	<b>E</b>			class	EN 13501-1
Resistance to water penetration	<b>W1</b>			class	EN 1928
Water vapour transmission Sd-Value	<b>0.08</b>	0.02	0.14	m	EN 12572
Tensile property max. force (MD)	<b>390</b>	330	450	N/50mm	EN 12311-1

Tensile property max. force (CD)	<b>300</b>	240	350	N/50mm	EN 12311-1
Tensile property elongation (MD)	<b>70</b>	50	110	%	EN 12311-1
Tensile property elongation (CD)	<b>80</b>	50	110	%	EN 12311-1
Resistance to tearing (nail tearing) (MD)	<b>220</b>	170	300	N	EN 12310-1
Resistance to tearing (nail tearing) (CD)	<b>240</b>	200	330	N	EN 12310-1
Flexibility at low temperatures	<b>-40</b>			°C	EN 1109
Tensile property max. force (MD) after artificial ageing	<b>270</b>	245	360	N/50mm	EN 13859-1 Anh. C EN 12311-1
Tensile property max. force (CD) after artificial ageing	<b>200</b>	180	270	N/50mm	EN 13859-1 Anh. C EN 12311-1
Tensile property elongation (MD) after artificial ageing	<b>50</b>	35	100	%	EN 13859-1 Anh. C EN 12311-1
Tensile property elongation (CD) after artificial ageing	<b>55</b>	35	100	%	EN 13859-1 Anh. C EN 12311-1
Resistance to water penetration after artificial ageing	<b>W1</b>			class	EN 13859-1 Anh. C EN 1928
Hazardous substances	<b>none</b>				

**9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance (DOP) is issued under the sole responsibility of the manufacturer identified in point 4.**

**Signed for and on behalf of the manufacturer by:**

Seline Zürcher – Quality Management



Ruswil, 10.03.2023